



## XHTML Access Module

Module to enable generic document accessibility

W3C Editor's Draft 19 May 2008

This version:

<http://www.w3.org/MarkUp/2008/ED-xhtml-access-20080519>

Latest version:

<http://www.w3.org/TR/xhtml-access>

Previous version:

<http://www.w3.org/TR/2008/WD-xhtml-access-20080107>

Diff from previous version:

[xhtml-access-diff.html](#)

Editors:

Mark Birbeck, webBackplane [mark.birbeck@webBackplane.com](mailto:mark.birbeck@webBackplane.com)

Shane McCarron, Applied Testing and Technology, Inc.

Steven Pemberton, CWI/W3C®

T. V. Raman, Google, Inc.

Richard Schwerdtfeger, IBM Corporation

This document is also available in these non-normative formats: PostScript version, PDF version, ZIP archive, and Gzip'd TAR archive.

The English version of this specification is the only normative version. Non-normative translations may also be available.

Copyright © 2007-2008 W3C® (MIT, ERCIM, Keio), All Rights Reserved. W3C liability, trademark and document use rules apply.

---

## Abstract

The XHTML Access module defines an element that, when used in conjunction with other XHTML modules in XHTML Family Markup Languages, enables a more robust accessibility model than is presently possible.

## Status of This Document

*This section describes the status of this document at the time of its publication. Other documents may supersede this document. A list of current W3C publications and the latest revision of this technical report can be found in the W3C technical reports index at <http://www.w3.org/TR/>.*

This is a Last Call Working Draft produced by the XHTML 2 Working Group. It reflects a consensus among the Working Group members, in conjunction with input from the User Agent Accessibility Guidelines Working Group and others in the community. The Last Call review period extends through 16 June, 2008. The goals of the XHTML 2 Working Group are discussed in the XHTML 2 Working Group charter.

This document was produced by a group operating under the 5 February 2004 W3C Patent Policy. W3C maintains a public list of any patent disclosures made in connection with the deliverables of the group; that page also includes instructions for disclosing a patent. An individual who has actual knowledge of a patent which the individual believes contains Essential Claim(s) must disclose the information in accordance with section 6 of the W3C Patent Policy.

Publication as a Working Draft does not imply endorsement by the W3C Membership. This is a draft document and may be updated, replaced or obsoleted by other documents at any time. It is inappropriate to cite this document as other than work in progress.

Please report errors in this specification to [www-html-editor@w3.org](mailto:www-html-editor@w3.org) (archive). It is inappropriate to send discussion email to this address. Public discussion may take place on [www-html@w3.org](mailto:www-html@w3.org) (archive).

## Table of Contents

1. Introduction . . . . .	.5
2. Conformance Requirements . . . . .	.7
2.1. Document Conformance . . . . .	.7
2.2. Host Language Conformance . . . . .	.7
2.3. User Agent Conformance . . . . .	.8
3. XHTML Access Module . . . . .	.9
3.1. The access element . . . . .	.9
3.1.1. activate = ( yes   no* ) . . . . .	.9
3.1.2. key = Character . . . . .	.9
3.1.3. targetid = IDREFs . . . . .	10
3.1.4. targetrole = CURIEs . . . . .	10
A. Schema Implementation . . . . .	13
A.1. Access Element Module . . . . .	13
B. DTD Implementation . . . . .	15
B.1. Qualified Names Module . . . . .	15
B.2. Element Definition Module . . . . .	16

C. References . . . . .	19
C.1. Normative References . . . . .	19
C.2. Other References . . . . .	19
D. Acknowledgments . . . . .	21



# 1. Introduction

*This section is informative.*

This document contains a single module designed to be used to help make XHTML-family markup languages more effective at supporting the needs of the Accessibility Community. It has been developed in conjunction with the W3C's Web Accessibility Initiative and other interested parties. It provides a generic mechanism for defining the relationship between document components and well-known accessibility taxonomies.



## 2. Conformance Requirements

This section is *normative*.

The keywords "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC2119 [p.19] ].

Note that all examples in this document are informative, and are not meant to be interpreted as normative requirements.

### 2.1. Document Conformance

XHTML Access is not a stand-alone document type. It is intended to be integrated into other XHTML Family Markup Languages. A conforming XHTML Access document is a document that requires only the facilities described as mandatory in this specification and the facilities described as mandatory in its host language. Such a document must meet all the following criteria:

1. The document MUST conform to the constraints expressed in its host language implementation.
2. If the host language is not in the XHTML namespace, and the host language does not incorporate this module into its own namespace, then the document MUST contain an `xmlns:` declaration for the XHTML Access namespace [XMLNAMES [p.19] ]. The namespace for XHTML Access Module is defined to be `http://www.w3.org/1999/xhtml`. An example start tag of a root element might look like:

Example

```
<html xmlns="http://www.w3.org/1999/xhtml" xml:lang="en" >
```

### 2.2. Host Language Conformance

When XHTML Access is included in a host language, all of the facilities required in this specification MUST be included in the host language. In addition, the element defined in this specification MUST be included in the content model of the host language. The element defined in this specification MAY be incorporated into the namespace of the host language, or it MAY remain in the XHTML namespace. Finally, XHTML Access requires the availability of the XHTML Role Attribute Module [XHTMLROLE [p.19] ] and of the Core Attribute Collection as defined in XHTML Modularization [XHTMLMOD [p.19] ].

## 2.3. User Agent Conformance

A conforming user agent **MUST** support all of the features required in this specification.



## 3. XHTML Access Module

This section is *normative*.

This module defines the access element.

Element	Attributes	Minimal Content Model
access	Common, activate, key, targetid, targetrole	EMPTY

Implementations: XML Schema [p.13] , XML DTD [p.15]

### 3.1. The access element

The access element assigns an accessibility mapping to elements within a document. Actuating the mapping results in the element gaining focus (either the document focus or an inspection focus, as determined by the user agent), and, if set by the author and permitted by the user's settings, in one or more other events being activated.

An access element must have either a targetrole or a targetid attribute specified. If neither a targetrole nor a targetid attribute are specified, the user agent **MUST NOT** define a mapping nor deliver any events.

*Attributes*

#### 3.1.1. activate = ( yes | no\* )

The activate attribute indicates whether a target element should be activated or not once it obtains focus. The default value for this attribute is "no", indicating that the element will not be "activated". User agents **MUST** provide mechanisms for overriding the author setting with user-specified settings in order to ensure that the act of moving content focus does not cause the user agent to take any further action (as per Checkpoint 9.5 of UAAG 1.0 [UAAG1 [p.19] ]).

User agents **MUST** provide keyboard mechanisms for "activating" any event associated with the focused element (as per Checkpoint 1.2 of UAAG 1.0). User agents **SHOULD** make available the list of events associated with the focused element (as per Checkpoint 9.6 of UAAG 1.0).

#### 3.1.2. key = Character

This attribute assigns a key mapping to an access shortcut. An access key is a single character from the document character set.

Triggering the access key defined in an access element moves focus from its current position to the next element in navigation order that has one of the referenced role or id values (see activate for information on how the element may be activated). Note that it is possible to deliver alternate events via [XMLEVENTS [p.20] ].

The invocation of access keys depends on the implementation. For instance, on some systems one may have to press an "alt" or "cmd" key in addition to the access key.

User agents **MUST** provide mechanisms for overriding the author setting with user-specified settings in order to ensure that the act of moving content focus does not cause the user agent to take any further action, as required by UAAG 1.0, Checkpoint 9.5. [UAAG1 [p.19] ] The character assigned to a key, and its relationship to a role or id attribute **SHOULD** be treated as an author suggestion. User agents **MAY** override any key assignment (e.g., if an assignment interferes with the operation of the user interface of the user agent, if the key is not available on a device, if a key is used by the operating environment). User agents **MUST** also allow users to override author assigned keys with their own key assignments (see Checkpoint 11.3 of UAAG 1.0). If a user chooses to change the key binding, the resultant user-defined remapping **SHOULD** persist across sessions.

If no key attribute is specified, the user agent **SHOULD** assign a key and alert the user to the key mapping. The resultant user agent assigned key mapping **SHOULD** persist.

The rendering of access keys depends on the user agent. We recommend that authors include the access key character in label text or wherever the access key is to apply. If the user agent can recognize that the currently mapped access key character appears in the label text of the element to which it is mapped, then the user agent may render the character in such a way as to emphasize its role as the access key and distinguish it from other characters (e.g., by underlining it).

A conforming user agent **SHOULD** also provide a centralized view of the current access key assignments (see Checkpoint 11.1 and Checkpoint 11.2 of UAAG 1.0).

### 3.1.3. targetid = IDREFs

The targetid attribute specifies one or more IDREFs related to target elements for the associated event (i.e., the node to which the event should be delivered).

### 3.1.4. targetrole = CURIEs

The targetrole attribute specifies a space separated list of CURIEs [CURIE [p.19] ] that maps to an element with a role attribute with the same value.

If a targetid and a targetrole are both specified for an element, the targetid attribute value must take precedence.

If the prefix is omitted from a CURIE, the default value of `http://www.w3.org/1999/xhtml/vocab#` **MUST** be used.

Access element that focuses into a field

```
<access key="s"
  title="Social Security Number"
  targetrole="ss:number" />
```

### Accessing a table of contents

```
<access key="c"
  title="Table of Contents"
  targetrole="toc" />
```

### Access that moves to the main content

```
<access key="m"
  title="Main content"
  targetrole="main" />
```

### Access element that goes to a specific element

```
<access key="u"
  title="Username"
  targetid="username" />
```

### Access element with no specific key mapping

```
<access title="Navigation bar"
  targetrole="navigation" />
```



## A. Schema Implementation

This appendix is *informative*.

The schema implementation of XHTML Access Module conforms to the requirements defined in [XHTMLMOD [p.19] ]. It is included here as an example implementation.

### A.1. Access Element Module

```
<?xml version="1.0" encoding="UTF-8"?>
<xs:schema
  xmlns:xs="http://www.w3.org/2001/XMLSchema"
  elementFormDefault="qualified"
  xmlns:xh1ld="http://www.w3.org/1999/xhtml/datatypes/"
>
  <xs:import namespace="http://www.w3.org/1999/xhtml/datatypes/"
    schemaLocation="xhtml-datatypes-1.xsd" />

  <xs:annotation>
    <xs:documentation>
      This is the XML Schema module for XHTML Access
      $Id: xhtml-access-1.xsd,v 1.1 2008/04/11 19:56:12 ahby Exp $
    </xs:documentation>
    <xs:documentation source="xhtml-copyright-1.xsd"/>
    <xs:documentation source="http://www.w3.org/TR/xhtml-role#A_role"/>
  </xs:annotation>
  <xs:attributeGroup name="xhtml.access.attlist">
    <xs:attributeGroup ref="xhtml.Common.attrib"/>
    <xs:attribute name="activate" default="no">
      <xs:simpleType>
        <xs:restriction base="xs:NMTOKEN">
          <xs:enumeration value="yes"/>
          <xs:enumeration value="no"/>
        </xs:restriction>
      </xs:simpleType>
    </xs:attribute>
    <xs:attribute name="key" type="xh1ld:Character"/>
    <xs:attribute name="targetid">
      <xs:simpleType>
        <xs:list itemType="xs:IDREF"/>
      </xs:simpleType>
    </xs:attribute>
    <xs:attribute name="targetrole" type="xh1ld:CURIEs"/>
  </xs:attributeGroup>
  <xs:group name="xhtml.access.content">
    <xs:sequence/>
  </xs:group>
  <xs:complexType name="xhtml.access.type">
    <xs:group ref="xhtml.access.content"/>
    <xs:attributeGroup ref="xhtml.access.attlist"/>
  </xs:complexType>
</xs:schema>
```



## B. DTD Implementation

This appendix is *normative*.

The DTD implementation of XHTML Access Module conforms to the requirements defined in [XHTMLMOD [p.19] ]. Consequently, it provides a Qualified Names sub-module, and a module file for the XHTML Access Module defined in this specification.

### B.1. Qualified Names Module

```

<!-- ..... -->
<!-- XHTML Access QName Module ..... -->
<!-- file: xhtml-access-qname-1.mod

    This is XHTML Access - the Access Attribute Module for XHTML.

    Copyright 2007-2008 W3C (MIT, ERCIM, Keio), All Rights Reserved.

    This DTD module is identified by the PUBLIC and SYSTEM identifiers:

        PUBLIC "-//W3C//ENTITIES XHTML Access Attribute Qnames 1.0//EN"
        SYSTEM "http://www.w3.org/MarkUp/DTD/xhtml-access-qname-1.mod"

    Revisions:
    (none)
    ..... -->

<!-- XHTML Access Attribute QName (Qualified Name) Module

    This module is contained in two parts, labeled Section 'A' and 'B':

    Section A declares parameter entities to support namespace-
    qualified names, namespace declarations, and name prefixing
    for XHTML Access and extensions.

    Section B declares parameter entities used to provide
    namespace-qualified names for the XHTML access element:

        %XHTML-ACCESS.access.qname;    the xmlns-qualified name for access
        ...

    XHTML Access extensions would create a module similar to this one.
-->

<!-- Section A: XHTML Access Attribute XML Namespace Framework ::::::::::::::: -->

<!-- 1. Declare a %XHTML-ACCESS.prefixed; conditional section keyword, used
to activate namespace prefixing. The default value should
inherit '%NS.prefixed;' from the DTD driver, so that unless
overridden, the default behavior follows the overall DTD
prefixing scheme.
-->
<!ENTITY % NS.prefixed "IGNORE" >
<!ENTITY % XHTML-ACCESS.prefixed "%NS.prefixed;" >

```

```

<!-- 2. Declare a parameter entity (eg., %XHTML-ACCESS.xmlns;) containing
      the URI reference used to identify the XHTML Access Attribute namespace
-->
<!ENTITY % XHTML-ACCESS.xmlns "http://www.w3.org/1999/xhtml" >

<!-- 3. Declare parameter entities (eg., %XML.prefix;) containing
      the default namespace prefix string(s) to use when prefixing
      is enabled. This may be overridden in the DTD driver or the
      internal subset of a document instance. If no default prefix
      is desired, this may be declared as an empty string.

      NOTE: As specified in [XMLNAMES], the namespace prefix serves
      as a proxy for the URI reference, and is not in itself significant.
-->
<!ENTITY % XHTML-ACCESS.prefix "" >

<!-- 4. Declare parameter entities (eg., %XHTML-ACCESS.pfx;) containing the
      colonized prefix(es) (eg., '%XHTML-ACCESS.prefix;:') used when
      prefixing is active, an empty string when it is not.
-->
<![%XHTML-ACCESS.prefixed;[
<!ENTITY % XHTML-ACCESS.pfx "%XHTML-ACCESS.prefix;:" >
]]>
<!ENTITY % XHTML-ACCESS.pfx "" >

<!-- declare qualified name extensions here ..... -->
<!ENTITY % xhtml-access-qname-extra.mod "" >
%xhtml-access-qname-extra.mod;

<!-- 5. The parameter entity %XHTML-ACCESS.xmlns.extra.attrib; may be
      redeclared to contain any non-XHTML Access namespace
      declaration attributes for namespaces embedded in XML. The default
      is an empty string. XLink should be included here if used
      in the DTD.
-->
<!ENTITY % XHTML-ACCESS.xmlns.extra.attrib "" >

<!-- Section B: XML Qualified Names :::::::::::::::::::::::::::::::::::: -->

<!-- 6. This section declares parameter entities used to provide
      namespace-qualified names for the XHTML Access element.
-->

<!ENTITY % XHTML-ACCESS.access.qname "%XHTML-ACCESS.pfx;access" >

<!-- end of xhtml-access-qname-1.mod -->

```

## B.2. Element Definition Module

```

<!-- ..... -->
<!-- XHTML Access Module ..... -->
<!-- file: xhtml-access-1.mod

```

This is XHTML Access - the Access Module for XHTML.



Copyright 2007-2008 W3C (MIT, ERCIM, Keio), All Rights Reserved.

This DTD module is identified by the PUBLIC and SYSTEM identifiers:

```
PUBLIC "-//W3C//ELEMENTS XHTML Access Element 1.0//EN"
SYSTEM "http://www.w3.org/Markup/DTD/xhtml-access-1.mod"
```

Revisions:

(none)

..... -->

```
<!ENTITY % Character.datatype "CDATA" >
<!ENTITY % CURIEs.datatype "CDATA" >
<!ENTITY % IDREFs.datatype "CDATA" >

<!ENTITY % access.element "INCLUDE" >
<![%access.element;[
<!ENTITY % access.content "EMPTY" >
<!ENTITY % XHTML-ACCESS.access.qname "access" >
<!ELEMENT %XHTML-ACCESS.access.qname; %access.content; >
<!-- end of access.element -->]]>

<!ENTITY % access.attlist "INCLUDE" >
<![%access.attlist;[
<!ATTLIST %access.qname;
    %Common.attrib;
    activate      ( yes | no )          #IMPLIED
    key           %Character.datatype;  #IMPLIED
    targetid      %IDREFs.datatype;     #IMPLIED
    targetrole    %CURIEs.datatype;     #IMPLIED
>
<!-- end of access.attlist -->]]>

<!-- end of xhtml-access-1.mod -->
```



## C. References

This appendix is *normative*.

### C.1. Normative References

#### [CURIE]

"*CURIE Syntax 1.0*", W3C Working Draft, M. Birbeck, S. McCarron, *ed.*, 2 April 2008.

Available at: <http://www.w3.org/TR/2008/WD-curie-20080402/>

The latest version is available at: <http://www.w3.org/TR/curie>

#### [DOM2EVENTS]

"*Document Object Model (DOM) Level 2 Events Specification*", W3C Recommendation, T. Pixley, *ed.*, 13 November 2000.

Available at: <http://www.w3.org/TR/DOM-Level-2-Events/>

The latest version is available at: <http://www.w3.org/TR/DOM-Level-2-Events>

#### [IRI]

"*Internationalized Resource Identifiers (IRI)*", RFC 3987, M. Duerst, M. Suignard January 2005.

Available at: <http://www.ietf.org/rfc/rfc3987.txt>

#### [RFC2119]

"*Key words for use in RFCs to indicate requirement levels*", RFC 2119, S. Bradner, March 1997.

Available at: <http://www.rfc-editor.org/rfc/rfc2119.txt>

#### [XHTMLMOD]

"*Modularization of XHTML™ 1.1*", W3C Working Draft, D. Austin *et al.*, *eds.*, 5 July 2006.

Available at: <http://www.w3.org/TR/2006/WD-xhtml-modularization-20060705>

The latest version is available at: <http://www.w3.org/TR/xhtml-modularization>

#### [XMLNAMES]

"*Namespaces in XML*", W3C Recommendation, T. Bray *et al.*, *eds.*, 14 January 1999.

Available at: <http://www.w3.org/TR/1999/REC-xml-names-19990114>

The latest version is available at: <http://www.w3.org/TR/REC-xml-names>

#### [XHTMLROLE]

"*XHTML Role Attribute Module*", W3C Working Draft, M. Birbeck *et al.*, *eds.*, 7 April 2008.

Available at: <http://www.w3.org/TR/2008/WD-xhtml-role-20080407/>

The latest version is available at: <http://www.w3.org/TR/xhtml-role>

### C.2. Other References

#### [UAAG1]

"*User Agent Accessibility Guidelines 1.0*". Ian Jacobs *et al.*, 17 December 2002.

Available at: <http://www.w3.org/TR/2002/REC-UAAG10-20021217>

The latest version is available at: <http://www.w3.org/TR/UAAG10>

#### [XHTML2]

"*XHTML™ 2.0*". J. Axelsson *et al.*, 26 July 2006.

Available at: <http://www.w3.org/TR/2006/WD-xhtml2-20060726>

The latest version is available at: <http://www.w3.org/TR/xhtml2>

[XMLEVENTS]

"*XML Events*", W3C Recommendation, S. McCarron *et al.*, eds., 14 October 2003.

Available at: <http://www.w3.org/TR/2003/REC-xml-events-20031014>

## D. Acknowledgments

*This section is informative.*

At the time of publication, the participants in the W3C XHTML 2 Working Group were: