Document Object Model (DOM) Level 2 Style Specification

Version 1.0

W3C Recommendation *13 November, 2000*

This version:
http://www.w3.org/TR/2000/REC-DOM-Level-2-Style-20001113
(PostScript file , PDF file , plain text , ZIP file)
Latest version:
http://www.w3.org/TR/DOM-Level-2-Style
Previous version:
http://www.w3.org/TR/2000/PR-DOM-Level-2-Style-20000927

Editors:
Chris Wilson, *Microsoft Corp.*
Philippe Le Hégaret, *W3C, team contact (from November 1999)*
Vidur Apparao, *Netscape Communications Corp.*

Copyright © 2000 W3C® (MIT, INRIA, Keio), All Rights Reserved. W3C liability, trademark, document use and software licensing rules apply.

Abstract

This specification defines the Document Object Model Level 2 Style Sheets and Cascading Style Sheets (CSS), a platform- and language-neutral interface that allows programs and scripts to dynamically access and update the content and of style sheets documents. The Document Object Model Level 2 Style builds on the Document Object Model Level 2 Core [DOM Level 2 Core] and on the Document Object Model Level 2 Views [DOM Level 2 Views].

Status of this document

This section describes the status of this document at the time of its publication. Other documents may supersede this document. The latest status of this document series is maintained at the W3C.

This document has been reviewed by W3C Members and other interested parties and has been endorsed by the Director as a W3C Recommendation. It is a stable document and may be used as reference material or cited as a normative reference from another document. W3C's role in making the Recommendation is to draw attention to the specification and to promote its widespread deployment. This enhances the functionality and interoperability of the Web.

This document has been produced as part of the W3C DOM Activity. The authors of this document are the DOM Working Group members. Different modules of the Document Object Model have different editors.

Please send general comments about this document to the public mailing list www-dom@w3.org. An archive is available at http://lists.w3.org/Archives/Public/www-dom/.

The English version of this specification is the only normative version. Information about translations of this document is available at http://www.w3.org/2000/11/DOM-Level-2-translations.

The list of known errors in this document is available at http://www.w3.org/2000/11/DOM-Level-2-errata

A list of current W3C Recommendations and other technical documents can be found at http://www.w3.org/TR.

Table of contents

Expanded Table of Contents 3
Copyright Notice 5

Chapter 1: Document Object Model Style Sheets 9
Chapter 2: Document Object Model CSS 15

Appendix A: IDL Definitions 79
Appendix B: Java Language Binding 93
Appendix C: ECMAScript Language Binding 111
Appendix D: Acknowledgements 125
References 127
Index 129

Expanded Table of Contents

Expanded Table of Contents 3
Copyright Notice 5
W3C Document Copyright Notice and License 5
W3C Software Copyright Notice and License 6

Chapter 1: Document Object Model Style Sheets 9
1.1. Introduction 9
1.2. Style Sheet Interfaces 9
1.3. Document Extensions 13
1.4. Association between a style sheet and a document. 13
Chapter 2: Document Object Model CSS 15
2.1. Overview of the DOM Level 2 CSS Interfaces 15
2.2. CSS Fundamental Interfaces 15
2.2.1. Override and computed style sheet 37
2.2.2. Style sheet creation 38
2.2.3. Element with CSS inline style 39
2.3. CSS2 Extended Interface 40

Appendix A: IDL Definitions 79
A.1. Document Object Model Style Sheets 79
A.2. Document Object Model CSS 80
Appendix B: Java Language Binding 93
B.1. Document Object Model Style Sheets 93
B.2. Document Object Model CSS 94
Appendix C: ECMAScript Language Binding 111
C.1. Document Object Model StyleSheets 111
C.2. Document Object Model CSS 112
Appendix D: Acknowledgements 125
D.1. Production Systems 125
References 127
1. Normative references 127
2. Informative references 127
Index 129

Expanded Table of Contents

Copyright Notice

Copyright © 2000 World Wide Web Consortium, (Massachusetts Institute of Technology, Institut National de Recherche en Informatique et en Automatique, Keio University). All Rights Reserved.

This document is published under the W3C Document Copyright Notice and License [p.5] . The bindings within this document are published under the W3C Software Copyright Notice and License [p.6] . The software license requires "Notice of any changes or modifications to the W3C files, including the date changes were made." Consequently, modified versions of the DOM bindings must document that they do not conform to the W3C standard; in the case of the IDL definitions, the pragma prefix can no longer be 'w3c.org'; in the case of the Java Language binding, the package names can no longer be in the 'org.w3c' package.

W3C Document Copyright Notice and License

Note: This section is a copy of the W3C Document Notice and License and could be found at http://www.w3.org/Consortium/Legal/copyright-documents-19990405.

Copyright © 1994-2000 World Wide Web Consortium, (Massachusetts Institute of Technology, Institut National de Recherche en Informatique et en Automatique, Keio University). All Rights Reserved.

http://www.w3.org/Consortium/Legal/

Public documents on the W3C site are provided by the copyright holders under the following license. The software or Document Type Definitions (DTDs) associated with W3C specifications are governed by the Software Notice. By using and/or copying this document, or the W3C document from which this statement is linked, you (the licensee) agree that you have read, understood, and will comply with the following terms and conditions:

Permission to use, copy, and distribute the contents of this document, or the W3C document from which this statement is linked, in any medium for any purpose and without fee or royalty is hereby granted, provided that you include the following on *ALL* copies of the document, or portions thereof, that you use:

1. A link or URL to the original W3C document.
2. The pre-existing copyright notice of the original author, or if it doesn't exist, a notice of the form: "Copyright © [$date-of-document] World Wide Web Consortium, (Massachusetts Institute of Technology, Institut National de Recherche en Informatique et en Automatique, Keio University). All Rights Reserved. http://www.w3.org/Consortium/Legal/" (Hypertext is preferred, but a textual representation is permitted.)
3. *If it exists*, the STATUS of the W3C document.

When space permits, inclusion of the full text of this **NOTICE** should be provided. We request that authorship attribution be provided in any software, documents, or other items or products that you create pursuant to the implementation of the contents of this document, or any portion thereof.

No right to create modifications or derivatives of W3C documents is granted pursuant to this license. However, if additional requirements (documented in the Copyright FAQ) are satisfied, the right to create modifications or derivatives is sometimes granted by the W3C to individuals complying with those requirements.

THIS DOCUMENT IS PROVIDED "AS IS," AND COPYRIGHT HOLDERS MAKE NO REPRESENTATIONS OR WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, NON-INFRINGEMENT, OR TITLE; THAT THE CONTENTS OF THE DOCUMENT ARE SUITABLE FOR ANY PURPOSE; NOR THAT THE IMPLEMENTATION OF SUCH CONTENTS WILL NOT INFRINGE ANY THIRD PARTY PATENTS, COPYRIGHTS, TRADEMARKS OR OTHER RIGHTS.

COPYRIGHT HOLDERS WILL NOT BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF ANY USE OF THE DOCUMENT OR THE PERFORMANCE OR IMPLEMENTATION OF THE CONTENTS THEREOF.

The name and trademarks of copyright holders may NOT be used in advertising or publicity pertaining to this document or its contents without specific, written prior permission. Title to copyright in this document will at all times remain with copyright holders.

W3C Software Copyright Notice and License

Note: This section is a copy of the W3C Software Copyright Notice and License and could be found at http://www.w3.org/Consortium/Legal/copyright-software-19980720

Copyright © 1994-2000 World Wide Web Consortium, (Massachusetts Institute of Technology, Institut National de Recherche en Informatique et en Automatique, Keio University). All Rights Reserved.

http://www.w3.org/Consortium/Legal/

This W3C work (including software, documents, or other related items) is being provided by the copyright holders under the following license. By obtaining, using and/or copying this work, you (the licensee) agree that you have read, understood, and will comply with the following terms and conditions:

Permission to use, copy, and modify this software and its documentation, with or without modification, for any purpose and without fee or royalty is hereby granted, provided that you include the following on ALL copies of the software and documentation or portions thereof, including modifications, that you make:

1. The full text of this NOTICE in a location viewable to users of the redistributed or derivative work.
2. Any pre-existing intellectual property disclaimers. If none exist, then a notice of the following form: "Copyright © [$date-of-software] World Wide Web Consortium, (Massachusetts Institute of Technology, Institut National de Recherche en Informatique et en Automatique, Keio University). All Rights Reserved. http://www.w3.org/Consortium/Legal/."

3. Notice of any changes or modifications to the W3C files, including the date changes were made. (We recommend you provide URIs to the location from which the code is derived.)

THIS SOFTWARE AND DOCUMENTATION IS PROVIDED "AS IS," AND COPYRIGHT HOLDERS MAKE NO REPRESENTATIONS OR WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO, WARRANTIES OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE OR THAT THE USE OF THE SOFTWARE OR DOCUMENTATION WILL NOT INFRINGE ANY THIRD PARTY PATENTS, COPYRIGHTS, TRADEMARKS OR OTHER RIGHTS.

COPYRIGHT HOLDERS WILL NOT BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF ANY USE OF THE SOFTWARE OR DOCUMENTATION.

The name and trademarks of copyright holders may NOT be used in advertising or publicity pertaining to the software without specific, written prior permission. Title to copyright in this software and any associated documentation will at all times remain with copyright holders.

W3C Software Copyright Notice and License

1. Document Object Model Style Sheets

Editors
Chris Wilson, Microsoft Corp.
Philippe Le Hégaret, W3C
Vidur Apparao, Netscape Communications Corp.

1.1. Introduction

The DOM Level 2 Style Sheet interfaces are base interfaces used to represent any type of style sheet. The expectation is that DOM modules that represent a specific style sheet language may contain interfaces that derive from these interfaces.

The interfaces found within this section are not mandatory. A DOM application may use the `hasFeature(feature, version)` method of the `DOMImplementation` interface with parameter values "StyleSheets" and "2.0" (respectively) to determine whether or not this module is supported by the implementation. In order to fully support this module, an implementation must also support the "Core" feature defined defined in the DOM 2 Core specification [DOM Level 2 Core]. Please refer to additional information about *conformance* in the DOM Level 2 Core specification [DOM Level 2 Core].

1.2. Style Sheet Interfaces

This set of interfaces represents the generic notion of style sheets.

Interface *StyleSheet* (introduced in **DOM Level 2**)

The `StyleSheet` interface is the abstract base interface for any type of style sheet. It represents a single style sheet associated with a structured document. In HTML, the StyleSheet interface represents either an external style sheet, included via the HTML *LINK* element, or an inline *STYLE* element. In XML, this interface represents an external style sheet, included via a *style sheet processing instruction*.

IDL Definition

```
// Introduced in DOM Level 2:
interface StyleSheet {
  readonly attribute DOMString        type;
           attribute boolean          disabled;
  readonly attribute Node             ownerNode;
  readonly attribute StyleSheet       parentStyleSheet;
  readonly attribute DOMString        href;
  readonly attribute DOMString        title;
  readonly attribute MediaList        media;
};
```

Attributes

`disabled` of type `boolean`

`false` if the style sheet is applied to the document. `true` if it is not. Modifying this attribute may cause a new resolution of style for the document. A stylesheet only applies if both an appropriate medium definition is present and the disabled attribute is false. So, if the media doesn't apply to the current user agent, the `disabled` attribute is ignored.

`href` of type `DOMString`, readonly

If the style sheet is a linked style sheet, the value of its attribute is its location. For inline style sheets, the value of this attribute is `null`. See the *href attribute definition* for the `LINK` element in HTML 4.0, and the href pseudo-attribute for the XML *style sheet processing instruction*.

`media` of type `MediaList` [p.11] , readonly

The intended destination media for style information. The media is often specified in the `ownerNode`. If no media has been specified, the `MediaList` [p.11] will be empty. See the *media attribute definition* for the `LINK` element in HTML 4.0, and the media pseudo-attribute for the XML *style sheet processing instruction* . Modifying the media list may cause a change to the attribute `disabled`.

`ownerNode` of type `Node`, readonly

The node that associates this style sheet with the document. For HTML, this may be the corresponding `LINK` or `STYLE` element. For XML, it may be the linking processing instruction. For style sheets that are included by other style sheets, the value of this attribute is `null`.

`parentStyleSheet` of type `StyleSheet` [p.9] , readonly

For style sheet languages that support the concept of style sheet inclusion, this attribute represents the including style sheet, if one exists. If the style sheet is a top-level style sheet, or the style sheet language does not support inclusion, the value of this attribute is `null`.

`title` of type `DOMString`, readonly

The advisory title. The title is often specified in the `ownerNode`. See the *title attribute definition* for the `LINK` element in HTML 4.0, and the title pseudo-attribute for the XML *style sheet processing instruction*.

`type` of type `DOMString`, readonly

This specifies the style sheet language for this style sheet. The style sheet language is specified as a content type (e.g. "text/css"). The *content type* is often specified in the `ownerNode`. Also see the *type attribute definition* for the `LINK` element in HTML 4.0, and the type pseudo-attribute for the XML *style sheet processing instruction*.

Interface *StyleSheetList* (introduced in **DOM Level 2**)

The `StyleSheetList` interface provides the abstraction of an ordered collection of style sheets.

The items in the `StyleSheetList` are accessible via an integral index, starting from 0.

IDL Definition

```
// Introduced in DOM Level 2:
interface StyleSheetList {
  readonly attribute unsigned long    length;
  StyleSheet         item(in unsigned long index);
};
```

Attributes

`length` of type `unsigned long`, readonly

The number of `StyleSheets` [p.9] in the list. The range of valid child stylesheet indices is `0` to `length-1` inclusive.

Methods

`item`

Used to retrieve a style sheet by ordinal index. If index is greater than or equal to the number of style sheets in the list, this returns `null`.

Parameters

`index` of type `unsigned long`

Index into the collection

Return Value

`StyleSheet` [p.9]	The style sheet at the `index` position in the `StyleSheetList`, or `null` if that is not a valid index.

No Exceptions

Interface *MediaList* (introduced in **DOM Level 2**)

The `MediaList` interface provides the abstraction of an ordered collection of *media*, without defining or constraining how this collection is implemented. An empty list is the same as a list that contains the medium `"all"`.

The items in the `MediaList` are accessible via an integral index, starting from 0.

IDL Definition

```
// Introduced in DOM Level 2:
interface MediaList {
           attribute DOMString        mediaText;
                                        // raises(DOMException) on setting

  readonly attribute unsigned long    length;
  DOMString          item(in unsigned long index);
  void               deleteMedium(in DOMString oldMedium)
                                        raises(DOMException);
  void               appendMedium(in DOMString newMedium)
                                        raises(DOMException);
};
```

Attributes

`length` of type `unsigned long`, readonly

The number of media in the list. The range of valid media is `0` to `length-1` inclusive.

`mediaText` of type `DOMString`

The parsable textual representation of the media list. This is a comma-separated list of media.

Exceptions on setting

`DOMException`	SYNTAX_ERR: Raised if the specified string value has a syntax error and is unparsable. NO_MODIFICATION_ALLOWED_ERR: Raised if this media list is readonly.

Methods

`appendMedium`

Adds the medium `newMedium` to the end of the list. If the `newMedium` is already used, it is first removed.

Parameters

`newMedium` of type `DOMString`

The new medium to add.

Exceptions

`DOMException`	INVALID_CHARACTER_ERR: If the medium contains characters that are invalid in the underlying style language. NO_MODIFICATION_ALLOWED_ERR: Raised if this list is readonly.

No Return Value

`deleteMedium`

Deletes the medium indicated by `oldMedium` from the list.

Parameters

`oldMedium` of type `DOMString`

The medium to delete in the media list.

Exceptions

`DOMException`	NO_MODIFICATION_ALLOWED_ERR: Raised if this list is readonly. NOT_FOUND_ERR: Raised if `oldMedium` is not in the list.

No Return Value

`item`

Returns the `index`th in the list. If `index` is greater than or equal to the number of media in the list, this returns `null`.

Parameters

`index` of type `unsigned long`

Index into the collection.

Return Value

`DOMString`	The medium at the `index`th position in the `MediaList`, or `null` if that is not a valid index.

No Exceptions

1.3. Document Extensions

Interface *LinkStyle* (introduced in **DOM Level 2**)

The `LinkStyle` interface provides a mechanism by which a style sheet can be retrieved from the node responsible for linking it into a document. An instance of the `LinkStyle` interface can be obtained using binding-specific casting methods on an instance of a linking node (`HTMLLinkElement`, `HTMLStyleElement` or `ProcessingInstruction` in DOM Level 2).

IDL Definition

```
// Introduced in DOM Level 2:
interface LinkStyle {
  readonly attribute StyleSheet       sheet;
};
```

Attributes

`sheet` of type `StyleSheet` [p.9] , readonly

The style sheet.

Interface *DocumentStyle* (introduced in **DOM Level 2**)

The `DocumentStyle` interface provides a mechanism by which the style sheets embedded in a document can be retrieved. The expectation is that an instance of the `DocumentStyle` interface can be obtained by using binding-specific casting methods on an instance of the `Document` interface.

IDL Definition

```
// Introduced in DOM Level 2:
interface DocumentStyle {
  readonly attribute StyleSheetList   styleSheets;
};
```

Attributes

`styleSheets` of type `StyleSheetList` [p.10] , readonly

A list containing all the style sheets explicitly linked into or embedded in a document. For HTML documents, this includes external style sheets, included via the HTML *LINK* element, and inline *STYLE* elements. In XML, this includes external style sheets, included via style sheet processing instructions (see [XML-StyleSheet]).

1.4. Association between a style sheet and a document.

HTML and Style Sheet Creation

A style sheet can be associated with an HTMLDocument in one of two ways:

- By creating a new LINK HTML element (see the `HTMLLinkElement` interface in the [DOM Level 2 HTML] and [HTML4.0]). The underlying style sheet will be created after the element is

inserted into the document and both the href and the type attribute have been set in a way indicating that the linked object is a style sheet.

- By creating a new STYLE HTML element (see the `HTMLStyleElement` interface in the [DOM Level 2 HTML] and [HTML4.0]). The underlying style sheet will be created after the element is inserted into the document and the type attribute is set in a way indicating that the element corresponds to a style sheet language interpreted by the user agent.

HTML and Style Sheet Removal

Removing a LINK HTML element or a STYLE HTML element removes the underlying style sheet from the style sheet collection associated with a document. Specifically, the removed style sheet is no longer applied to the presentation of the document.

XML and Style Sheet Creation

A new style sheet can be created and associated with an XML document by creating a processing instruction with the target 'xml-stylesheet' [XML-StyleSheet] and inserting it into the document.

XML and Style Sheet Removal

Removing a processing instruction with a target of 'xml-stylesheet' [XML-StyleSheet] removes the underlying style sheet from the style sheet collection associated with a document. Specifically, the removed style sheet is no longer applied to the presentation of the document.

2. Document Object Model CSS

Editors
Chris Wilson, Microsoft Corp.
Philippe Le Hégaret, W3C
Vidur Apparao, Netscape Communications Corp.

2.1. Overview of the DOM Level 2 CSS Interfaces

The DOM Level 2 Cascading Style Sheets (CSS) interfaces are designed with the goal of exposing CSS constructs to object model consumers. Cascading Style Sheets is a declarative syntax for defining presentation rules, properties and ancillary constructs used to format and render Web documents. This document specifies a mechanism to programmatically access and modify the rich style and presentation control provided by CSS (specifically CSS level 2 [CSS2]). This augments CSS by providing a mechanism to dynamically control the inclusion and exclusion of individual style sheets, as well as manipulate CSS rules and properties.

The CSS interfaces are organized in a logical, rather than physical structure. A collection of all style sheets referenced by or embedded in the document is accessible on the document interface. Each item in this collection exposes the properties common to all style sheets referenced or embedded in HTML and XML documents; this interface is described in the Document Object Model Style Sheets [p.9] . User style sheets are not accessible through this collection, in part due to potential privacy concerns (and certainly read-write issues).

For each CSS style sheet, an additional interface is exposed - the `CSSStyleSheet` [p.16] interface. This interface allows access to the collection of rules within a CSS style sheet and methods to modify that collection. Interfaces are provided for each specific type of rule in CSS2 (e.g. style declarations, `@import` rules, or `@font-face` rules), as well as a shared generic `CSSRule` [p.18] interface.

The most common type of rule is a style declaration. The `CSSStyleRule` [p.20] interface that represents this type of rule provides string access to the CSS selector of the rule, and access to the property declarations through the `CSSStyleDeclaration` [p.24] interface.

Finally, an optional `CSS2Properties` [p.40] interface is described; this interface (if implemented) provides shortcuts to the string values of all the properties in CSS level 2.

All CSS objects in the DOM are "live", that is, a change in the style sheet is reflected in the computed and actual style.

2.2. CSS Fundamental Interfaces

The interfaces within this section are considered fundamental CSS interfaces, and must be supported by all conforming implementations of the CSS module. These interfaces represent CSS style sheets specifically.

A DOM application may use the `hasFeature(feature, version)` method of the `DOMImplementation` interface with parameter values "CSS" and "2.0" (respectively) to determine whether or not this module is supported by the implementation. In order to fully support this module, an implementation must also support the "Core" feature defined defined in the DOM Level 2 Core specification [DOM Level 2 Core] and the "Views" feature defined in the DOM Level 2 Views specification [DOM Level 2 Views]. Please refer to additional information about *conformance* in the DOM Level 2 Core specification [DOM Level 2 Core].

Interface *CSSStyleSheet* (introduced in **DOM Level 2**)

The `CSSStyleSheet` interface is a concrete interface used to represent a CSS style sheet i.e., a style sheet whose content type is "text/css".

IDL Definition

```
// Introduced in DOM Level 2:
interface CSSStyleSheet : stylesheets::StyleSheet {
  readonly attribute CSSRule          ownerRule;
  readonly attribute CSSRuleList      cssRules;
  unsigned long      insertRule(in DOMString rule,
                                in unsigned long index)
                                        raises(DOMException);
  void               deleteRule(in unsigned long index)
                                        raises(DOMException);
};
```

Attributes

`cssRules` of type `CSSRuleList` [p.17] , readonly

The list of all CSS rules contained within the style sheet. This includes both *rule sets* and *at-rules*.

`ownerRule` of type `CSSRule` [p.18] , readonly

If this style sheet comes from an `@import` rule, the `ownerRule` attribute will contain the `CSSImportRule` [p.23] . In that case, the `ownerNode` attribute in the `StyleSheet` [p.9] interface will be `null`. If the style sheet comes from an element or a processing instruction, the `ownerRule` attribute will be `null` and the `ownerNode` attribute will contain the `Node`.

Methods

`deleteRule`

Used to delete a rule from the style sheet.

Parameters

`index` of type `unsigned long`

The index within the style sheet's rule list of the rule to remove.

Exceptions

`DOMException`	INDEX_SIZE_ERR: Raised if the specified index does not correspond to a rule in the style sheet's rule list.
	NO_MODIFICATION_ALLOWED_ERR: Raised if this style sheet is readonly.

No Return Value

`insertRule`

Used to insert a new rule into the style sheet. The new rule now becomes part of the cascade.

Parameters

`rule` of type `DOMString`

The parsable text representing the rule. For rule sets this contains both the selector and the style declaration. For at-rules, this specifies both the at-identifier and the rule content.

`index` of type `unsigned long`

The index within the style sheet's rule list of the rule before which to insert the specified rule. If the specified index is equal to the length of the style sheet's rule collection, the rule will be added to the end of the style sheet.

Return Value

`unsigned long`	The index within the style sheet's rule collection of the newly inserted rule.

Exceptions

`DOMException`	HIERARCHY_REQUEST_ERR: Raised if the rule cannot be inserted at the specified index e.g. if an `@import` rule is inserted after a standard rule set or other at-rule. INDEX_SIZE_ERR: Raised if the specified index is not a valid insertion point. NO_MODIFICATION_ALLOWED_ERR: Raised if this style sheet is readonly. SYNTAX_ERR: Raised if the specified rule has a syntax error and is unparsable.

Interface *CSSRuleList* (introduced in **DOM Level 2**)

The `CSSRuleList` interface provides the abstraction of an ordered collection of CSS rules.

The items in the `CSSRuleList` are accessible via an integral index, starting from 0.

IDL Definition

```
// Introduced in DOM Level 2:
interface CSSRuleList {
  readonly attribute unsigned long    length;
  CSSRule             item(in unsigned long index);
};
```

Attributes

`length` of type `unsigned long`, readonly

The number of `CSSRules` [p.18] in the list. The range of valid child rule indices is `0` to `length-1` inclusive.

Methods

`item`

Used to retrieve a CSS rule by ordinal index. The order in this collection represents the order of the rules in the CSS style sheet. If index is greater than or equal to the number of rules in the list, this returns `null`.

Parameters

`index` of type `unsigned long`

Index into the collection

Return Value

`CSSRule` [p.18]	The style rule at the `index` position in the `CSSRuleList`, or `null` if that is not a valid index.

No Exceptions

Interface *CSSRule* (introduced in **DOM Level 2**)

The `CSSRule` interface is the abstract base interface for any type of CSS *statement*. This includes both *rule sets* and *at-rules*. An implementation is expected to preserve all rules specified in a CSS style sheet, even if the rule is not recognized by the parser. Unrecognized rules are represented using the `CSSUnknownRule` [p.24] interface.

IDL Definition

```
// Introduced in DOM Level 2:
interface CSSRule {

  // RuleType
  const unsigned short      UNKNOWN_RULE                  = 0;
  const unsigned short      STYLE_RULE                    = 1;
  const unsigned short      CHARSET_RULE                  = 2;
  const unsigned short      IMPORT_RULE                   = 3;
  const unsigned short      MEDIA_RULE                    = 4;
  const unsigned short      FONT_FACE_RULE                = 5;
  const unsigned short      PAGE_RULE                     = 6;

  readonly attribute unsigned short   type;
           attribute DOMString        cssText;
                                        // raises(DOMException) on setting

  readonly attribute CSSStyleSheet    parentStyleSheet;
  readonly attribute CSSRule          parentRule;
};
```

Definition group *RuleType*

An integer indicating which type of rule this is.

Defined Constants

`CHARSET_RULE`
: The rule is a `CSSCharsetRule` [p.23] .

`FONT_FACE_RULE`
: The rule is a `CSSFontFaceRule` [p.22] .

`IMPORT_RULE`
: The rule is a `CSSImportRule` [p.23] .

`MEDIA_RULE`
: The rule is a `CSSMediaRule` [p.20] .

`PAGE_RULE`
: The rule is a `CSSPageRule` [p.22] .

`STYLE_RULE`
: The rule is a `CSSStyleRule` [p.20] .

`UNKNOWN_RULE`
: The rule is a `CSSUnknownRule` [p.24] .

Attributes

`cssText` of type `DOMString`
: The parsable textual representation of the rule. This reflects the current state of the rule and not its initial value.

Exceptions on setting

`DOMException`	SYNTAX_ERR: Raised if the specified CSS string value has a syntax error and is unparsable. INVALID_MODIFICATION_ERR: Raised if the specified CSS string value represents a different type of rule than the current one. HIERARCHY_REQUEST_ERR: Raised if the rule cannot be inserted at this point in the style sheet. NO_MODIFICATION_ALLOWED_ERR: Raised if the rule is readonly.

`parentRule` of type `CSSRule` [p.18] , readonly
: If this rule is contained inside another rule (e.g. a style rule inside an @media block), this is the containing rule. If this rule is not nested inside any other rules, this returns `null`.

`parentStyleSheet` of type `CSSStyleSheet` [p.16] , readonly
: The style sheet that contains this rule.

`type` of type `unsigned short`, readonly
: The type of the rule, as defined above. The expectation is that binding-specific casting methods can be used to cast down from an instance of the `CSSRule` interface to the specific derived interface implied by the `type`.

Interface *CSSStyleRule* (introduced in **DOM Level 2**)

The `CSSStyleRule` interface represents a single *rule set* in a CSS style sheet.

IDL Definition

```
// Introduced in DOM Level 2:
interface CSSStyleRule : CSSRule {
           attribute DOMString        selectorText;
                                        // raises(DOMException) on setting

  readonly attribute CSSStyleDeclaration  style;
};
```

Attributes

`selectorText` of type `DOMString`
: The textual representation of the *selector* for the rule set. The implementation may have stripped out insignificant whitespace while parsing the selector.
Exceptions on setting

`DOMException`	SYNTAX_ERR: Raised if the specified CSS string value has a syntax error and is unparsable. NO_MODIFICATION_ALLOWED_ERR: Raised if this rule is readonly.

`style` of type `CSSStyleDeclaration` [p.24] , readonly
: The *declaration-block* of this rule set.

Interface *CSSMediaRule* (introduced in **DOM Level 2**)

The `CSSMediaRule` interface represents a *@media rule* in a CSS style sheet. A `@media` rule can be used to delimit style rules for specific media types.

IDL Definition

```
// Introduced in DOM Level 2:
interface CSSMediaRule : CSSRule {
  readonly attribute stylesheets::MediaList  media;
  readonly attribute CSSRuleList      cssRules;
  unsigned long      insertRule(in DOMString rule,
                                in unsigned long index)
                                        raises(DOMException);
  void               deleteRule(in unsigned long index)
                                        raises(DOMException);
};
```

Attributes

`cssRules` of type `CSSRuleList` [p.17] , readonly
: A list of all CSS rules contained within the media block.

`media` of type `stylesheets::MediaList`, readonly
A list of *media types* for this rule.

Methods

`deleteRule`
Used to delete a rule from the media block.

Parameters

`index` of type `unsigned long`
The index within the media block's rule collection of the rule to remove.

Exceptions

`DOMException`	INDEX_SIZE_ERR: Raised if the specified index does not correspond to a rule in the media rule list. NO_MODIFICATION_ALLOWED_ERR: Raised if this media rule is readonly.

No Return Value

`insertRule`
Used to insert a new rule into the media block.

Parameters

`rule` of type `DOMString`
The parsable text representing the rule. For rule sets this contains both the selector and the style declaration. For at-rules, this specifies both the at-identifier and the rule content.

`index` of type `unsigned long`
The index within the media block's rule collection of the rule before which to insert the specified rule. If the specified index is equal to the length of the media blocks's rule collection, the rule will be added to the end of the media block.

Return Value

`unsigned long`	The index within the media block's rule collection of the newly inserted rule.

Exceptions

`DOMException`	HIERARCHY_REQUEST_ERR: Raised if the rule cannot be inserted at the specified index, e.g., if an `@import` rule is inserted after a standard rule set or other at-rule. INDEX_SIZE_ERR: Raised if the specified index is not a valid insertion point. NO_MODIFICATION_ALLOWED_ERR: Raised if this media rule is readonly. SYNTAX_ERR: Raised if the specified rule has a syntax error and is unparsable.

Interface *CSSFontFaceRule* (introduced in **DOM Level 2**)

The `CSSFontFaceRule` interface represents a *@font-face rule* in a CSS style sheet. The `@font-face` rule is used to hold a set of font descriptions.

IDL Definition

```
// Introduced in DOM Level 2:
interface CSSFontFaceRule : CSSRule {
  readonly attribute CSSStyleDeclaration  style;
};
```

Attributes

`style` of type `CSSStyleDeclaration` [p.24] , readonly

The *declaration-block* of this rule.

Interface *CSSPageRule* (introduced in **DOM Level 2**)

The `CSSPageRule` interface represents a *@page rule* within a CSS style sheet. The `@page` rule is used to specify the dimensions, orientation, margins, etc. of a page box for paged media.

IDL Definition

```
// Introduced in DOM Level 2:
interface CSSPageRule : CSSRule {
           attribute DOMString        selectorText;
                                        // raises(DOMException) on setting

  readonly attribute CSSStyleDeclaration  style;
};
```

Attributes

`selectorText` of type `DOMString`

The parsable textual representation of the page selector for the rule.

Exceptions on setting

`DOMException`	SYNTAX_ERR: Raised if the specified CSS string value has a syntax error and is unparsable. NO_MODIFICATION_ALLOWED_ERR: Raised if this rule is readonly.

`style` of type `CSSStyleDeclaration` [p.24] , readonly
The *declaration-block* of this rule.

Interface *CSSImportRule* (introduced in **DOM Level 2**)

The `CSSImportRule` interface represents a *@import rule* within a CSS style sheet. The `@import` rule is used to import style rules from other style sheets.

IDL Definition

```
// Introduced in DOM Level 2:
interface CSSImportRule : CSSRule {
  readonly attribute DOMString        href;
  readonly attribute stylesheets::MediaList  media;
  readonly attribute CSSStyleSheet    styleSheet;
};
```

Attributes

`href` of type `DOMString`, readonly
The location of the style sheet to be imported. The attribute will not contain the `"url(...)"` specifier around the URI.

`media` of type `stylesheets::MediaList`, readonly
A list of media types for which this style sheet may be used.

`styleSheet` of type `CSSStyleSheet` [p.16] , readonly
The style sheet referred to by this rule, if it has been loaded. The value of this attribute is `null` if the style sheet has not yet been loaded or if it will not be loaded (e.g. if the style sheet is for a media type not supported by the user agent).

Interface *CSSCharsetRule* (introduced in **DOM Level 2**)

The `CSSCharsetRule` interface represents a *@charset rule* in a CSS style sheet. The value of the `encoding` attribute does not affect the encoding of text data in the DOM objects; this encoding is always UTF-16. After a stylesheet is loaded, the value of the `encoding` attribute is the value found in the `@charset` rule. If there was no `@charset` in the original document, then no `CSSCharsetRule` is created. The value of the `encoding` attribute may also be used as a hint for the encoding used on serialization of the style sheet.

The value of the *@charset rule* (and therefore of the `CSSCharsetRule`) may not correspond to the encoding the document actually came in; character encoding information e.g. in an HTTP header, has priority (see *CSS document representation*) but this is not reflected in the `CSSCharsetRule`.

IDL Definition

```
// Introduced in DOM Level 2:
interface CSSCharsetRule : CSSRule {
           attribute DOMString        encoding;
                                        // raises(DOMException) on setting

};
```

Attributes

`encoding` of type `DOMString`

The encoding information used in this `@charset` rule.

Exceptions on setting

`DOMException`	SYNTAX_ERR: Raised if the specified encoding value has a syntax error and is unparsable.
	NO_MODIFICATION_ALLOWED_ERR: Raised if this encoding rule is readonly.

Interface *CSSUnknownRule* (introduced in **DOM Level 2**)

The `CSSUnknownRule` interface represents an at-rule not supported by this user agent.

IDL Definition

```
// Introduced in DOM Level 2:
interface CSSUnknownRule : CSSRule {
};
```

Interface *CSSStyleDeclaration* (introduced in **DOM Level 2**)

The `CSSStyleDeclaration` interface represents a single *CSS declaration block*. This interface may be used to determine the style properties currently set in a block or to set style properties explicitly within the block.

While an implementation may not recognize all CSS properties within a CSS declaration block, it is expected to provide access to all specified properties in the style sheet through the `CSSStyleDeclaration` interface. Furthermore, implementations that support a specific level of CSS should correctly handle *CSS shorthand* properties for that level. For a further discussion of shorthand properties, see the `CSS2Properties` [p.40] interface.

This interface is also used to provide a **read-only** access to the *computed values* of an element. See also the `ViewCSS` [p.37] interface.

Note: The CSS Object Model doesn't provide an access to the *specified* or *actual* values of the CSS cascade.

IDL Definition

```
// Introduced in DOM Level 2:
interface CSSStyleDeclaration {
           attribute DOMString        cssText;
                                        // raises(DOMException) on setting

  DOMString          getPropertyValue(in DOMString propertyName);
  CSSValue           getPropertyCSSValue(in DOMString propertyName);
  DOMString          removeProperty(in DOMString propertyName)
                                        raises(DOMException);
  DOMString          getPropertyPriority(in DOMString propertyName);
  void               setProperty(in DOMString propertyName,
                                 in DOMString value,
                                 in DOMString priority)
                                        raises(DOMException);
  readonly attribute unsigned long    length;
  DOMString          item(in unsigned long index);
  readonly attribute CSSRule          parentRule;
};
```

Attributes

`cssText` of type `DOMString`

The parsable textual representation of the declaration block (excluding the surrounding curly braces). Setting this attribute will result in the parsing of the new value and resetting of all the properties in the declaration block including the removal or addition of properties.

Exceptions on setting

`DOMException`	SYNTAX_ERR: Raised if the specified CSS string value has a syntax error and is unparsable. NO_MODIFICATION_ALLOWED_ERR: Raised if this declaration is readonly or a property is readonly.

`length` of type `unsigned long`, readonly

The number of properties that have been explicitly set in this declaration block. The range of valid indices is 0 to length-1 inclusive.

`parentRule` of type `CSSRule` [p.18] , readonly

The CSS rule that contains this declaration block or `null` if this `CSSStyleDeclaration` is not attached to a `CSSRule` [p.18] .

Methods

`getPropertyCSSValue`

Used to retrieve the object representation of the value of a CSS property if it has been explicitly set within this declaration block. This method returns `null` if the property is a *shorthand* property. Shorthand property values can only be accessed and modified as strings, using the `getPropertyValue` and `setProperty` methods.

Parameters

`propertyName` of type `DOMString`

The name of the CSS property. See the *CSS property index*.

Return Value

`CSSValue` [p.27]	Returns the value of the property if it has been explicitly set for this declaration block. Returns `null` if the property has not been set.

No Exceptions

`getPropertyPriority`

Used to retrieve the priority of a CSS property (e.g. the `"important"` qualifier) if the property has been explicitly set in this declaration block.

Parameters

`propertyName` of type `DOMString`

The name of the CSS property. See the *CSS property index*.

Return Value

`DOMString`	A string representing the priority (e.g. `"important"`) if one exists. The empty string if none exists.

No Exceptions

`getPropertyValue`

Used to retrieve the value of a CSS property if it has been explicitly set within this declaration block.

Parameters

`propertyName` of type `DOMString`

The name of the CSS property. See the *CSS property index*.

Return Value

`DOMString`	Returns the value of the property if it has been explicitly set for this declaration block. Returns the empty string if the property has not been set.

No Exceptions

`item`

Used to retrieve the properties that have been explicitly set in this declaration block. The order of the properties retrieved using this method does not have to be the order in which they were set. This method can be used to iterate over all properties in this declaration block.

Parameters

`index` of type `unsigned long`

Index of the property name to retrieve.

Return Value

`DOMString`	The name of the property at this ordinal position. The empty string if no property exists at this position.

No Exceptions

`removeProperty`
Used to remove a CSS property if it has been explicitly set within this declaration block.
Parameters
`propertyName` of type `DOMString`
The name of the CSS property. See the *CSS property index*.
Return Value

`DOMString`	Returns the value of the property if it has been explicitly set for this declaration block. Returns the empty string if the property has not been set or the property name does not correspond to a known CSS property.

Exceptions

`DOMException`	NO_MODIFICATION_ALLOWED_ERR: Raised if this declaration is readonly or the property is readonly.

`setProperty`
Used to set a property value and priority within this declaration block.
Parameters
`propertyName` of type `DOMString`
The name of the CSS property. See the *CSS property index*.
`value` of type `DOMString`
The new value of the property.
`priority` of type `DOMString`
The new priority of the property (e.g. `"important"`).
Exceptions

`DOMException`	SYNTAX_ERR: Raised if the specified value has a syntax error and is unparsable. NO_MODIFICATION_ALLOWED_ERR: Raised if this declaration is readonly or the property is readonly.

No Return Value

Interface *CSSValue* (introduced in **DOM Level 2**)

The `CSSValue` interface represents a simple or a complex value. A `CSSValue` object only occurs in a context of a CSS property.

IDL Definition

```
// Introduced in DOM Level 2:
interface CSSValue {

  // UnitTypes
```

```
  const unsigned short      CSS_INHERIT                    = 0;
  const unsigned short      CSS_PRIMITIVE_VALUE            = 1;
  const unsigned short      CSS_VALUE_LIST                 = 2;
  const unsigned short      CSS_CUSTOM                     = 3;

           attribute DOMString        cssText;
                                        // raises(DOMException) on setting

  readonly attribute unsigned short   cssValueType;
};
```

Definition group *UnitTypes*

An integer indicating which type of unit applies to the value.

Defined Constants

`CSS_CUSTOM`
: The value is a custom value.

`CSS_INHERIT`
: The value is inherited and the `cssText` contains "inherit".

`CSS_PRIMITIVE_VALUE`
: The value is a primitive value and an instance of the `CSSPrimitiveValue` [p.28] interface can be obtained by using binding-specific casting methods on this instance of the `CSSValue` interface.

`CSS_VALUE_LIST`
: The value is a `CSSValue` list and an instance of the `CSSValueList` [p.34] interface can be obtained by using binding-specific casting methods on this instance of the `CSSValue` interface.

Attributes

`cssText` of type `DOMString`
: A string representation of the current value.

Exceptions on setting

`DOMException`	SYNTAX_ERR: Raised if the specified CSS string value has a syntax error (according to the attached property) or is unparsable. INVALID_MODIFICATION_ERR: Raised if the specified CSS string value represents a different type of values than the values allowed by the CSS property. NO_MODIFICATION_ALLOWED_ERR: Raised if this value is readonly.

`cssValueType` of type `unsigned short`, readonly
: A code defining the type of the value as defined above.

Interface *CSSPrimitiveValue* (introduced in **DOM Level 2**)

The `CSSPrimitiveValue` interface represents a single *CSS value*. This interface may be used to determine the value of a specific style property currently set in a block or to set a specific style property explicitly within the block. An instance of this interface might be obtained from the `getPropertyCSSValue` method of the `CSSStyleDeclaration` [p.24] interface. A `CSSPrimitiveValue` object only occurs in a context of a CSS property.

Conversions are allowed between absolute values (from millimeters to centimeters, from degrees to radians, and so on) but not between relative values. (For example, a pixel value cannot be converted to a centimeter value.) Percentage values can't be converted since they are relative to the parent value (or another property value). There is one exception for color percentage values: since a color percentage value is relative to the range 0-255, a color percentage value can be converted to a number; (see also the `RGBColor` [p.35] interface).

IDL Definition

```
// Introduced in DOM Level 2:
interface CSSPrimitiveValue : CSSValue {

  // UnitTypes
  const unsigned short      CSS_UNKNOWN                    = 0;
  const unsigned short      CSS_NUMBER                     = 1;
  const unsigned short      CSS_PERCENTAGE                 = 2;
  const unsigned short      CSS_EMS                        = 3;
  const unsigned short      CSS_EXS                        = 4;
  const unsigned short      CSS_PX                         = 5;
  const unsigned short      CSS_CM                         = 6;
  const unsigned short      CSS_MM                         = 7;
  const unsigned short      CSS_IN                         = 8;
  const unsigned short      CSS_PT                         = 9;
  const unsigned short      CSS_PC                         = 10;
  const unsigned short      CSS_DEG                        = 11;
  const unsigned short      CSS_RAD                        = 12;
  const unsigned short      CSS_GRAD                       = 13;
  const unsigned short      CSS_MS                         = 14;
  const unsigned short      CSS_S                          = 15;
  const unsigned short      CSS_HZ                         = 16;
  const unsigned short      CSS_KHZ                        = 17;
  const unsigned short      CSS_DIMENSION                  = 18;
  const unsigned short      CSS_STRING                     = 19;
  const unsigned short      CSS_URI                        = 20;
  const unsigned short      CSS_IDENT                      = 21;
  const unsigned short      CSS_ATTR                       = 22;
  const unsigned short      CSS_COUNTER                    = 23;
  const unsigned short      CSS_RECT                       = 24;
  const unsigned short      CSS_RGBCOLOR                   = 25;

  readonly attribute unsigned short   primitiveType;
  void               setFloatValue(in unsigned short unitType,
                                   in float floatValue)
                                        raises(DOMException);
  float              getFloatValue(in unsigned short unitType)
                                        raises(DOMException);
  void               setStringValue(in unsigned short stringType,
                                    in DOMString stringValue)
```

```
                                        raises(DOMException);
  DOMString          getStringValue()
                                        raises(DOMException);
  Counter            getCounterValue()
                                        raises(DOMException);
  Rect               getRectValue()
                                        raises(DOMException);
  RGBColor           getRGBColorValue()
                                        raises(DOMException);
};
```

Definition group *UnitTypes*

An integer indicating which type of unit applies to the value.

Defined Constants

`CSS_ATTR`
: The value is a *attribute function*. The value can be obtained by using the `getStringValue` method.

`CSS_CM`
: The value is a *length (cm)*. The value can be obtained by using the `getFloatValue` method.

`CSS_COUNTER`
: The value is a *counter or counters function*. The value can be obtained by using the `getCounterValue` method.

`CSS_DEG`
: The value is an *angle (deg)*. The value can be obtained by using the `getFloatValue` method.

`CSS_DIMENSION`
: The value is a number with an unknown dimension. The value can be obtained by using the `getFloatValue` method.

`CSS_EMS`
: The value is a *length (ems)*. The value can be obtained by using the `getFloatValue` method.

`CSS_EXS`
: The value is a *length (exs)*. The value can be obtained by using the `getFloatValue` method.

`CSS_GRAD`
: The value is an *angle (grad)*. The value can be obtained by using the `getFloatValue` method.

`CSS_HZ`
: The value is a *frequency (Hz)*. The value can be obtained by using the `getFloatValue` method.

`CSS_IDENT`
: The value is an *identifier*. The value can be obtained by using the `getStringValue` method.

`CSS_IN`
: The value is a *length (in)*. The value can be obtained by using the `getFloatValue` method.

`CSS_KHZ`
: The value is a *frequency (kHz)*. The value can be obtained by using the `getFloatValue` method.

`CSS_MM`
: The value is a *length (mm)*. The value can be obtained by using the `getFloatValue` method.

`CSS_MS`
: The value is a *time (ms)*. The value can be obtained by using the `getFloatValue` method.

`CSS_NUMBER`
: The value is a simple *number*. The value can be obtained by using the `getFloatValue` method.

`CSS_PC`
: The value is a *length (pc)*. The value can be obtained by using the `getFloatValue` method.

`CSS_PERCENTAGE`
: The value is a *percentage*. The value can be obtained by using the `getFloatValue` method.

`CSS_PT`
: The value is a *length (pt)*. The value can be obtained by using the `getFloatValue` method.

`CSS_PX`
: The value is a *length (px)*. The value can be obtained by using the `getFloatValue` method.

`CSS_RAD`
: The value is an *angle (rad)*. The value can be obtained by using the `getFloatValue` method.

`CSS_RECT`
: The value is a *rect function*. The value can be obtained by using the `getRectValue` method.

`CSS_RGBCOLOR`
: The value is a *RGB color*. The value can be obtained by using the `getRGBColorValue` method.

`CSS_S`
: The value is a *time (s)*. The value can be obtained by using the `getFloatValue` method.

`CSS_STRING`
: The value is a *STRING*. The value can be obtained by using the `getStringValue` method.

`CSS_UNKNOWN`
: The value is not a recognized CSS2 value. The value can only be obtained by using the `cssText` attribute.

`CSS_URI`
: The value is a *URI*. The value can be obtained by using the `getStringValue` method.

Attributes

`primitiveType` of type `unsigned short`, readonly

The type of the value as defined by the constants specified above.

Methods

`getCounterValue`

This method is used to get the Counter value. If this CSS value doesn't contain a counter value, a `DOMException` is raised. Modification to the corresponding style property can be achieved using the `Counter` [p.36] interface.

Return Value

`Counter` [p.36]	The Counter value.

Exceptions

`DOMException`	INVALID_ACCESS_ERR: Raised if the CSS value doesn't contain a Counter value (e.g. this is not `CSS_COUNTER`).

No Parameters

`getFloatValue`

This method is used to get a float value in a specified unit. If this CSS value doesn't contain a float value or can't be converted into the specified unit, a `DOMException` is raised.

Parameters

`unitType` of type `unsigned short`

A unit code to get the float value. The unit code can only be a float unit type (i.e. `CSS_NUMBER`, `CSS_PERCENTAGE`, `CSS_EMS`, `CSS_EXS`, `CSS_PX`, `CSS_CM`, `CSS_MM`, `CSS_IN`, `CSS_PT`, `CSS_PC`, `CSS_DEG`, `CSS_RAD`, `CSS_GRAD`, `CSS_MS`, `CSS_S`, `CSS_HZ`, `CSS_KHZ`, `CSS_DIMENSION`).

Return Value

`float`	The float value in the specified unit.

Exceptions

`DOMException`	INVALID_ACCESS_ERR: Raised if the CSS value doesn't contain a float value or if the float value can't be converted into the specified unit.

`getRGBColorValue`

This method is used to get the RGB color. If this CSS value doesn't contain a RGB color value, a `DOMException` is raised. Modification to the corresponding style property can be achieved using the `RGBColor` [p.35] interface.

Return Value

`RGBColor` [p.35] the RGB color value.

Exceptions

`DOMException` INVALID_ACCESS_ERR: Raised if the attached property can't return a RGB color value (e.g. this is not `CSS_RGBCOLOR`).

No Parameters

`getRectValue`

This method is used to get the Rect value. If this CSS value doesn't contain a rect value, a `DOMException` is raised. Modification to the corresponding style property can be achieved using the `Rect` [p.36] interface.

Return Value

`Rect` [p.36] The Rect value.

Exceptions

`DOMException` INVALID_ACCESS_ERR: Raised if the CSS value doesn't contain a Rect value. (e.g. this is not `CSS_RECT`).

No Parameters

`getStringValue`

This method is used to get the string value. If the CSS value doesn't contain a string value, a `DOMException` is raised.

Note: Some properties (like 'font-family' or 'voice-family') convert a whitespace separated list of idents to a string.

Return Value

`DOMString` The string value in the current unit. The current `primitiveType` can only be a string unit type (i.e. `CSS_STRING`, `CSS_URI`, `CSS_IDENT` and `CSS_ATTR`).

Exceptions

`DOMException` INVALID_ACCESS_ERR: Raised if the CSS value doesn't contain a string value.

No Parameters

`setFloatValue`

A method to set the float value with a specified unit. If the property attached with this value can not accept the specified unit or the float value, the value will be unchanged and a

`DOMException` will be raised.

Parameters

`unitType` of type `unsigned short`

A unit code as defined above. The unit code can only be a float unit type (i.e. `CSS_NUMBER`, `CSS_PERCENTAGE`, `CSS_EMS`, `CSS_EXS`, `CSS_PX`, `CSS_CM`, `CSS_MM`, `CSS_IN`, `CSS_PT`, `CSS_PC`, `CSS_DEG`, `CSS_RAD`, `CSS_GRAD`, `CSS_MS`, `CSS_S`, `CSS_HZ`, `CSS_KHZ`, `CSS_DIMENSION`).

`floatValue` of type `float`

The new float value.

Exceptions

`DOMException`	INVALID_ACCESS_ERR: Raised if the attached property doesn't support the float value or the unit type. NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

No Return Value

`setStringValue`

A method to set the string value with the specified unit. If the property attached to this value can't accept the specified unit or the string value, the value will be unchanged and a `DOMException` will be raised.

Parameters

`stringType` of type `unsigned short`

A string code as defined above. The string code can only be a string unit type (i.e. `CSS_STRING`, `CSS_URI`, `CSS_IDENT`, and `CSS_ATTR`).

`stringValue` of type `DOMString`

The new string value.

Exceptions

`DOMException`	INVALID_ACCESS_ERR: Raised if the CSS value doesn't contain a string value or if the string value can't be converted into the specified unit. NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

No Return Value

Interface *CSSValueList* (introduced in **DOM Level 2**)

The `CSSValueList` interface provides the abstraction of an ordered collection of CSS values.

Some properties allow an empty list into their syntax. In that case, these properties take the `none` identifier. So, an empty list means that the property has the value `none`.

The items in the `CSSValueList` are accessible via an integral index, starting from 0.

IDL Definition

```
// Introduced in DOM Level 2:
interface CSSValueList : CSSValue {
  readonly attribute unsigned long    length;
  CSSValue           item(in unsigned long index);
};
```

Attributes

`length` of type `unsigned long`, readonly

The number of `CSSValues` [p.27] in the list. The range of valid values of the indices is `0` to `length-1` inclusive.

Methods

`item`

Used to retrieve a `CSSValue` [p.27] by ordinal index. The order in this collection represents the order of the values in the CSS style property. If index is greater than or equal to the number of values in the list, this returns `null`.

Parameters

`index` of type `unsigned long`

Index into the collection.

Return Value

`CSSValue` [p.27]	The `CSSValue` at the `index` position in the `CSSValueList`, or `null` if that is not a valid index.

No Exceptions

Interface *RGBColor* (introduced in **DOM Level 2**)

The `RGBColor` interface is used to represent any *RGB color* value. This interface reflects the values in the underlying style property. Hence, modifications made to the `CSSPrimitiveValue` [p.28] objects modify the style property.

A specified RGB color is not clipped (even if the number is outside the range 0-255 or 0%-100%). A computed RGB color is clipped depending on the device.

Even if a style sheet can only contain an integer for a color value, the internal storage of this integer is a float, and this can be used as a float in the specified or the computed style.

A color percentage value can always be converted to a number and vice versa.

IDL Definition

```
// Introduced in DOM Level 2:
interface RGBColor {
  readonly attribute CSSPrimitiveValue  red;
  readonly attribute CSSPrimitiveValue  green;
  readonly attribute CSSPrimitiveValue  blue;
};
```

Attributes

`blue` of type `CSSPrimitiveValue` [p.28] , readonly
: This attribute is used for the blue value of the RGB color.

`green` of type `CSSPrimitiveValue` [p.28] , readonly
: This attribute is used for the green value of the RGB color.

`red` of type `CSSPrimitiveValue` [p.28] , readonly
: This attribute is used for the red value of the RGB color.

Interface *Rect* (introduced in **DOM Level 2**)

The `Rect` interface is used to represent any *rect* value. This interface reflects the values in the underlying style property. Hence, modifications made to the `CSSPrimitiveValue` [p.28] objects modify the style property.

IDL Definition

```
// Introduced in DOM Level 2:
interface Rect {
  readonly attribute CSSPrimitiveValue  top;
  readonly attribute CSSPrimitiveValue  right;
  readonly attribute CSSPrimitiveValue  bottom;
  readonly attribute CSSPrimitiveValue  left;
};
```

Attributes

`bottom` of type `CSSPrimitiveValue` [p.28] , readonly
: This attribute is used for the bottom of the rect.

`left` of type `CSSPrimitiveValue` [p.28] , readonly
: This attribute is used for the left of the rect.

`right` of type `CSSPrimitiveValue` [p.28] , readonly
: This attribute is used for the right of the rect.

`top` of type `CSSPrimitiveValue` [p.28] , readonly
: This attribute is used for the top of the rect.

Interface *Counter* (introduced in **DOM Level 2**)

The `Counter` interface is used to represent any *counter or counters function* value. This interface reflects the values in the underlying style property.

IDL Definition

```
// Introduced in DOM Level 2:
interface Counter {
  readonly attribute DOMString        identifier;
  readonly attribute DOMString        listStyle;
  readonly attribute DOMString        separator;
};
```

Attributes

`identifier` of type `DOMString`, readonly
: This attribute is used for the identifier of the counter.

`listStyle` of type `DOMString`, readonly
: This attribute is used for the style of the list.

`separator` of type `DOMString`, readonly
: This attribute is used for the separator of the nested counters.

2.2.1. Override and computed style sheet

Interface *ViewCSS* (introduced in **DOM Level 2**)

This interface represents a CSS view. The `getComputedStyle` method provides a **read only access** to the *computed values* of an element.

The expectation is that an instance of the `ViewCSS` interface can be obtained by using binding-specific casting methods on an instance of the `AbstractView` interface.

Since a computed style is related to an `Element` node, if this element is removed from the document, the associated `CSSStyleDeclaration` [p.24] and `CSSValue` [p.27] related to this declaration are no longer valid.

IDL Definition

```
// Introduced in DOM Level 2:
interface ViewCSS : views::AbstractView {
  CSSStyleDeclaration getComputedStyle(in Element elt,
                                       in DOMString pseudoElt);
};
```

Methods

`getComputedStyle`
: This method is used to get the computed style as it is defined in [CSS2].

Parameters

`elt` of type `Element`
: The element whose style is to be computed. This parameter cannot be null.

`pseudoElt` of type `DOMString`
: The pseudo-element or `null` if none.

Return Value

`CSSStyleDeclaration` [p.24]	The computed style. The `CSSStyleDeclaration` is read-only and contains only absolute values.

No Exceptions

Interface *DocumentCSS* (introduced in **DOM Level 2**)

This interface represents a document with a CSS view.

The `getOverrideStyle` method provides a mechanism through which a DOM author could effect immediate change to the style of an element without modifying the explicitly linked style sheets of a document or the inline style of elements in the style sheets. This style sheet comes after the author style sheet in the cascade algorithm and is called *override style sheet*. The override style sheet takes precedence over author style sheets. An "!important" declaration still takes precedence over a normal declaration. Override, author, and user style sheets all may contain "!important" declarations. User "!important" rules take precedence over both override and author "!important" rules, and override "!important" rules take precedence over author "!important" rules.

The expectation is that an instance of the `DocumentCSS` interface can be obtained by using binding-specific casting methods on an instance of the `Document` interface.

IDL Definition

```
// Introduced in DOM Level 2:
interface DocumentCSS : stylesheets::DocumentStyle {
  CSSStyleDeclaration getOverrideStyle(in Element elt,
                                       in DOMString pseudoElt);
};
```

Methods

`getOverrideStyle`

This method is used to retrieve the override style declaration for a specified element and a specified pseudo-element.

Parameters

`elt` of type `Element`

The element whose style is to be modified. This parameter cannot be null.

`pseudoElt` of type `DOMString`

The pseudo-element or `null` if none.

Return Value

`CSSStyleDeclaration` [p.24] The override style declaration.

No Exceptions

2.2.2. Style sheet creation

Interface *DOMImplementationCSS* (introduced in **DOM Level 2**)

This interface allows the DOM user to create a `CSSStyleSheet` [p.16] outside the context of a document. There is no way to associate the new `CSSStyleSheet` with a document in DOM Level 2.

IDL Definition

```
// Introduced in DOM   Level 2:
interface DOMImplementationCSS : DOMImplementation {
  CSSStyleSheet      createCSSStyleSheet(in DOMString title,
                                         in DOMString media)
                                        raises(DOMException);
};
```

Methods

`createCSSStyleSheet`

Creates a new `CSSStyleSheet` [p.16] .

Parameters

`title` of type `DOMString`

The advisory title. See also the Style Sheet Interfaces [p.10] section.

`media` of type `DOMString`

The comma-separated list of media associated with the new style sheet. See also the Style Sheet Interfaces [p.10] section.

Return Value

`CSSStyleSheet` [p.16]	A new CSS style sheet.

Exceptions

`DOMException`	SYNTAX_ERR: Raised if the specified media string value has a syntax error and is unparsable.

2.2.3. Element with CSS inline style

Interface *ElementCSSInlineStyle* (introduced in **DOM Level 2**)

Inline style information attached to elements is exposed through the `style` attribute. This represents the contents of the *STYLE* attribute for HTML elements (or elements in other schemas or DTDs which use the STYLE attribute in the same way). The expectation is that an instance of the ElementCSSInlineStyle interface can be obtained by using binding-specific casting methods on an instance of the Element interface when the element supports inline CSS style informations.

IDL Definition

```
// Introduced in DOM Level 2:
interface ElementCSSInlineStyle {
  readonly attribute CSSStyleDeclaration  style;
};
```

Attributes

`style` of type `CSSStyleDeclaration` [p.24] , readonly

The style attribute.

2.3. CSS2 Extended Interface

The interface found within this section are not mandatory. A DOM application may use the `hasFeature(feature, version)` method of the `DOMImplementation` interface with parameter values "CSS2" and "2.0" (respectively) to determine whether or not this module is supported by the implementation. In order to fully support this module, an implementation must also support the "CSS" feature defined defined in CSS Fundamental Interfaces [p.15] . Please refer to additional information about *conformance* in the DOM Level 2 Core specification [DOM Level 2 Core].

Interface *CSS2Properties* (introduced in **DOM Level 2**)

The `CSS2Properties` interface represents a convenience mechanism for retrieving and setting properties within a `CSSStyleDeclaration` [p.24] . The attributes of this interface correspond to all the *properties specified in CSS2*. Getting an attribute of this interface is equivalent to calling the `getPropertyValue` method of the `CSSStyleDeclaration` interface. Setting an attribute of this interface is equivalent to calling the `setProperty` method of the `CSSStyleDeclaration` interface.

A conformant implementation of the CSS module is not required to implement the `CSS2Properties` interface. If an implementation does implement this interface, the expectation is that language-specific methods can be used to cast from an instance of the `CSSStyleDeclaration` [p.24] interface to the `CSS2Properties` interface.

If an implementation does implement this interface, it is expected to understand the specific syntax of the shorthand properties, and apply their semantics; when the `margin` property is set, for example, the `marginTop`, `marginRight`, `marginBottom` and `marginLeft` properties are actually being set by the underlying implementation.

When dealing with CSS "shorthand" properties, the shorthand properties should be decomposed into their component longhand properties as appropriate, and when querying for their value, the form returned should be the shortest form exactly equivalent to the declarations made in the ruleset. However, if there is no shorthand declaration that could be added to the ruleset without changing in any way the rules already declared in the ruleset (i.e., by adding longhand rules that were previously not declared in the ruleset), then the empty string should be returned for the shorthand property.

For example, querying for the `font` property should not return "normal normal normal 14pt/normal Arial, sans-serif", when "14pt Arial, sans-serif" suffices. (The normals are initial values, and are implied by use of the longhand property.)

If the values for all the longhand properties that compose a particular string are the initial values, then a string consisting of all the initial values should be returned (e.g. a `border-width` value of "medium" should be returned as such, not as "").

For some shorthand properties that take missing values from other sides, such as the `margin`, `padding`, and `border-[width|style|color]` properties, the minimum number of sides possible should be used; i.e., "0px 10px" will be returned instead of "0px 10px 0px 10px".

If the value of a shorthand property can not be decomposed into its component longhand properties, as is the case for the `font` property with a value of "menu", querying for the values of the component longhand properties should return the empty string.

IDL Definition

```
// Introduced in DOM Level 2:
interface CSS2Properties {
           attribute DOMString        azimuth;
                                        // raises(DOMException) on setting

           attribute DOMString        background;
                                        // raises(DOMException) on setting

           attribute DOMString        backgroundAttachment;
                                        // raises(DOMException) on setting

           attribute DOMString        backgroundColor;
                                        // raises(DOMException) on setting

           attribute DOMString        backgroundImage;
                                        // raises(DOMException) on setting

           attribute DOMString        backgroundPosition;
                                        // raises(DOMException) on setting

           attribute DOMString        backgroundRepeat;
                                        // raises(DOMException) on setting

           attribute DOMString        border;
                                        // raises(DOMException) on setting

           attribute DOMString        borderCollapse;
                                        // raises(DOMException) on setting

           attribute DOMString        borderColor;
                                        // raises(DOMException) on setting

           attribute DOMString        borderSpacing;
                                        // raises(DOMException) on setting

           attribute DOMString        borderStyle;
                                        // raises(DOMException) on setting

           attribute DOMString        borderTop;
                                        // raises(DOMException) on setting

           attribute DOMString        borderRight;
                                        // raises(DOMException) on setting

           attribute DOMString        borderBottom;
                                        // raises(DOMException) on setting

           attribute DOMString        borderLeft;
                                        // raises(DOMException) on setting
```

```
attribute DOMString        borderTopColor;
                             // raises(DOMException) on setting

attribute DOMString        borderRightColor;
                             // raises(DOMException) on setting

attribute DOMString        borderBottomColor;
                             // raises(DOMException) on setting

attribute DOMString        borderLeftColor;
                             // raises(DOMException) on setting

attribute DOMString        borderTopStyle;
                             // raises(DOMException) on setting

attribute DOMString        borderRightStyle;
                             // raises(DOMException) on setting

attribute DOMString        borderBottomStyle;
                             // raises(DOMException) on setting

attribute DOMString        borderLeftStyle;
                             // raises(DOMException) on setting

attribute DOMString        borderTopWidth;
                             // raises(DOMException) on setting

attribute DOMString        borderRightWidth;
                             // raises(DOMException) on setting

attribute DOMString        borderBottomWidth;
                             // raises(DOMException) on setting

attribute DOMString        borderLeftWidth;
                             // raises(DOMException) on setting

attribute DOMString        borderWidth;
                             // raises(DOMException) on setting

attribute DOMString        bottom;
                             // raises(DOMException) on setting

attribute DOMString        captionSide;
                             // raises(DOMException) on setting

attribute DOMString        clear;
                             // raises(DOMException) on setting

attribute DOMString        clip;
                             // raises(DOMException) on setting

attribute DOMString        color;
                             // raises(DOMException) on setting

attribute DOMString        content;
                             // raises(DOMException) on setting
```

```
attribute DOMString        counterIncrement;
                             // raises(DOMException) on setting

attribute DOMString        counterReset;
                             // raises(DOMException) on setting

attribute DOMString        cue;
                             // raises(DOMException) on setting

attribute DOMString        cueAfter;
                             // raises(DOMException) on setting

attribute DOMString        cueBefore;
                             // raises(DOMException) on setting

attribute DOMString        cursor;
                             // raises(DOMException) on setting

attribute DOMString        direction;
                             // raises(DOMException) on setting

attribute DOMString        display;
                             // raises(DOMException) on setting

attribute DOMString        elevation;
                             // raises(DOMException) on setting

attribute DOMString        emptyCells;
                             // raises(DOMException) on setting

attribute DOMString        cssFloat;
                             // raises(DOMException) on setting

attribute DOMString        font;
                             // raises(DOMException) on setting

attribute DOMString        fontFamily;
                             // raises(DOMException) on setting

attribute DOMString        fontSize;
                             // raises(DOMException) on setting

attribute DOMString        fontSizeAdjust;
                             // raises(DOMException) on setting

attribute DOMString        fontStretch;
                             // raises(DOMException) on setting

attribute DOMString        fontStyle;
                             // raises(DOMException) on setting

attribute DOMString        fontVariant;
                             // raises(DOMException) on setting

attribute DOMString        fontWeight;
                             // raises(DOMException) on setting
```

```
attribute DOMString        height;
                             // raises(DOMException) on setting

attribute DOMString        left;
                             // raises(DOMException) on setting

attribute DOMString        letterSpacing;
                             // raises(DOMException) on setting

attribute DOMString        lineHeight;
                             // raises(DOMException) on setting

attribute DOMString        listStyle;
                             // raises(DOMException) on setting

attribute DOMString        listStyleImage;
                             // raises(DOMException) on setting

attribute DOMString        listStylePosition;
                             // raises(DOMException) on setting

attribute DOMString        listStyleType;
                             // raises(DOMException) on setting

attribute DOMString        margin;
                             // raises(DOMException) on setting

attribute DOMString        marginTop;
                             // raises(DOMException) on setting

attribute DOMString        marginRight;
                             // raises(DOMException) on setting

attribute DOMString        marginBottom;
                             // raises(DOMException) on setting

attribute DOMString        marginLeft;
                             // raises(DOMException) on setting

attribute DOMString        markerOffset;
                             // raises(DOMException) on setting

attribute DOMString        marks;
                             // raises(DOMException) on setting

attribute DOMString        maxHeight;
                             // raises(DOMException) on setting

attribute DOMString        maxWidth;
                             // raises(DOMException) on setting

attribute DOMString        minHeight;
                             // raises(DOMException) on setting

attribute DOMString        minWidth;
                             // raises(DOMException) on setting
```

```
attribute DOMString        orphans;
                             // raises(DOMException) on setting

attribute DOMString        outline;
                             // raises(DOMException) on setting

attribute DOMString        outlineColor;
                             // raises(DOMException) on setting

attribute DOMString        outlineStyle;
                             // raises(DOMException) on setting

attribute DOMString        outlineWidth;
                             // raises(DOMException) on setting

attribute DOMString        overflow;
                             // raises(DOMException) on setting

attribute DOMString        padding;
                             // raises(DOMException) on setting

attribute DOMString        paddingTop;
                             // raises(DOMException) on setting

attribute DOMString        paddingRight;
                             // raises(DOMException) on setting

attribute DOMString        paddingBottom;
                             // raises(DOMException) on setting

attribute DOMString        paddingLeft;
                             // raises(DOMException) on setting

attribute DOMString        page;
                             // raises(DOMException) on setting

attribute DOMString        pageBreakAfter;
                             // raises(DOMException) on setting

attribute DOMString        pageBreakBefore;
                             // raises(DOMException) on setting

attribute DOMString        pageBreakInside;
                             // raises(DOMException) on setting

attribute DOMString        pause;
                             // raises(DOMException) on setting

attribute DOMString        pauseAfter;
                             // raises(DOMException) on setting

attribute DOMString        pauseBefore;
                             // raises(DOMException) on setting

attribute DOMString        pitch;
                             // raises(DOMException) on setting
```

```
attribute DOMString        pitchRange;
                             // raises(DOMException) on setting

attribute DOMString        playDuring;
                             // raises(DOMException) on setting

attribute DOMString        position;
                             // raises(DOMException) on setting

attribute DOMString        quotes;
                             // raises(DOMException) on setting

attribute DOMString        richness;
                             // raises(DOMException) on setting

attribute DOMString        right;
                             // raises(DOMException) on setting

attribute DOMString        size;
                             // raises(DOMException) on setting

attribute DOMString        speak;
                             // raises(DOMException) on setting

attribute DOMString        speakHeader;
                             // raises(DOMException) on setting

attribute DOMString        speakNumeral;
                             // raises(DOMException) on setting

attribute DOMString        speakPunctuation;
                             // raises(DOMException) on setting

attribute DOMString        speechRate;
                             // raises(DOMException) on setting

attribute DOMString        stress;
                             // raises(DOMException) on setting

attribute DOMString        tableLayout;
                             // raises(DOMException) on setting

attribute DOMString        textAlign;
                             // raises(DOMException) on setting

attribute DOMString        textDecoration;
                             // raises(DOMException) on setting

attribute DOMString        textIndent;
                             // raises(DOMException) on setting

attribute DOMString        textShadow;
                             // raises(DOMException) on setting

attribute DOMString        textTransform;
                             // raises(DOMException) on setting
```

```
            attribute DOMString        top;
                                         // raises(DOMException) on setting

            attribute DOMString        unicodeBidi;
                                         // raises(DOMException) on setting

            attribute DOMString        verticalAlign;
                                         // raises(DOMException) on setting

            attribute DOMString        visibility;
                                         // raises(DOMException) on setting

            attribute DOMString        voiceFamily;
                                         // raises(DOMException) on setting

            attribute DOMString        volume;
                                         // raises(DOMException) on setting

            attribute DOMString        whiteSpace;
                                         // raises(DOMException) on setting

            attribute DOMString        widows;
                                         // raises(DOMException) on setting

            attribute DOMString        width;
                                         // raises(DOMException) on setting

            attribute DOMString        wordSpacing;
                                         // raises(DOMException) on setting

            attribute DOMString        zIndex;
                                         // raises(DOMException) on setting

};
```

Attributes

`azimuth` of type `DOMString`

See the *azimuth property definition* in CSS2.

Exceptions on setting

`DOMException`	SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable. NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`background` of type `DOMString`

See the *background property definition* in CSS2.

Exceptions on setting

`DOMException` SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable.

NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`backgroundAttachment` of type `DOMString`

See the *background-attachment property definition* in CSS2.

Exceptions on setting

`DOMException` SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable.

NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`backgroundColor` of type `DOMString`

See the *background-color property definition* in CSS2.

Exceptions on setting

`DOMException` SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable.

NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`backgroundImage` of type `DOMString`

See the *background-image property definition* in CSS2.

Exceptions on setting

`DOMException` SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable.

NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`backgroundPosition` of type `DOMString`

See the *background-position property definition* in CSS2.

Exceptions on setting

`DOMException` SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable.

NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`backgroundRepeat` of type `DOMString`

See the *background-repeat property definition* in CSS2.

Exceptions on setting

`DOMException` SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable.

NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`border` of type `DOMString`

See the *border property definition* in CSS2.

Exceptions on setting

`DOMException` SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable.

NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`borderBottom` of type `DOMString`

See the *border-bottom property definition* in CSS2.

Exceptions on setting

`DOMException` SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable.

NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`borderBottomColor` of type `DOMString`

See the *border-bottom-color property definition* in CSS2.

Exceptions on setting

`DOMException` SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable.

NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`borderBottomStyle` of type `DOMString`

See the *border-bottom-style property definition* in CSS2.

Exceptions on setting

`DOMException` SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable.

NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`borderBottomWidth` of type `DOMString`

See the *border-bottom-width property definition* in CSS2.

Exceptions on setting

`DOMException` SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable.

NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`borderCollapse` of type `DOMString`

See the *border-collapse property definition* in CSS2.

Exceptions on setting

`DOMException` SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable.

NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`borderColor` of type `DOMString`

See the *border-color property definition* in CSS2.

Exceptions on setting

`DOMException` SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable.

NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`borderLeft` of type `DOMString`

See the *border-left property definition* in CSS2.

Exceptions on setting

`DOMException` SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable.

NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`borderLeftColor` of type `DOMString`

See the *border-left-color property definition* in CSS2.

Exceptions on setting

`DOMException` SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable.

NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`borderLeftStyle` of type `DOMString`

See the *border-left-style property definition* in CSS2.

Exceptions on setting

`DOMException` SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable.

NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`borderLeftWidth` of type `DOMString`

See the *border-left-width property definition* in CSS2.

Exceptions on setting

`DOMException` SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable.

NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`borderRight` of type `DOMString`

See the *border-right property definition* in CSS2.

Exceptions on setting

`DOMException` SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable.

NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`borderRightColor` of type `DOMString`

See the *border-right-color property definition* in CSS2.

Exceptions on setting

`DOMException` SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable.

NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`borderRightStyle` of type `DOMString`

See the *border-right-style property definition* in CSS2.

Exceptions on setting

`DOMException` SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable.

NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`borderRightWidth` of type `DOMString`

See the *border-right-width property definition* in CSS2.

Exceptions on setting

`DOMException` SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable.

NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`borderSpacing` of type `DOMString`

See the *border-spacing property definition* in CSS2.

Exceptions on setting

`DOMException` SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable.

NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`borderStyle` of type `DOMString`

See the *border-style property definition* in CSS2.

Exceptions on setting

`DOMException` SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable.

NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`borderTop` of type `DOMString`

See the *border-top property definition* in CSS2.

Exceptions on setting

`DOMException` SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable.

NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`borderTopColor` of type `DOMString`

See the *border-top-color property definition* in CSS2.

Exceptions on setting

`DOMException` SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable.

NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`borderTopStyle` of type `DOMString`

See the *border-top-style property definition* in CSS2.

Exceptions on setting

`DOMException` SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable.

NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`borderTopWidth` of type `DOMString`

See the *border-top-width property definition* in CSS2.

Exceptions on setting

`DOMException` SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable.

NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`borderWidth` of type `DOMString`

See the *border-width property definition* in CSS2.

Exceptions on setting

`DOMException` SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable.

NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`bottom` of type `DOMString`

See the *bottom property definition* in CSS2.

Exceptions on setting

`DOMException`	SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable. NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`captionSide` of type `DOMString`

See the *caption-side property definition* in CSS2.

Exceptions on setting

`DOMException`	SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable. NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`clear` of type `DOMString`

See the *clear property definition* in CSS2.

Exceptions on setting

`DOMException`	SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable. NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`clip` of type `DOMString`

See the *clip property definition* in CSS2.

Exceptions on setting

`DOMException`	SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable. NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`color` of type `DOMString`

See the *color property definition* in CSS2.

Exceptions on setting

`DOMException` SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable.

NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`content` of type `DOMString`

See the *content property definition* in CSS2.

Exceptions on setting

`DOMException` SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable.

NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`counterIncrement` of type `DOMString`

See the *counter-increment property definition* in CSS2.

Exceptions on setting

`DOMException` SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable.

NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`counterReset` of type `DOMString`

See the *counter-reset property definition* in CSS2.

Exceptions on setting

`DOMException` SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable.

NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`cssFloat` of type `DOMString`

See the *float property definition* in CSS2.

Exceptions on setting

`DOMException` SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable.

NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`cue` of type `DOMString`

See the *cue property definition* in CSS2.

Exceptions on setting

`DOMException` SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable.

NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`cueAfter` of type `DOMString`

See the *cue-after property definition* in CSS2.

Exceptions on setting

`DOMException` SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable.

NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`cueBefore` of type `DOMString`

See the *cue-before property definition* in CSS2.

Exceptions on setting

`DOMException` SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable.

NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`cursor` of type `DOMString`

See the *cursor property definition* in CSS2.

Exceptions on setting

`DOMException` SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable.

NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`direction` of type `DOMString`

See the *direction property definition* in CSS2.

Exceptions on setting

`DOMException` SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable.

NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`display` of type `DOMString`

See the *display property definition* in CSS2.

Exceptions on setting

`DOMException` SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable.

NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`elevation` of type `DOMString`

See the *elevation property definition* in CSS2.

Exceptions on setting

`DOMException` SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable.

NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`emptyCells` of type `DOMString`

See the *empty-cells property definition* in CSS2.

Exceptions on setting

`DOMException` SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable.

NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`font` of type `DOMString`

See the *font property definition* in CSS2.

Exceptions on setting

`DOMException` SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable.

NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`fontFamily` of type `DOMString`

See the *font-family property definition* in CSS2.

Exceptions on setting

`DOMException` SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable.

NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`fontSize` of type `DOMString`

See the *font-size property definition* in CSS2.

Exceptions on setting

`DOMException` SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable.

NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`fontSizeAdjust` of type `DOMString`

See the *font-size-adjust property definition* in CSS2.

Exceptions on setting

`DOMException` SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable.

NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`fontStretch` of type `DOMString`

See the *font-stretch property definition* in CSS2.

Exceptions on setting

`DOMException` SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable.

NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`fontStyle` of type `DOMString`

See the *font-style property definition* in CSS2.

Exceptions on setting

`DOMException` SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable.

NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`fontVariant` of type `DOMString`

See the *font-variant property definition* in CSS2.

Exceptions on setting

`DOMException` SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable.

NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`fontWeight` of type `DOMString`

See the *font-weight property definition* in CSS2.

Exceptions on setting

`DOMException` SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable.

NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`height` of type `DOMString`

See the *height property definition* in CSS2.

Exceptions on setting

`DOMException` SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable.

NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`left` of type `DOMString`

See the *left property definition* in CSS2.

Exceptions on setting

`DOMException` SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable.

NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`letterSpacing` of type `DOMString`

See the *letter-spacing property definition* in CSS2.

Exceptions on setting

`DOMException` SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable.

NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`lineHeight` of type `DOMString`

See the *line-height property definition* in CSS2.

Exceptions on setting

`DOMException` SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable.

NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`listStyle` of type `DOMString`

See the *list-style property definition* in CSS2.

Exceptions on setting

`DOMException` SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable.

NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`listStyleImage` of type `DOMString`

See the *list-style-image property definition* in CSS2.

Exceptions on setting

`DOMException` SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable.

NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`listStylePosition` of type `DOMString`

See the *list-style-position property definition* in CSS2.

Exceptions on setting

`DOMException` SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable.

NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`listStyleType` of type `DOMString`

See the *list-style-type property definition* in CSS2.

Exceptions on setting

`DOMException` SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable.

NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`margin` of type `DOMString`

See the *margin property definition* in CSS2.

Exceptions on setting

`DOMException` SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable.

NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`marginBottom` of type `DOMString`

See the *margin-bottom property definition* in CSS2.

Exceptions on setting

`DOMException` SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable.

NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`marginLeft` of type `DOMString`

See the *margin-left property definition* in CSS2.

Exceptions on setting

`DOMException` SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable.

NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`marginRight` of type `DOMString`

See the *margin-right property definition* in CSS2.

Exceptions on setting

`DOMException` SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable.

NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`marginTop` of type `DOMString`

See the *margin-top property definition* in CSS2.

Exceptions on setting

`DOMException` SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable.

NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`markerOffset` of type `DOMString`

See the *marker-offset property definition* in CSS2.

Exceptions on setting

`DOMException` SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable.

NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`marks` of type `DOMString`

See the *marks property definition* in CSS2.

Exceptions on setting

`DOMException` SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable.

NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`maxHeight` of type `DOMString`

See the *max-height property definition* in CSS2.

Exceptions on setting

`DOMException` SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable.

NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`maxWidth` of type `DOMString`

See the *max-width property definition* in CSS2.

Exceptions on setting

`DOMException` SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable.

NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`minHeight` of type `DOMString`

See the *min-height property definition* in CSS2.

Exceptions on setting

`DOMException` SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable.

NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`minWidth` of type `DOMString`

See the *min-width property definition* in CSS2.

Exceptions on setting

`DOMException` SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable.

NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`orphans` of type `DOMString`

See the *orphans property definition* in CSS2.

Exceptions on setting

`DOMException` SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable.

NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`outline` of type `DOMString`

See the *outline property definition* in CSS2.

Exceptions on setting

`DOMException` SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable.

NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`outlineColor` of type `DOMString`

See the *outline-color property definition* in CSS2.

Exceptions on setting

`DOMException` SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable.

NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`outlineStyle` of type `DOMString`

See the *outline-style property definition* in CSS2.

Exceptions on setting

`DOMException` SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable.

NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`outlineWidth` of type `DOMString`

See the *outline-width property definition* in CSS2.

Exceptions on setting

`DOMException`	SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable. NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`overflow` of type `DOMString`

See the *overflow property definition* in CSS2.

Exceptions on setting

`DOMException`	SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable. NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`padding` of type `DOMString`

See the *padding property definition* in CSS2.

Exceptions on setting

`DOMException`	SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable. NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`paddingBottom` of type `DOMString`

See the *padding-bottom property definition* in CSS2.

Exceptions on setting

`DOMException`	SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable. NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`paddingLeft` of type `DOMString`

See the *padding-left property definition* in CSS2.

Exceptions on setting

`DOMException` SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable.

NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`paddingRight` of type `DOMString`

See the *padding-right property definition* in CSS2.

Exceptions on setting

`DOMException` SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable.

NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`paddingTop` of type `DOMString`

See the *padding-top property definition* in CSS2.

Exceptions on setting

`DOMException` SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable.

NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`page` of type `DOMString`

See the *page property definition* in CSS2.

Exceptions on setting

`DOMException` SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable.

NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`pageBreakAfter` of type `DOMString`

See the *page-break-after property definition* in CSS2.

Exceptions on setting

`DOMException` SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable.

NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`pageBreakBefore` of type `DOMString`

See the *page-break-before property definition* in CSS2.

Exceptions on setting

`DOMException` SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable.

NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`pageBreakInside` of type `DOMString`

See the *page-break-inside property definition* in CSS2.

Exceptions on setting

`DOMException` SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable.

NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`pause` of type `DOMString`

See the *pause property definition* in CSS2.

Exceptions on setting

`DOMException` SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable.

NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`pauseAfter` of type `DOMString`

See the *pause-after property definition* in CSS2.

Exceptions on setting

`DOMException` SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable.

NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`pauseBefore` of type `DOMString`

See the *pause-before property definition* in CSS2.

Exceptions on setting

`DOMException` SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable.

NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`pitch` of type `DOMString`

See the *pitch property definition* in CSS2.

Exceptions on setting

`DOMException` SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable.

NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`pitchRange` of type `DOMString`

See the *pitch-range property definition* in CSS2.

Exceptions on setting

`DOMException` SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable.

NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`playDuring` of type `DOMString`

See the *play-during property definition* in CSS2.

Exceptions on setting

`DOMException`	SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable. NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`position` of type `DOMString`

See the *position property definition* in CSS2.

Exceptions on setting

`DOMException`	SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable. NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`quotes` of type `DOMString`

See the *quotes property definition* in CSS2.

Exceptions on setting

`DOMException`	SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable. NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`richness` of type `DOMString`

See the *richness property definition* in CSS2.

Exceptions on setting

`DOMException`	SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable. NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`right` of type `DOMString`

See the *right property definition* in CSS2.

Exceptions on setting

`DOMException`	SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable. NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`size` of type `DOMString`

See the *size property definition* in CSS2.

Exceptions on setting

`DOMException`	SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable. NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`speak` of type `DOMString`

See the *speak property definition* in CSS2.

Exceptions on setting

`DOMException`	SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable. NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`speakHeader` of type `DOMString`

See the *speak-header property definition* in CSS2.

Exceptions on setting

`DOMException`	SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable. NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`speakNumeral` of type `DOMString`

See the *speak-numeral property definition* in CSS2.

Exceptions on setting

`DOMException` SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable.

NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`speakPunctuation` of type `DOMString`

See the *speak-punctuation property definition* in CSS2.

Exceptions on setting

`DOMException` SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable.

NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`speechRate` of type `DOMString`

See the *speech-rate property definition* in CSS2.

Exceptions on setting

`DOMException` SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable.

NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`stress` of type `DOMString`

See the *stress property definition* in CSS2.

Exceptions on setting

`DOMException` SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable.

NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`tableLayout` of type `DOMString`

See the *table-layout property definition* in CSS2.

Exceptions on setting

`DOMException` SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable.

NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`textAlign` of type `DOMString`

See the *text-align property definition* in CSS2.

Exceptions on setting

`DOMException` SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable.

NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`textDecoration` of type `DOMString`

See the *text-decoration property definition* in CSS2.

Exceptions on setting

`DOMException` SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable.

NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`textIndent` of type `DOMString`

See the *text-indent property definition* in CSS2.

Exceptions on setting

`DOMException` SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable.

NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`textShadow` of type `DOMString`

See the *text-shadow property definition* in CSS2.

Exceptions on setting

`DOMException` SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable.

NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`textTransform` of type `DOMString`

See the *text-transform property definition* in CSS2.

Exceptions on setting

`DOMException` SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable.

NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`top` of type `DOMString`

See the *top property definition* in CSS2.

Exceptions on setting

`DOMException` SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable.

NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`unicodeBidi` of type `DOMString`

See the *unicode-bidi property definition* in CSS2.

Exceptions on setting

`DOMException` SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable.

NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`verticalAlign` of type `DOMString`

See the *vertical-align property definition* in CSS2.

Exceptions on setting

`DOMException` SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable.

NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`visibility` of type `DOMString`

See the *visibility property definition* in CSS2.

Exceptions on setting

`DOMException` SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable.

NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`voiceFamily` of type `DOMString`

See the *voice-family property definition* in CSS2.

Exceptions on setting

`DOMException` SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable.

NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`volume` of type `DOMString`

See the *volume property definition* in CSS2.

Exceptions on setting

`DOMException` SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable.

NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`whiteSpace` of type `DOMString`

See the *white-space property definition* in CSS2.

Exceptions on setting

`DOMException`	SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable. NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`widows` of type `DOMString`

See the *widows property definition* in CSS2.

Exceptions on setting

`DOMException`	SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable. NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`width` of type `DOMString`

See the *width property definition* in CSS2.

Exceptions on setting

`DOMException`	SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable. NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`wordSpacing` of type `DOMString`

See the *word-spacing property definition* in CSS2.

Exceptions on setting

`DOMException`	SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable. NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

`zIndex` of type `DOMString`

See the *z-index property definition* in CSS2.

Exceptions on setting

`DOMException`	SYNTAX_ERR: Raised if the new value has a syntax error and is unparsable. NO_MODIFICATION_ALLOWED_ERR: Raised if this property is readonly.

Appendix A: IDL Definitions

This appendix contains the complete OMG IDL [OMGIDL] for the Level 2 Document Object Model Style definitions. The definitions are divided into Stylesheets [p.79] and CSS [p.80] .

The IDL files are also available as:
http://www.w3.org/TR/2000/REC-DOM-Level-2-Style-20001113/idl.zip

A.1: Document Object Model Style Sheets

stylesheets.idl:

```
// File: stylesheets.idl

#ifndef _STYLESHEETS_IDL_
#define _STYLESHEETS_IDL_

#include "dom.idl"

#pragma prefix "dom.w3c.org"
module stylesheets
{

  typedef dom::DOMString DOMString;
  typedef dom::Node Node;

  interface MediaList;

  // Introduced in DOM Level 2:
  interface StyleSheet {
    readonly attribute DOMString        type;
             attribute boolean          disabled;
    readonly attribute Node             ownerNode;
    readonly attribute StyleSheet       parentStyleSheet;
    readonly attribute DOMString        href;
    readonly attribute DOMString        title;
    readonly attribute MediaList        media;
  };

  // Introduced in DOM Level 2:
  interface StyleSheetList {
    readonly attribute unsigned long    length;
    StyleSheet          item(in unsigned long index);
  };

  // Introduced in DOM Level 2:
  interface MediaList {
             attribute DOMString        mediaText;
                                        // raises(dom::DOMException) on setting

    readonly attribute unsigned long    length;
    DOMString           item(in unsigned long index);
    void                deleteMedium(in DOMString oldMedium)
```

```
                                        raises(dom::DOMException);
    void                appendMedium(in DOMString newMedium)
                                        raises(dom::DOMException);
  };

  // Introduced in DOM Level 2:
  interface LinkStyle {
    readonly attribute StyleSheet       sheet;
  };

  // Introduced in DOM Level 2:
  interface DocumentStyle {
    readonly attribute StyleSheetList   styleSheets;
  };
};

#endif // _STYLESHEETS_IDL_
```

A.2: Document Object Model CSS

css.idl:

```
// File: css.idl

#ifndef _CSS_IDL_
#define _CSS_IDL_

#include "dom.idl"
#include "stylesheets.idl"
#include "views.idl"

#pragma prefix "dom.w3c.org"
module css
{

  typedef dom::DOMString DOMString;
  typedef dom::Element Element;
  typedef dom::DOMImplementation DOMImplementation;

  interface CSSRule;
  interface CSSStyleSheet;
  interface CSSStyleDeclaration;
  interface CSSValue;
  interface Counter;
  interface Rect;
  interface RGBColor;

  // Introduced in DOM Level 2:
  interface CSSRuleList {
    readonly attribute unsigned long    length;
    CSSRule             item(in unsigned long index);
  };

  // Introduced in DOM Level 2:
  interface CSSRule {
```

```
  // RuleType
  const unsigned short      UNKNOWN_RULE                  = 0;
  const unsigned short      STYLE_RULE                    = 1;
  const unsigned short      CHARSET_RULE                  = 2;
  const unsigned short      IMPORT_RULE                   = 3;
  const unsigned short      MEDIA_RULE                    = 4;
  const unsigned short      FONT_FACE_RULE                = 5;
  const unsigned short      PAGE_RULE                     = 6;

  readonly attribute unsigned short   type;
           attribute DOMString        cssText;
                                      // raises(dom::DOMException) on setting

  readonly attribute CSSStyleSheet    parentStyleSheet;
  readonly attribute CSSRule          parentRule;
};

// Introduced in DOM Level 2:
interface CSSStyleRule : CSSRule {
           attribute DOMString        selectorText;
                                      // raises(dom::DOMException) on setting

  readonly attribute CSSStyleDeclaration  style;
};

// Introduced in DOM Level 2:
interface CSSMediaRule : CSSRule {
  readonly attribute stylesheets::MediaList  media;
  readonly attribute CSSRuleList      cssRules;
  unsigned long      insertRule(in DOMString rule,
                                in unsigned long index)
                                      raises(dom::DOMException);
  void               deleteRule(in unsigned long index)
                                      raises(dom::DOMException);
};

// Introduced in DOM Level 2:
interface CSSFontFaceRule : CSSRule {
  readonly attribute CSSStyleDeclaration  style;
};

// Introduced in DOM Level 2:
interface CSSPageRule : CSSRule {
           attribute DOMString        selectorText;
                                      // raises(dom::DOMException) on setting

  readonly attribute CSSStyleDeclaration  style;
};

// Introduced in DOM Level 2:
interface CSSImportRule : CSSRule {
  readonly attribute DOMString        href;
  readonly attribute stylesheets::MediaList  media;
  readonly attribute CSSStyleSheet    styleSheet;
};
```

```
// Introduced in DOM Level 2:
interface CSSCharsetRule : CSSRule {
           attribute DOMString        encoding;
                                      // raises(dom::DOMException) on setting

};

// Introduced in DOM Level 2:
interface CSSUnknownRule : CSSRule {
};

// Introduced in DOM Level 2:
interface CSSStyleDeclaration {
           attribute DOMString        cssText;
                                      // raises(dom::DOMException) on setting

  DOMString          getPropertyValue(in DOMString propertyName);
  CSSValue           getPropertyCSSValue(in DOMString propertyName);
  DOMString          removeProperty(in DOMString propertyName)
                                      raises(dom::DOMException);
  DOMString          getPropertyPriority(in DOMString propertyName);
  void               setProperty(in DOMString propertyName,
                                 in DOMString value,
                                 in DOMString priority)
                                      raises(dom::DOMException);
  readonly attribute unsigned long    length;
  DOMString          item(in unsigned long index);
  readonly attribute CSSRule          parentRule;
};

// Introduced in DOM Level 2:
interface CSSValue {

  // UnitTypes
  const unsigned short      CSS_INHERIT                   = 0;
  const unsigned short      CSS_PRIMITIVE_VALUE           = 1;
  const unsigned short      CSS_VALUE_LIST                = 2;
  const unsigned short      CSS_CUSTOM                    = 3;

           attribute DOMString        cssText;
                                      // raises(dom::DOMException) on setting

  readonly attribute unsigned short   cssValueType;
};

// Introduced in DOM Level 2:
interface CSSPrimitiveValue : CSSValue {

  // UnitTypes
  const unsigned short      CSS_UNKNOWN                   = 0;
  const unsigned short      CSS_NUMBER                    = 1;
  const unsigned short      CSS_PERCENTAGE                = 2;
  const unsigned short      CSS_EMS                       = 3;
  const unsigned short      CSS_EXS                       = 4;
  const unsigned short      CSS_PX                        = 5;
  const unsigned short      CSS_CM                        = 6;
  const unsigned short      CSS_MM                        = 7;
```

```
  const unsigned short      CSS_IN                          = 8;
  const unsigned short      CSS_PT                          = 9;
  const unsigned short      CSS_PC                          = 10;
  const unsigned short      CSS_DEG                         = 11;
  const unsigned short      CSS_RAD                         = 12;
  const unsigned short      CSS_GRAD                        = 13;
  const unsigned short      CSS_MS                          = 14;
  const unsigned short      CSS_S                           = 15;
  const unsigned short      CSS_HZ                          = 16;
  const unsigned short      CSS_KHZ                         = 17;
  const unsigned short      CSS_DIMENSION                   = 18;
  const unsigned short      CSS_STRING                      = 19;
  const unsigned short      CSS_URI                         = 20;
  const unsigned short      CSS_IDENT                       = 21;
  const unsigned short      CSS_ATTR                        = 22;
  const unsigned short      CSS_COUNTER                     = 23;
  const unsigned short      CSS_RECT                        = 24;
  const unsigned short      CSS_RGBCOLOR                    = 25;

  readonly attribute unsigned short   primitiveType;
  void               setFloatValue(in unsigned short unitType,
                                   in float floatValue)
                                     raises(dom::DOMException);
  float              getFloatValue(in unsigned short unitType)
                                     raises(dom::DOMException);
  void               setStringValue(in unsigned short stringType,
                                    in DOMString stringValue)
                                     raises(dom::DOMException);
  DOMString          getStringValue()
                                     raises(dom::DOMException);
  Counter            getCounterValue()
                                     raises(dom::DOMException);
  Rect               getRectValue()
                                     raises(dom::DOMException);
  RGBColor           getRGBColorValue()
                                     raises(dom::DOMException);
};

// Introduced in DOM Level 2:
interface CSSValueList : CSSValue {
  readonly attribute unsigned long    length;
  CSSValue           item(in unsigned long index);
};

// Introduced in DOM Level 2:
interface RGBColor {
  readonly attribute CSSPrimitiveValue  red;
  readonly attribute CSSPrimitiveValue  green;
  readonly attribute CSSPrimitiveValue  blue;
};

// Introduced in DOM Level 2:
interface Rect {
  readonly attribute CSSPrimitiveValue  top;
  readonly attribute CSSPrimitiveValue  right;
  readonly attribute CSSPrimitiveValue  bottom;
  readonly attribute CSSPrimitiveValue  left;
```

```
};

// Introduced in DOM Level 2:
interface Counter {
  readonly attribute DOMString        identifier;
  readonly attribute DOMString        listStyle;
  readonly attribute DOMString        separator;
};

// Introduced in DOM Level 2:
interface ElementCSSInlineStyle {
  readonly attribute CSSStyleDeclaration  style;
};

// Introduced in DOM Level 2:
interface CSS2Properties {
           attribute DOMString        azimuth;
                                      // raises(dom::DOMException) on setting

           attribute DOMString        background;
                                      // raises(dom::DOMException) on setting

           attribute DOMString        backgroundAttachment;
                                      // raises(dom::DOMException) on setting

           attribute DOMString        backgroundColor;
                                      // raises(dom::DOMException) on setting

           attribute DOMString        backgroundImage;
                                      // raises(dom::DOMException) on setting

           attribute DOMString        backgroundPosition;
                                      // raises(dom::DOMException) on setting

           attribute DOMString        backgroundRepeat;
                                      // raises(dom::DOMException) on setting

           attribute DOMString        border;
                                      // raises(dom::DOMException) on setting

           attribute DOMString        borderCollapse;
                                      // raises(dom::DOMException) on setting

           attribute DOMString        borderColor;
                                      // raises(dom::DOMException) on setting

           attribute DOMString        borderSpacing;
                                      // raises(dom::DOMException) on setting

           attribute DOMString        borderStyle;
                                      // raises(dom::DOMException) on setting

           attribute DOMString        borderTop;
                                      // raises(dom::DOMException) on setting

           attribute DOMString        borderRight;
                                      // raises(dom::DOMException) on setting
```

```
attribute DOMString        borderBottom;
                           // raises(dom::DOMException) on setting

attribute DOMString        borderLeft;
                           // raises(dom::DOMException) on setting

attribute DOMString        borderTopColor;
                           // raises(dom::DOMException) on setting

attribute DOMString        borderRightColor;
                           // raises(dom::DOMException) on setting

attribute DOMString        borderBottomColor;
                           // raises(dom::DOMException) on setting

attribute DOMString        borderLeftColor;
                           // raises(dom::DOMException) on setting

attribute DOMString        borderTopStyle;
                           // raises(dom::DOMException) on setting

attribute DOMString        borderRightStyle;
                           // raises(dom::DOMException) on setting

attribute DOMString        borderBottomStyle;
                           // raises(dom::DOMException) on setting

attribute DOMString        borderLeftStyle;
                           // raises(dom::DOMException) on setting

attribute DOMString        borderTopWidth;
                           // raises(dom::DOMException) on setting

attribute DOMString        borderRightWidth;
                           // raises(dom::DOMException) on setting

attribute DOMString        borderBottomWidth;
                           // raises(dom::DOMException) on setting

attribute DOMString        borderLeftWidth;
                           // raises(dom::DOMException) on setting

attribute DOMString        borderWidth;
                           // raises(dom::DOMException) on setting

attribute DOMString        bottom;
                           // raises(dom::DOMException) on setting

attribute DOMString        captionSide;
                           // raises(dom::DOMException) on setting

attribute DOMString        clear;
                           // raises(dom::DOMException) on setting

attribute DOMString        clip;
                           // raises(dom::DOMException) on setting
```

```
attribute DOMString        color;
                           // raises(dom::DOMException) on setting

attribute DOMString        content;
                           // raises(dom::DOMException) on setting

attribute DOMString        counterIncrement;
                           // raises(dom::DOMException) on setting

attribute DOMString        counterReset;
                           // raises(dom::DOMException) on setting

attribute DOMString        cue;
                           // raises(dom::DOMException) on setting

attribute DOMString        cueAfter;
                           // raises(dom::DOMException) on setting

attribute DOMString        cueBefore;
                           // raises(dom::DOMException) on setting

attribute DOMString        cursor;
                           // raises(dom::DOMException) on setting

attribute DOMString        direction;
                           // raises(dom::DOMException) on setting

attribute DOMString        display;
                           // raises(dom::DOMException) on setting

attribute DOMString        elevation;
                           // raises(dom::DOMException) on setting

attribute DOMString        emptyCells;
                           // raises(dom::DOMException) on setting

attribute DOMString        cssFloat;
                           // raises(dom::DOMException) on setting

attribute DOMString        font;
                           // raises(dom::DOMException) on setting

attribute DOMString        fontFamily;
                           // raises(dom::DOMException) on setting

attribute DOMString        fontSize;
                           // raises(dom::DOMException) on setting

attribute DOMString        fontSizeAdjust;
                           // raises(dom::DOMException) on setting

attribute DOMString        fontStretch;
                           // raises(dom::DOMException) on setting

attribute DOMString        fontStyle;
                           // raises(dom::DOMException) on setting
```

```
attribute DOMString        fontVariant;
                           // raises(dom::DOMException) on setting

attribute DOMString        fontWeight;
                           // raises(dom::DOMException) on setting

attribute DOMString        height;
                           // raises(dom::DOMException) on setting

attribute DOMString        left;
                           // raises(dom::DOMException) on setting

attribute DOMString        letterSpacing;
                           // raises(dom::DOMException) on setting

attribute DOMString        lineHeight;
                           // raises(dom::DOMException) on setting

attribute DOMString        listStyle;
                           // raises(dom::DOMException) on setting

attribute DOMString        listStyleImage;
                           // raises(dom::DOMException) on setting

attribute DOMString        listStylePosition;
                           // raises(dom::DOMException) on setting

attribute DOMString        listStyleType;
                           // raises(dom::DOMException) on setting

attribute DOMString        margin;
                           // raises(dom::DOMException) on setting

attribute DOMString        marginTop;
                           // raises(dom::DOMException) on setting

attribute DOMString        marginRight;
                           // raises(dom::DOMException) on setting

attribute DOMString        marginBottom;
                           // raises(dom::DOMException) on setting

attribute DOMString        marginLeft;
                           // raises(dom::DOMException) on setting

attribute DOMString        markerOffset;
                           // raises(dom::DOMException) on setting

attribute DOMString        marks;
                           // raises(dom::DOMException) on setting

attribute DOMString        maxHeight;
                           // raises(dom::DOMException) on setting

attribute DOMString        maxWidth;
                           // raises(dom::DOMException) on setting
```

```
attribute DOMString        minHeight;
                           // raises(dom::DOMException) on setting

attribute DOMString        minWidth;
                           // raises(dom::DOMException) on setting

attribute DOMString        orphans;
                           // raises(dom::DOMException) on setting

attribute DOMString        outline;
                           // raises(dom::DOMException) on setting

attribute DOMString        outlineColor;
                           // raises(dom::DOMException) on setting

attribute DOMString        outlineStyle;
                           // raises(dom::DOMException) on setting

attribute DOMString        outlineWidth;
                           // raises(dom::DOMException) on setting

attribute DOMString        overflow;
                           // raises(dom::DOMException) on setting

attribute DOMString        padding;
                           // raises(dom::DOMException) on setting

attribute DOMString        paddingTop;
                           // raises(dom::DOMException) on setting

attribute DOMString        paddingRight;
                           // raises(dom::DOMException) on setting

attribute DOMString        paddingBottom;
                           // raises(dom::DOMException) on setting

attribute DOMString        paddingLeft;
                           // raises(dom::DOMException) on setting

attribute DOMString        page;
                           // raises(dom::DOMException) on setting

attribute DOMString        pageBreakAfter;
                           // raises(dom::DOMException) on setting

attribute DOMString        pageBreakBefore;
                           // raises(dom::DOMException) on setting

attribute DOMString        pageBreakInside;
                           // raises(dom::DOMException) on setting

attribute DOMString        pause;
                           // raises(dom::DOMException) on setting

attribute DOMString        pauseAfter;
                           // raises(dom::DOMException) on setting
```

```
attribute DOMString        pauseBefore;
                           // raises(dom::DOMException) on setting

attribute DOMString        pitch;
                           // raises(dom::DOMException) on setting

attribute DOMString        pitchRange;
                           // raises(dom::DOMException) on setting

attribute DOMString        playDuring;
                           // raises(dom::DOMException) on setting

attribute DOMString        position;
                           // raises(dom::DOMException) on setting

attribute DOMString        quotes;
                           // raises(dom::DOMException) on setting

attribute DOMString        richness;
                           // raises(dom::DOMException) on setting

attribute DOMString        right;
                           // raises(dom::DOMException) on setting

attribute DOMString        size;
                           // raises(dom::DOMException) on setting

attribute DOMString        speak;
                           // raises(dom::DOMException) on setting

attribute DOMString        speakHeader;
                           // raises(dom::DOMException) on setting

attribute DOMString        speakNumeral;
                           // raises(dom::DOMException) on setting

attribute DOMString        speakPunctuation;
                           // raises(dom::DOMException) on setting

attribute DOMString        speechRate;
                           // raises(dom::DOMException) on setting

attribute DOMString        stress;
                           // raises(dom::DOMException) on setting

attribute DOMString        tableLayout;
                           // raises(dom::DOMException) on setting

attribute DOMString        textAlign;
                           // raises(dom::DOMException) on setting

attribute DOMString        textDecoration;
                           // raises(dom::DOMException) on setting

attribute DOMString        textIndent;
                           // raises(dom::DOMException) on setting
```

```
            attribute DOMString        textShadow;
                                       // raises(dom::DOMException) on setting

            attribute DOMString        textTransform;
                                       // raises(dom::DOMException) on setting

            attribute DOMString        top;
                                       // raises(dom::DOMException) on setting

            attribute DOMString        unicodeBidi;
                                       // raises(dom::DOMException) on setting

            attribute DOMString        verticalAlign;
                                       // raises(dom::DOMException) on setting

            attribute DOMString        visibility;
                                       // raises(dom::DOMException) on setting

            attribute DOMString        voiceFamily;
                                       // raises(dom::DOMException) on setting

            attribute DOMString        volume;
                                       // raises(dom::DOMException) on setting

            attribute DOMString        whiteSpace;
                                       // raises(dom::DOMException) on setting

            attribute DOMString        widows;
                                       // raises(dom::DOMException) on setting

            attribute DOMString        width;
                                       // raises(dom::DOMException) on setting

            attribute DOMString        wordSpacing;
                                       // raises(dom::DOMException) on setting

            attribute DOMString        zIndex;
                                       // raises(dom::DOMException) on setting

};

// Introduced in DOM Level 2:
interface CSSStyleSheet : stylesheets::StyleSheet {
  readonly attribute CSSRule          ownerRule;
  readonly attribute CSSRuleList      cssRules;
  unsigned long      insertRule(in DOMString rule,
                                in unsigned long index)
                                       raises(dom::DOMException);
  void               deleteRule(in unsigned long index)
                                       raises(dom::DOMException);
};

// Introduced in DOM Level 2:
interface ViewCSS : views::AbstractView {
  CSSStyleDeclaration getComputedStyle(in Element elt,
                                       in DOMString pseudoElt);
```

```
  };

  // Introduced in DOM Level 2:
  interface DocumentCSS : stylesheets::DocumentStyle {
    CSSStyleDeclaration getOverrideStyle(in Element elt,
                                         in DOMString pseudoElt);
  };

  // Introduced in DOM   Level 2:
  interface DOMImplementationCSS : DOMImplementation {
    CSSStyleSheet      createCSSStyleSheet(in DOMString title,
                                           in DOMString media)
                                        raises(dom::DOMException);
  };
};

#endif // _CSS_IDL_
```

css.idl:

Appendix B: Java Language Binding

This appendix contains the complete Java Language [Java] binding for the Level 2 Document Object Model Style. The definitions are divided into StyleSheets [p.93] and CSS [p.94] .

The Java files are also available as
http://www.w3.org/TR/2000/REC-DOM-Level-2-Style-20001113/java-binding.zip

B.1: Document Object Model Style Sheets

org/w3c/dom/stylesheets/StyleSheet.java:

```
package org.w3c.dom.stylesheets;

import org.w3c.dom.Node;

public interface StyleSheet {
    public String getType();

    public boolean getDisabled();
    public void setDisabled(boolean disabled);

    public Node getOwnerNode();

    public StyleSheet getParentStyleSheet();

    public String getHref();

    public String getTitle();

    public MediaList getMedia();

}
```

org/w3c/dom/stylesheets/StyleSheetList.java:

```
package org.w3c.dom.stylesheets;

public interface StyleSheetList {
    public int getLength();

    public StyleSheet item(int index);

}
```

org/w3c/dom/stylesheets/MediaList.java:

```
package org.w3c.dom.stylesheets;

import org.w3c.dom.DOMException;

public interface MediaList {
```

```
    public String getMediaText();
    public void setMediaText(String mediaText)
                          throws DOMException;

    public int getLength();

    public String item(int index);

    public void deleteMedium(String oldMedium)
                            throws DOMException;

    public void appendMedium(String newMedium)
                            throws DOMException;

}
```

org/w3c/dom/stylesheets/LinkStyle.java:

```
package org.w3c.dom.stylesheets;

public interface LinkStyle {
    public StyleSheet getSheet();

}
```

org/w3c/dom/stylesheets/DocumentStyle.java:

```
package org.w3c.dom.stylesheets;

public interface DocumentStyle {
    public StyleSheetList getStyleSheets();

}
```

B.2: Document Object Model CSS

org/w3c/dom/css/CSSStyleSheet.java:

```
package org.w3c.dom.css;

import org.w3c.dom.DOMException;
import org.w3c.dom.stylesheets.StyleSheet;

public interface CSSStyleSheet extends StyleSheet {
    public CSSRule getOwnerRule();

    public CSSRuleList getCssRules();

    public int insertRule(String rule,
                          int index)
                          throws DOMException;
```

```
    public void deleteRule(int index)
                           throws DOMException;

}
```

org/w3c/dom/css/CSSRuleList.java:

```
package org.w3c.dom.css;

public interface CSSRuleList {
    public int getLength();

    public CSSRule item(int index);

}
```

org/w3c/dom/css/CSSRule.java:

```
package org.w3c.dom.css;

import org.w3c.dom.DOMException;

public interface CSSRule {
    // RuleType
    public static final short UNKNOWN_RULE              = 0;
    public static final short STYLE_RULE                = 1;
    public static final short CHARSET_RULE              = 2;
    public static final short IMPORT_RULE               = 3;
    public static final short MEDIA_RULE                = 4;
    public static final short FONT_FACE_RULE            = 5;
    public static final short PAGE_RULE                 = 6;

    public short getType();

    public String getCssText();
    public void setCssText(String cssText)
                        throws DOMException;

    public CSSStyleSheet getParentStyleSheet();

    public CSSRule getParentRule();

}
```

org/w3c/dom/css/CSSStyleRule.java:

```
package org.w3c.dom.css;

import org.w3c.dom.DOMException;

public interface CSSStyleRule extends CSSRule {
    public String getSelectorText();
    public void setSelectorText(String selectorText)
                        throws DOMException;
```

```
    public CSSStyleDeclaration getStyle();

}
```

org/w3c/dom/css/CSSMediaRule.java:

```
package org.w3c.dom.css;

import org.w3c.dom.DOMException;
import org.w3c.dom.stylesheets.MediaList;

public interface CSSMediaRule extends CSSRule {
    public MediaList getMedia();

    public CSSRuleList getCssRules();

    public int insertRule(String rule,
                          int index)
                          throws DOMException;

    public void deleteRule(int index)
                           throws DOMException;

}
```

org/w3c/dom/css/CSSFontFaceRule.java:

```
package org.w3c.dom.css;

public interface CSSFontFaceRule extends CSSRule {
    public CSSStyleDeclaration getStyle();

}
```

org/w3c/dom/css/CSSPageRule.java:

```
package org.w3c.dom.css;

import org.w3c.dom.DOMException;

public interface CSSPageRule extends CSSRule {
    public String getSelectorText();
    public void setSelectorText(String selectorText)
                           throws DOMException;

    public CSSStyleDeclaration getStyle();

}
```

org/w3c/dom/css/CSSImportRule.java:

```
package org.w3c.dom.css;

import org.w3c.dom.stylesheets.MediaList;

public interface CSSImportRule extends CSSRule {
    public String getHref();

    public MediaList getMedia();

    public CSSStyleSheet getStyleSheet();

}
```

org/w3c/dom/css/CSSCharsetRule.java:

```
package org.w3c.dom.css;

import org.w3c.dom.DOMException;

public interface CSSCharsetRule extends CSSRule {
    public String getEncoding();
    public void setEncoding(String encoding)
                            throws DOMException;

}
```

org/w3c/dom/css/CSSUnknownRule.java:

```
package org.w3c.dom.css;

public interface CSSUnknownRule extends CSSRule {
}
```

org/w3c/dom/css/CSSStyleDeclaration.java:

```
package org.w3c.dom.css;

import org.w3c.dom.DOMException;

public interface CSSStyleDeclaration {
    public String getCssText();
    public void setCssText(String cssText)
                            throws DOMException;

    public String getPropertyValue(String propertyName);

    public CSSValue getPropertyCSSValue(String propertyName);

    public String removeProperty(String propertyName)
                                 throws DOMException;

    public String getPropertyPriority(String propertyName);
```

```
    public void setProperty(String propertyName,
                            String value,
                            String priority)
                            throws DOMException;

    public int getLength();

    public String item(int index);

    public CSSRule getParentRule();

}
```

org/w3c/dom/css/CSSValue.java:

```
package org.w3c.dom.css;

import org.w3c.dom.DOMException;

public interface CSSValue {
    // UnitTypes
    public static final short CSS_INHERIT               = 0;
    public static final short CSS_PRIMITIVE_VALUE       = 1;
    public static final short CSS_VALUE_LIST            = 2;
    public static final short CSS_CUSTOM                = 3;

    public String getCssText();
    public void setCssText(String cssText)
                        throws DOMException;

    public short getCssValueType();

}
```

org/w3c/dom/css/CSSPrimitiveValue.java:

```
package org.w3c.dom.css;

import org.w3c.dom.DOMException;

public interface CSSPrimitiveValue extends CSSValue {
    // UnitTypes
    public static final short CSS_UNKNOWN               = 0;
    public static final short CSS_NUMBER                = 1;
    public static final short CSS_PERCENTAGE            = 2;
    public static final short CSS_EMS                   = 3;
    public static final short CSS_EXS                   = 4;
    public static final short CSS_PX                    = 5;
    public static final short CSS_CM                    = 6;
    public static final short CSS_MM                    = 7;
    public static final short CSS_IN                    = 8;
    public static final short CSS_PT                    = 9;
    public static final short CSS_PC                    = 10;
    public static final short CSS_DEG                   = 11;
    public static final short CSS_RAD                   = 12;
    public static final short CSS_GRAD                  = 13;
```

```
    public static final short CSS_MS                    = 14;
    public static final short CSS_S                     = 15;
    public static final short CSS_HZ                    = 16;
    public static final short CSS_KHZ                   = 17;
    public static final short CSS_DIMENSION             = 18;
    public static final short CSS_STRING                = 19;
    public static final short CSS_URI                   = 20;
    public static final short CSS_IDENT                 = 21;
    public static final short CSS_ATTR                  = 22;
    public static final short CSS_COUNTER               = 23;
    public static final short CSS_RECT                  = 24;
    public static final short CSS_RGBCOLOR              = 25;

    public short getPrimitiveType();

    public void setFloatValue(short unitType,
                              float floatValue)
                              throws DOMException;

    public float getFloatValue(short unitType)
                               throws DOMException;

    public void setStringValue(short stringType,
                               String stringValue)
                               throws DOMException;

    public String getStringValue()
                                 throws DOMException;

    public Counter getCounterValue()
                                   throws DOMException;

    public Rect getRectValue()
                             throws DOMException;

    public RGBColor getRGBColorValue()
                                     throws DOMException;

}
```

org/w3c/dom/css/CSSValueList.java:

```
package org.w3c.dom.css;

public interface CSSValueList extends CSSValue {
    public int getLength();

    public CSSValue item(int index);

}
```

org/w3c/dom/css/RGBColor.java:

```
package org.w3c.dom.css;

public interface RGBColor {
    public CSSPrimitiveValue getRed();

    public CSSPrimitiveValue getGreen();

    public CSSPrimitiveValue getBlue();

}
```

org/w3c/dom/css/Rect.java:

```
package org.w3c.dom.css;

public interface Rect {
    public CSSPrimitiveValue getTop();

    public CSSPrimitiveValue getRight();

    public CSSPrimitiveValue getBottom();

    public CSSPrimitiveValue getLeft();

}
```

org/w3c/dom/css/Counter.java:

```
package org.w3c.dom.css;

public interface Counter {
    public String getIdentifier();

    public String getListStyle();

    public String getSeparator();

}
```

org/w3c/dom/css/ViewCSS.java:

```
package org.w3c.dom.css;

import org.w3c.dom.views.AbstractView;
import org.w3c.dom.Element;

public interface ViewCSS extends AbstractView {
    public CSSStyleDeclaration getComputedStyle(Element elt,
                                                String pseudoElt);

}
```

org/w3c/dom/css/DocumentCSS.java:

```
package org.w3c.dom.css;

import org.w3c.dom.stylesheets.DocumentStyle;
import org.w3c.dom.Element;

public interface DocumentCSS extends DocumentStyle {
    public CSSStyleDeclaration getOverrideStyle(Element elt,
                                                String pseudoElt);

}
```

org/w3c/dom/css/DOMImplementationCSS.java:

```
package org.w3c.dom.css;

import org.w3c.dom.DOMImplementation;
import org.w3c.dom.DOMException;

public interface DOMImplementationCSS extends DOMImplementation {
    public CSSStyleSheet createCSSStyleSheet(String title,
                                             String media)
                                             throws DOMException;

}
```

org/w3c/dom/css/ElementCSSInlineStyle.java:

```
package org.w3c.dom.css;

public interface ElementCSSInlineStyle {
    public CSSStyleDeclaration getStyle();

}
```

org/w3c/dom/css/CSS2Properties.java:

```
package org.w3c.dom.css;

import org.w3c.dom.DOMException;

public interface CSS2Properties {
    public String getAzimuth();
    public void setAzimuth(String azimuth)
                                             throws DOMException;

    public String getBackground();
    public void setBackground(String background)
                                             throws DOMException;

    public String getBackgroundAttachment();
    public void setBackgroundAttachment(String backgroundAttachment)
                                             throws DOMException;
```

```
public String getBackgroundColor();
public void setBackgroundColor(String backgroundColor)
                                        throws DOMException;

public String getBackgroundImage();
public void setBackgroundImage(String backgroundImage)
                                        throws DOMException;

public String getBackgroundPosition();
public void setBackgroundPosition(String backgroundPosition)
                                        throws DOMException;

public String getBackgroundRepeat();
public void setBackgroundRepeat(String backgroundRepeat)
                                        throws DOMException;

public String getBorder();
public void setBorder(String border)
                                        throws DOMException;

public String getBorderCollapse();
public void setBorderCollapse(String borderCollapse)
                                        throws DOMException;

public String getBorderColor();
public void setBorderColor(String borderColor)
                                        throws DOMException;

public String getBorderSpacing();
public void setBorderSpacing(String borderSpacing)
                                        throws DOMException;

public String getBorderStyle();
public void setBorderStyle(String borderStyle)
                                        throws DOMException;

public String getBorderTop();
public void setBorderTop(String borderTop)
                                        throws DOMException;

public String getBorderRight();
public void setBorderRight(String borderRight)
                                        throws DOMException;

public String getBorderBottom();
public void setBorderBottom(String borderBottom)
                                        throws DOMException;

public String getBorderLeft();
public void setBorderLeft(String borderLeft)
                                        throws DOMException;

public String getBorderTopColor();
public void setBorderTopColor(String borderTopColor)
                                        throws DOMException;

public String getBorderRightColor();
```

```
public void setBorderRightColor(String borderRightColor)
                                        throws DOMException;

public String getBorderBottomColor();
public void setBorderBottomColor(String borderBottomColor)
                                        throws DOMException;

public String getBorderLeftColor();
public void setBorderLeftColor(String borderLeftColor)
                                        throws DOMException;

public String getBorderTopStyle();
public void setBorderTopStyle(String borderTopStyle)
                                        throws DOMException;

public String getBorderRightStyle();
public void setBorderRightStyle(String borderRightStyle)
                                        throws DOMException;

public String getBorderBottomStyle();
public void setBorderBottomStyle(String borderBottomStyle)
                                        throws DOMException;

public String getBorderLeftStyle();
public void setBorderLeftStyle(String borderLeftStyle)
                                        throws DOMException;

public String getBorderTopWidth();
public void setBorderTopWidth(String borderTopWidth)
                                        throws DOMException;

public String getBorderRightWidth();
public void setBorderRightWidth(String borderRightWidth)
                                        throws DOMException;

public String getBorderBottomWidth();
public void setBorderBottomWidth(String borderBottomWidth)
                                        throws DOMException;

public String getBorderLeftWidth();
public void setBorderLeftWidth(String borderLeftWidth)
                                        throws DOMException;

public String getBorderWidth();
public void setBorderWidth(String borderWidth)
                                        throws DOMException;

public String getBottom();
public void setBottom(String bottom)
                                        throws DOMException;

public String getCaptionSide();
public void setCaptionSide(String captionSide)
                                        throws DOMException;

public String getClear();
public void setClear(String clear)
```

```
                                        throws DOMException;

public String getClip();
public void setClip(String clip)
                                        throws DOMException;

public String getColor();
public void setColor(String color)
                                        throws DOMException;

public String getContent();
public void setContent(String content)
                                        throws DOMException;

public String getCounterIncrement();
public void setCounterIncrement(String counterIncrement)
                                        throws DOMException;

public String getCounterReset();
public void setCounterReset(String counterReset)
                                        throws DOMException;

public String getCue();
public void setCue(String cue)
                                        throws DOMException;

public String getCueAfter();
public void setCueAfter(String cueAfter)
                                        throws DOMException;

public String getCueBefore();
public void setCueBefore(String cueBefore)
                                        throws DOMException;

public String getCursor();
public void setCursor(String cursor)
                                        throws DOMException;

public String getDirection();
public void setDirection(String direction)
                                        throws DOMException;

public String getDisplay();
public void setDisplay(String display)
                                        throws DOMException;

public String getElevation();
public void setElevation(String elevation)
                                        throws DOMException;

public String getEmptyCells();
public void setEmptyCells(String emptyCells)
                                        throws DOMException;

public String getCssFloat();
public void setCssFloat(String cssFloat)
                                        throws DOMException;
```

```
public String getFont();
public void setFont(String font)
                                        throws DOMException;

public String getFontFamily();
public void setFontFamily(String fontFamily)
                                        throws DOMException;

public String getFontSize();
public void setFontSize(String fontSize)
                                        throws DOMException;

public String getFontSizeAdjust();
public void setFontSizeAdjust(String fontSizeAdjust)
                                        throws DOMException;

public String getFontStretch();
public void setFontStretch(String fontStretch)
                                        throws DOMException;

public String getFontStyle();
public void setFontStyle(String fontStyle)
                                        throws DOMException;

public String getFontVariant();
public void setFontVariant(String fontVariant)
                                        throws DOMException;

public String getFontWeight();
public void setFontWeight(String fontWeight)
                                        throws DOMException;

public String getHeight();
public void setHeight(String height)
                                        throws DOMException;

public String getLeft();
public void setLeft(String left)
                                        throws DOMException;

public String getLetterSpacing();
public void setLetterSpacing(String letterSpacing)
                                        throws DOMException;

public String getLineHeight();
public void setLineHeight(String lineHeight)
                                        throws DOMException;

public String getListStyle();
public void setListStyle(String listStyle)
                                        throws DOMException;

public String getListStyleImage();
public void setListStyleImage(String listStyleImage)
                                        throws DOMException;
```

```
public String getListStylePosition();
public void setListStylePosition(String listStylePosition)
                                        throws DOMException;

public String getListStyleType();
public void setListStyleType(String listStyleType)
                                        throws DOMException;

public String getMargin();
public void setMargin(String margin)
                                        throws DOMException;

public String getMarginTop();
public void setMarginTop(String marginTop)
                                        throws DOMException;

public String getMarginRight();
public void setMarginRight(String marginRight)
                                        throws DOMException;

public String getMarginBottom();
public void setMarginBottom(String marginBottom)
                                        throws DOMException;

public String getMarginLeft();
public void setMarginLeft(String marginLeft)
                                        throws DOMException;

public String getMarkerOffset();
public void setMarkerOffset(String markerOffset)
                                        throws DOMException;

public String getMarks();
public void setMarks(String marks)
                                        throws DOMException;

public String getMaxHeight();
public void setMaxHeight(String maxHeight)
                                        throws DOMException;

public String getMaxWidth();
public void setMaxWidth(String maxWidth)
                                        throws DOMException;

public String getMinHeight();
public void setMinHeight(String minHeight)
                                        throws DOMException;

public String getMinWidth();
public void setMinWidth(String minWidth)
                                        throws DOMException;

public String getOrphans();
public void setOrphans(String orphans)
                                        throws DOMException;

public String getOutline();
```

```
public void setOutline(String outline)
                                        throws DOMException;

public String getOutlineColor();
public void setOutlineColor(String outlineColor)
                                        throws DOMException;

public String getOutlineStyle();
public void setOutlineStyle(String outlineStyle)
                                        throws DOMException;

public String getOutlineWidth();
public void setOutlineWidth(String outlineWidth)
                                        throws DOMException;

public String getOverflow();
public void setOverflow(String overflow)
                                        throws DOMException;

public String getPadding();
public void setPadding(String padding)
                                        throws DOMException;

public String getPaddingTop();
public void setPaddingTop(String paddingTop)
                                        throws DOMException;

public String getPaddingRight();
public void setPaddingRight(String paddingRight)
                                        throws DOMException;

public String getPaddingBottom();
public void setPaddingBottom(String paddingBottom)
                                        throws DOMException;

public String getPaddingLeft();
public void setPaddingLeft(String paddingLeft)
                                        throws DOMException;

public String getPage();
public void setPage(String page)
                                        throws DOMException;

public String getPageBreakAfter();
public void setPageBreakAfter(String pageBreakAfter)
                                        throws DOMException;

public String getPageBreakBefore();
public void setPageBreakBefore(String pageBreakBefore)
                                        throws DOMException;

public String getPageBreakInside();
public void setPageBreakInside(String pageBreakInside)
                                        throws DOMException;

public String getPause();
public void setPause(String pause)
```

```
                                        throws DOMException;

public String getPauseAfter();
public void setPauseAfter(String pauseAfter)
                                        throws DOMException;

public String getPauseBefore();
public void setPauseBefore(String pauseBefore)
                                        throws DOMException;

public String getPitch();
public void setPitch(String pitch)
                                        throws DOMException;

public String getPitchRange();
public void setPitchRange(String pitchRange)
                                        throws DOMException;

public String getPlayDuring();
public void setPlayDuring(String playDuring)
                                        throws DOMException;

public String getPosition();
public void setPosition(String position)
                                        throws DOMException;

public String getQuotes();
public void setQuotes(String quotes)
                                        throws DOMException;

public String getRichness();
public void setRichness(String richness)
                                        throws DOMException;

public String getRight();
public void setRight(String right)
                                        throws DOMException;

public String getSize();
public void setSize(String size)
                                        throws DOMException;

public String getSpeak();
public void setSpeak(String speak)
                                        throws DOMException;

public String getSpeakHeader();
public void setSpeakHeader(String speakHeader)
                                        throws DOMException;

public String getSpeakNumeral();
public void setSpeakNumeral(String speakNumeral)
                                        throws DOMException;

public String getSpeakPunctuation();
public void setSpeakPunctuation(String speakPunctuation)
                                        throws DOMException;
```

```
public String getSpeechRate();
public void setSpeechRate(String speechRate)
                                        throws DOMException;

public String getStress();
public void setStress(String stress)
                                        throws DOMException;

public String getTableLayout();
public void setTableLayout(String tableLayout)
                                        throws DOMException;

public String getTextAlign();
public void setTextAlign(String textAlign)
                                        throws DOMException;

public String getTextDecoration();
public void setTextDecoration(String textDecoration)
                                        throws DOMException;

public String getTextIndent();
public void setTextIndent(String textIndent)
                                        throws DOMException;

public String getTextShadow();
public void setTextShadow(String textShadow)
                                        throws DOMException;

public String getTextTransform();
public void setTextTransform(String textTransform)
                                        throws DOMException;

public String getTop();
public void setTop(String top)
                                        throws DOMException;

public String getUnicodeBidi();
public void setUnicodeBidi(String unicodeBidi)
                                        throws DOMException;

public String getVerticalAlign();
public void setVerticalAlign(String verticalAlign)
                                        throws DOMException;

public String getVisibility();
public void setVisibility(String visibility)
                                        throws DOMException;

public String getVoiceFamily();
public void setVoiceFamily(String voiceFamily)
                                        throws DOMException;

public String getVolume();
public void setVolume(String volume)
                                        throws DOMException;
```

```
    public String getWhiteSpace();
    public void setWhiteSpace(String whiteSpace)
                                            throws DOMException;

    public String getWidows();
    public void setWidows(String widows)
                                            throws DOMException;

    public String getWidth();
    public void setWidth(String width)
                                            throws DOMException;

    public String getWordSpacing();
    public void setWordSpacing(String wordSpacing)
                                            throws DOMException;

    public String getZIndex();
    public void setZIndex(String zIndex)
                                            throws DOMException;

}
```

Appendix C: ECMAScript Language Binding

This appendix contains the complete ECMAScript [ECMAScript] binding for the Level 2 Document Object Model Style definitions. The definitions are divided into StyleSheets [p.111] and CSS [p.112] .

Note: Exceptions handling is only supported by ECMAScript implementation conformant with the Standard ECMA-262 3rd. Edition ([ECMAScript]).

C.1: Document Object Model StyleSheets

Object **StyleSheet**

The **StyleSheet** object has the following properties:

type

This read-only property is of type **String**.

disabled

This property is of type **Boolean**.

ownerNode

This read-only property is a **Node** object.

parentStyleSheet

This read-only property is a **StyleSheet** object.

href

This read-only property is of type **String**.

title

This read-only property is of type **String**.

media

This read-only property is a **MediaList** object.

Object **StyleSheetList**

The **StyleSheetList** object has the following properties:

length

This read-only property is of type **Number**.

The **StyleSheetList** object has the following methods:

item(index)

This method returns a **StyleSheet** object.

The **index** parameter is of type **Number**.

Note: This object can also be dereferenced using square bracket notation (e.g. obj[1]). Dereferencing with an integer **index** is equivalent to invoking the **item** method with that index.

Object **MediaList**

The **MediaList** object has the following properties:

mediaText

This property is of type **String** and can raise a **DOMException** object on setting.

length

This read-only property is of type **Number**.

The **MediaList** object has the following methods:

item(index)
This method returns a **String**.
The **index** parameter is of type **Number**.
Note: This object can also be dereferenced using square bracket notation (e.g. obj[1]). Dereferencing with an integer **index** is equivalent to invoking the **item** method with that index.

deleteMedium(oldMedium)
This method has no return value.
The **oldMedium** parameter is of type **String**.
This method can raise a **DOMException** object.

appendMedium(newMedium)
This method has no return value.
The **newMedium** parameter is of type **String**.
This method can raise a **DOMException** object.

Object **LinkStyle**

The **LinkStyle** object has the following properties:

sheet
This read-only property is a **StyleSheet** object.

Object **DocumentStyle**

The **DocumentStyle** object has the following properties:

styleSheets
This read-only property is a **StyleSheetList** object.

C.2: Document Object Model CSS

Object **CSSStyleSheet**

CSSStyleSheet has the all the properties and methods of the **StyleSheet** object as well as the properties and methods defined below.

The **CSSStyleSheet** object has the following properties:

ownerRule
This read-only property is a **CSSRule** object.

cssRules
This read-only property is a **CSSRuleList** object.

The **CSSStyleSheet** object has the following methods:

insertRule(rule, index)
This method returns a **Number**.
The **rule** parameter is of type **String**.
The **index** parameter is of type **Number**.
This method can raise a **DOMException** object.

deleteRule(index)
This method has no return value.
The **index** parameter is of type **Number**.
This method can raise a **DOMException** object.

Object **CSSRuleList**

The **CSSRuleList** object has the following properties:

length

This read-only property is of type **Number**.

The **CSSRuleList** object has the following methods:

item(index)

This method returns a **CSSRule** object.

The **index** parameter is of type **Number**.

Note: This object can also be dereferenced using square bracket notation (e.g. obj[1]). Dereferencing with an integer **index** is equivalent to invoking the **item** method with that index.

Prototype Object **CSSRule**

The **CSSRule** class has the following constants:

CSSRule.UNKNOWN_RULE

This constant is of type **Number** and its value is **0**.

CSSRule.STYLE_RULE

This constant is of type **Number** and its value is **1**.

CSSRule.CHARSET_RULE

This constant is of type **Number** and its value is **2**.

CSSRule.IMPORT_RULE

This constant is of type **Number** and its value is **3**.

CSSRule.MEDIA_RULE

This constant is of type **Number** and its value is **4**.

CSSRule.FONT_FACE_RULE

This constant is of type **Number** and its value is **5**.

CSSRule.PAGE_RULE

This constant is of type **Number** and its value is **6**.

Object **CSSRule**

The **CSSRule** object has the following properties:

type

This read-only property is of type **Number**.

cssText

This property is of type **String** and can raise a **DOMException** object on setting.

parentStyleSheet

This read-only property is a **CSSStyleSheet** object.

parentRule

This read-only property is a **CSSRule** object.

Object **CSSStyleRule**

CSSStyleRule has the all the properties and methods of the **CSSRule** object as well as the properties and methods defined below.

The **CSSStyleRule** object has the following properties:

selectorText

This property is of type **String** and can raise a **DOMException** object on setting.

style

This read-only property is a **CSSStyleDeclaration** object.

Object **CSSMediaRule**

CSSMediaRule has the all the properties and methods of the **CSSRule** object as well as the properties and methods defined below.

The **CSSMediaRule** object has the following properties:

media

This read-only property is a **MediaList** object.

cssRules

This read-only property is a **CSSRuleList** object.

The **CSSMediaRule** object has the following methods:

insertRule(rule, index)

This method returns a **Number**.

The **rule** parameter is of type **String**.

The **index** parameter is of type **Number**.

This method can raise a **DOMException** object.

deleteRule(index)

This method has no return value.

The **index** parameter is of type **Number**.

This method can raise a **DOMException** object.

Object **CSSFontFaceRule**

CSSFontFaceRule has the all the properties and methods of the **CSSRule** object as well as the properties and methods defined below.

The **CSSFontFaceRule** object has the following properties:

style

This read-only property is a **CSSStyleDeclaration** object.

Object **CSSPageRule**

CSSPageRule has the all the properties and methods of the **CSSRule** object as well as the properties and methods defined below.

The **CSSPageRule** object has the following properties:

selectorText

This property is of type **String** and can raise a **DOMException** object on setting.

style

This read-only property is a **CSSStyleDeclaration** object.

Object **CSSImportRule**

CSSImportRule has the all the properties and methods of the **CSSRule** object as well as the properties and methods defined below.

The **CSSImportRule** object has the following properties:

href

This read-only property is of type **String**.

media

This read-only property is a **MediaList** object.

styleSheet

This read-only property is a **CSSStyleSheet** object.

Object **CSSCharsetRule**

CSSCharsetRule has the all the properties and methods of the **CSSRule** object as well as the properties and methods defined below.

The **CSSCharsetRule** object has the following properties:

encoding
This property is of type **String** and can raise a **DOMException** object on setting.

Object **CSSUnknownRule**

CSSUnknownRule has the all the properties and methods of the **CSSRule** object as well as the properties and methods defined below.

Object **CSSStyleDeclaration**

The **CSSStyleDeclaration** object has the following properties:

cssText
This property is of type **String** and can raise a **DOMException** object on setting.

length
This read-only property is of type **Number**.

parentRule
This read-only property is a **CSSRule** object.

The **CSSStyleDeclaration** object has the following methods:

getPropertyValue(propertyName)
This method returns a **String**.
The **propertyName** parameter is of type **String**.

getPropertyCSSValue(propertyName)
This method returns a **CSSValue** object.
The **propertyName** parameter is of type **String**.

removeProperty(propertyName)
This method returns a **String**.
The **propertyName** parameter is of type **String**.
This method can raise a **DOMException** object.

getPropertyPriority(propertyName)
This method returns a **String**.
The **propertyName** parameter is of type **String**.

setProperty(propertyName, value, priority)
This method has no return value.
The **propertyName** parameter is of type **String**.
The **value** parameter is of type **String**.
The **priority** parameter is of type **String**.
This method can raise a **DOMException** object.

item(index)
This method returns a **String**.
The **index** parameter is of type **Number**.
Note: This object can also be dereferenced using square bracket notation (e.g. obj[1]). Dereferencing with an integer **index** is equivalent to invoking the **item** method with that index.

Prototype Object **CSSValue**

The **CSSValue** class has the following constants:

CSSValue.CSS_INHERIT
This constant is of type **Number** and its value is **0**.

CSSValue.CSS_PRIMITIVE_VALUE
This constant is of type **Number** and its value is **1**.

CSSValue.CSS_VALUE_LIST
This constant is of type **Number** and its value is **2**.
CSSValue.CSS_CUSTOM
This constant is of type **Number** and its value is **3**.

Object **CSSValue**

The **CSSValue** object has the following properties:

cssText
This property is of type **String** and can raise a **DOMException** object on setting.
cssValueType
This read-only property is of type **Number**.

Prototype Object **CSSPrimitiveValue**

The **CSSPrimitiveValue** class has the following constants:

CSSPrimitiveValue.CSS_UNKNOWN
This constant is of type **Number** and its value is **0**.
CSSPrimitiveValue.CSS_NUMBER
This constant is of type **Number** and its value is **1**.
CSSPrimitiveValue.CSS_PERCENTAGE
This constant is of type **Number** and its value is **2**.
CSSPrimitiveValue.CSS_EMS
This constant is of type **Number** and its value is **3**.
CSSPrimitiveValue.CSS_EXS
This constant is of type **Number** and its value is **4**.
CSSPrimitiveValue.CSS_PX
This constant is of type **Number** and its value is **5**.
CSSPrimitiveValue.CSS_CM
This constant is of type **Number** and its value is **6**.
CSSPrimitiveValue.CSS_MM
This constant is of type **Number** and its value is **7**.
CSSPrimitiveValue.CSS_IN
This constant is of type **Number** and its value is **8**.
CSSPrimitiveValue.CSS_PT
This constant is of type **Number** and its value is **9**.
CSSPrimitiveValue.CSS_PC
This constant is of type **Number** and its value is **10**.
CSSPrimitiveValue.CSS_DEG
This constant is of type **Number** and its value is **11**.
CSSPrimitiveValue.CSS_RAD
This constant is of type **Number** and its value is **12**.
CSSPrimitiveValue.CSS_GRAD
This constant is of type **Number** and its value is **13**.
CSSPrimitiveValue.CSS_MS
This constant is of type **Number** and its value is **14**.
CSSPrimitiveValue.CSS_S
This constant is of type **Number** and its value is **15**.
CSSPrimitiveValue.CSS_HZ
This constant is of type **Number** and its value is **16**.

CSSPrimitiveValue.CSS_KHZ
This constant is of type **Number** and its value is **17**.
CSSPrimitiveValue.CSS_DIMENSION
This constant is of type **Number** and its value is **18**.
CSSPrimitiveValue.CSS_STRING
This constant is of type **Number** and its value is **19**.
CSSPrimitiveValue.CSS_URI
This constant is of type **Number** and its value is **20**.
CSSPrimitiveValue.CSS_IDENT
This constant is of type **Number** and its value is **21**.
CSSPrimitiveValue.CSS_ATTR
This constant is of type **Number** and its value is **22**.
CSSPrimitiveValue.CSS_COUNTER
This constant is of type **Number** and its value is **23**.
CSSPrimitiveValue.CSS_RECT
This constant is of type **Number** and its value is **24**.
CSSPrimitiveValue.CSS_RGBCOLOR
This constant is of type **Number** and its value is **25**.

Object **CSSPrimitiveValue**

CSSPrimitiveValue has the all the properties and methods of the **CSSValue** object as well as the properties and methods defined below.

The **CSSPrimitiveValue** object has the following properties:

primitiveType
This read-only property is of type **Number**.

The **CSSPrimitiveValue** object has the following methods:

setFloatValue(unitType, floatValue)
This method has no return value.
The **unitType** parameter is of type **Number**.
The **floatValue** parameter is a **float** object.
This method can raise a **DOMException** object.

getFloatValue(unitType)
This method returns a **float** object.
The **unitType** parameter is of type **Number**.
This method can raise a **DOMException** object.

setStringValue(stringType, stringValue)
This method has no return value.
The **stringType** parameter is of type **Number**.
The **stringValue** parameter is of type **String**.
This method can raise a **DOMException** object.

getStringValue()
This method returns a **String**.
This method can raise a **DOMException** object.

getCounterValue()
This method returns a **Counter** object.
This method can raise a **DOMException** object.

getRectValue()
This method returns a **Rect** object.
This method can raise a **DOMException** object.
getRGBColorValue()
This method returns a **RGBColor** object.
This method can raise a **DOMException** object.

Object **CSSValueList**

CSSValueList has the all the properties and methods of the **CSSValue** object as well as the properties and methods defined below.

The **CSSValueList** object has the following properties:

length
This read-only property is of type **Number**.

The **CSSValueList** object has the following methods:

item(index)
This method returns a **CSSValue** object.
The **index** parameter is of type **Number**.
Note: This object can also be dereferenced using square bracket notation (e.g. obj[1]). Dereferencing with an integer **index** is equivalent to invoking the **item** method with that index.

Object **RGBColor**

The **RGBColor** object has the following properties:

red
This read-only property is a **CSSPrimitiveValue** object.
green
This read-only property is a **CSSPrimitiveValue** object.
blue
This read-only property is a **CSSPrimitiveValue** object.

Object **Rect**

The **Rect** object has the following properties:

top
This read-only property is a **CSSPrimitiveValue** object.
right
This read-only property is a **CSSPrimitiveValue** object.
bottom
This read-only property is a **CSSPrimitiveValue** object.
left
This read-only property is a **CSSPrimitiveValue** object.

Object **Counter**

The **Counter** object has the following properties:

identifier
This read-only property is of type **String**.
listStyle
This read-only property is of type **String**.
separator
This read-only property is of type **String**.

Object **ViewCSS**

ViewCSS has the all the properties and methods of the **AbstractView** object as well as the properties and methods defined below.

The **ViewCSS** object has the following methods:

getComputedStyle(elt, pseudoElt)

This method returns a **CSSStyleDeclaration** object.
The **elt** parameter is a **Element** object.
The **pseudoElt** parameter is of type **String**.

Object **DocumentCSS**

DocumentCSS has the all the properties and methods of the **DocumentStyle** object as well as the properties and methods defined below.

The **DocumentCSS** object has the following methods:

getOverrideStyle(elt, pseudoElt)

This method returns a **CSSStyleDeclaration** object.
The **elt** parameter is a **Element** object.
The **pseudoElt** parameter is of type **String**.

Object **DOMImplementationCSS**

DOMImplementationCSS has the all the properties and methods of the **DOMImplementation** object as well as the properties and methods defined below.

The **DOMImplementationCSS** object has the following methods:

createCSSStyleSheet(title, media)

This method returns a **CSSStyleSheet** object.
The **title** parameter is of type **String**.
The **media** parameter is of type **String**.
This method can raise a **DOMException** object.

Object **ElementCSSInlineStyle**

The **ElementCSSInlineStyle** object has the following properties:

style

This read-only property is a **CSSStyleDeclaration** object.

Object **CSS2Properties**

The **CSS2Properties** object has the following properties:

azimuth

This property is of type **String** and can raise a **DOMException** object on setting.

background

This property is of type **String** and can raise a **DOMException** object on setting.

backgroundAttachment

This property is of type **String** and can raise a **DOMException** object on setting.

backgroundColor

This property is of type **String** and can raise a **DOMException** object on setting.

backgroundImage

This property is of type **String** and can raise a **DOMException** object on setting.

backgroundPosition

This property is of type **String** and can raise a **DOMException** object on setting.

backgroundRepeat

This property is of type **String** and can raise a **DOMException** object on setting.

border
This property is of type **String** and can raise a **DOMException** object on setting.
borderCollapse
This property is of type **String** and can raise a **DOMException** object on setting.
borderColor
This property is of type **String** and can raise a **DOMException** object on setting.
borderSpacing
This property is of type **String** and can raise a **DOMException** object on setting.
borderStyle
This property is of type **String** and can raise a **DOMException** object on setting.
borderTop
This property is of type **String** and can raise a **DOMException** object on setting.
borderRight
This property is of type **String** and can raise a **DOMException** object on setting.
borderBottom
This property is of type **String** and can raise a **DOMException** object on setting.
borderLeft
This property is of type **String** and can raise a **DOMException** object on setting.
borderTopColor
This property is of type **String** and can raise a **DOMException** object on setting.
borderRightColor
This property is of type **String** and can raise a **DOMException** object on setting.
borderBottomColor
This property is of type **String** and can raise a **DOMException** object on setting.
borderLeftColor
This property is of type **String** and can raise a **DOMException** object on setting.
borderTopStyle
This property is of type **String** and can raise a **DOMException** object on setting.
borderRightStyle
This property is of type **String** and can raise a **DOMException** object on setting.
borderBottomStyle
This property is of type **String** and can raise a **DOMException** object on setting.
borderLeftStyle
This property is of type **String** and can raise a **DOMException** object on setting.
borderTopWidth
This property is of type **String** and can raise a **DOMException** object on setting.
borderRightWidth
This property is of type **String** and can raise a **DOMException** object on setting.
borderBottomWidth
This property is of type **String** and can raise a **DOMException** object on setting.
borderLeftWidth
This property is of type **String** and can raise a **DOMException** object on setting.
borderWidth
This property is of type **String** and can raise a **DOMException** object on setting.
bottom
This property is of type **String** and can raise a **DOMException** object on setting.

captionSide
This property is of type **String** and can raise a **DOMException** object on setting.
clear
This property is of type **String** and can raise a **DOMException** object on setting.
clip
This property is of type **String** and can raise a **DOMException** object on setting.
color
This property is of type **String** and can raise a **DOMException** object on setting.
content
This property is of type **String** and can raise a **DOMException** object on setting.
counterIncrement
This property is of type **String** and can raise a **DOMException** object on setting.
counterReset
This property is of type **String** and can raise a **DOMException** object on setting.
cue
This property is of type **String** and can raise a **DOMException** object on setting.
cueAfter
This property is of type **String** and can raise a **DOMException** object on setting.
cueBefore
This property is of type **String** and can raise a **DOMException** object on setting.
cursor
This property is of type **String** and can raise a **DOMException** object on setting.
direction
This property is of type **String** and can raise a **DOMException** object on setting.
display
This property is of type **String** and can raise a **DOMException** object on setting.
elevation
This property is of type **String** and can raise a **DOMException** object on setting.
emptyCells
This property is of type **String** and can raise a **DOMException** object on setting.
cssFloat
This property is of type **String** and can raise a **DOMException** object on setting.
font
This property is of type **String** and can raise a **DOMException** object on setting.
fontFamily
This property is of type **String** and can raise a **DOMException** object on setting.
fontSize
This property is of type **String** and can raise a **DOMException** object on setting.
fontSizeAdjust
This property is of type **String** and can raise a **DOMException** object on setting.
fontStretch
This property is of type **String** and can raise a **DOMException** object on setting.
fontStyle
This property is of type **String** and can raise a **DOMException** object on setting.
fontVariant
This property is of type **String** and can raise a **DOMException** object on setting.

fontWeight
This property is of type **String** and can raise a **DOMException** object on setting.
height
This property is of type **String** and can raise a **DOMException** object on setting.
left
This property is of type **String** and can raise a **DOMException** object on setting.
letterSpacing
This property is of type **String** and can raise a **DOMException** object on setting.
lineHeight
This property is of type **String** and can raise a **DOMException** object on setting.
listStyle
This property is of type **String** and can raise a **DOMException** object on setting.
listStyleImage
This property is of type **String** and can raise a **DOMException** object on setting.
listStylePosition
This property is of type **String** and can raise a **DOMException** object on setting.
listStyleType
This property is of type **String** and can raise a **DOMException** object on setting.
margin
This property is of type **String** and can raise a **DOMException** object on setting.
marginTop
This property is of type **String** and can raise a **DOMException** object on setting.
marginRight
This property is of type **String** and can raise a **DOMException** object on setting.
marginBottom
This property is of type **String** and can raise a **DOMException** object on setting.
marginLeft
This property is of type **String** and can raise a **DOMException** object on setting.
markerOffset
This property is of type **String** and can raise a **DOMException** object on setting.
marks
This property is of type **String** and can raise a **DOMException** object on setting.
maxHeight
This property is of type **String** and can raise a **DOMException** object on setting.
maxWidth
This property is of type **String** and can raise a **DOMException** object on setting.
minHeight
This property is of type **String** and can raise a **DOMException** object on setting.
minWidth
This property is of type **String** and can raise a **DOMException** object on setting.
orphans
This property is of type **String** and can raise a **DOMException** object on setting.
outline
This property is of type **String** and can raise a **DOMException** object on setting.
outlineColor
This property is of type **String** and can raise a **DOMException** object on setting.

outlineStyle
This property is of type **String** and can raise a **DOMException** object on setting.
outlineWidth
This property is of type **String** and can raise a **DOMException** object on setting.
overflow
This property is of type **String** and can raise a **DOMException** object on setting.
padding
This property is of type **String** and can raise a **DOMException** object on setting.
paddingTop
This property is of type **String** and can raise a **DOMException** object on setting.
paddingRight
This property is of type **String** and can raise a **DOMException** object on setting.
paddingBottom
This property is of type **String** and can raise a **DOMException** object on setting.
paddingLeft
This property is of type **String** and can raise a **DOMException** object on setting.
page
This property is of type **String** and can raise a **DOMException** object on setting.
pageBreakAfter
This property is of type **String** and can raise a **DOMException** object on setting.
pageBreakBefore
This property is of type **String** and can raise a **DOMException** object on setting.
pageBreakInside
This property is of type **String** and can raise a **DOMException** object on setting.
pause
This property is of type **String** and can raise a **DOMException** object on setting.
pauseAfter
This property is of type **String** and can raise a **DOMException** object on setting.
pauseBefore
This property is of type **String** and can raise a **DOMException** object on setting.
pitch
This property is of type **String** and can raise a **DOMException** object on setting.
pitchRange
This property is of type **String** and can raise a **DOMException** object on setting.
playDuring
This property is of type **String** and can raise a **DOMException** object on setting.
position
This property is of type **String** and can raise a **DOMException** object on setting.
quotes
This property is of type **String** and can raise a **DOMException** object on setting.
richness
This property is of type **String** and can raise a **DOMException** object on setting.
right
This property is of type **String** and can raise a **DOMException** object on setting.
size
This property is of type **String** and can raise a **DOMException** object on setting.

speak
This property is of type **String** and can raise a **DOMException** object on setting.
speakHeader
This property is of type **String** and can raise a **DOMException** object on setting.
speakNumeral
This property is of type **String** and can raise a **DOMException** object on setting.
speakPunctuation
This property is of type **String** and can raise a **DOMException** object on setting.
speechRate
This property is of type **String** and can raise a **DOMException** object on setting.
stress
This property is of type **String** and can raise a **DOMException** object on setting.
tableLayout
This property is of type **String** and can raise a **DOMException** object on setting.
textAlign
This property is of type **String** and can raise a **DOMException** object on setting.
textDecoration
This property is of type **String** and can raise a **DOMException** object on setting.
textIndent
This property is of type **String** and can raise a **DOMException** object on setting.
textShadow
This property is of type **String** and can raise a **DOMException** object on setting.
textTransform
This property is of type **String** and can raise a **DOMException** object on setting.
top
This property is of type **String** and can raise a **DOMException** object on setting.
unicodeBidi
This property is of type **String** and can raise a **DOMException** object on setting.
verticalAlign
This property is of type **String** and can raise a **DOMException** object on setting.
visibility
This property is of type **String** and can raise a **DOMException** object on setting.
voiceFamily
This property is of type **String** and can raise a **DOMException** object on setting.
volume
This property is of type **String** and can raise a **DOMException** object on setting.
whiteSpace
This property is of type **String** and can raise a **DOMException** object on setting.
widows
This property is of type **String** and can raise a **DOMException** object on setting.
width
This property is of type **String** and can raise a **DOMException** object on setting.
wordSpacing
This property is of type **String** and can raise a **DOMException** object on setting.
zIndex
This property is of type **String** and can raise a **DOMException** object on setting.

Appendix D: Acknowledgements

Many people contributed to this specification, including members of the DOM Working Group and the DOM Interest Group. We especially thank the following:

Lauren Wood (SoftQuad Software Inc., *chair*), Andrew Watson (Object Management Group), Andy Heninger (IBM), Arnaud Le Hors (W3C and IBM), Ben Chang (Oracle), Bill Smith (Sun), Bill Shea (Merrill Lynch), Bob Sutor (IBM), Chris Lovett (Microsoft), Chris Wilson (Microsoft), David Brownell (Sun), David Singer (IBM), Don Park (invited), Eric Vasilik (Microsoft), Gavin Nicol (INSO), Ian Jacobs (W3C), James Clark (invited), James Davidson (Sun), Jared Sorensen (Novell), Joe Kesselman (IBM), Joe Lapp (webMethods), Joe Marini (Macromedia), Johnny Stenback (Netscape), Jonathan Marsh (Microsoft), Jonathan Robie (Texcel Research and Software AG), Kim Adamson-Sharpe (SoftQuad Software Inc.), Laurence Cable (Sun), Mark Davis (IBM), Mark Scardina (Oracle), Martin Dürst (W3C), Mick Goulish (Software AG), Mike Champion (Arbortext and Software AG), Miles Sabin (Cromwell Media), Patti Lutsky (Arbortext), Paul Grosso (Arbortext), Peter Sharpe (SoftQuad Software Inc.), Phil Karlton (Netscape), Philippe Le Hégaret (W3C, *W3C team contact*), Ramesh Lekshmynarayanan (Merrill Lynch), Ray Whitmer (iMall, Excite@Home and Netscape), Rich Rollman (Microsoft), Rick Gessner (Netscape), Scott Isaacs (Microsoft), Sharon Adler (INSO), Steve Byrne (JavaSoft), Tim Bray (invited), Tom Pixley (Netscape), Vidur Apparao (Netscape), Vinod Anupam (Lucent).

Thanks to all those who have helped to improve this specification by sending suggestions and corrections.

D.1: Production Systems

This specification was written in XML. The HTML, OMG IDL, Java and ECMA Script bindings were all produced automatically.

Thanks to Joe English, author of cost, which was used as the basis for producing DOM Level 1. Thanks also to Gavin Nicol, who wrote the scripts which run on top of cost. Arnaud Le Hors and Philippe Le Hégaret maintained the scripts.

For DOM Level 2, we used Xerces as the basis DOM implementation and wish to thank the authors. Philippe Le Hégaret and Arnaud Le Hors wrote the Java programs which are the DOM application.

Thanks also to Jan Kärrman, author of html2ps, which we use in creating the PostScript version of the specification.

References

For the latest version of any W3C specification please consult the list of W3C Technical Reports available at http://www.w3.org/TR.

E.1: Normative references

DOM Level 2 Core
W3C (World Wide Web Consortium) Document Object Model Level 2 Core Specification, November 2000. Available at http://www.w3.org/TR/2000/REC-DOM-Level-2-Core-20001113

CSS2
W3C (World Wide Web Consortium) Cascading Style Sheets, level 2 Specification, May 1998. Available at http://www.w3.org/TR/1998/REC-CSS2-19980512

ECMAScript
ECMA (European Computer Manufacturers Association) ECMAScript Language Specification. Available at http://www.ecma.ch/ecma1/STAND/ECMA-262.HTM

HTML4.0
W3C (World Wide Web Consortium) HTML 4.0 Specification, April 1998. Available at http://www.w3.org/TR/1998/REC-html40-19980424

Java
Sun Microsystems Inc. The Java Language Specification, James Gosling, Bill Joy, and Guy Steele, September 1996. Available at http://java.sun.com/docs/books/jls

OMGIDL
OMG (Object Management Group) IDL (Interface Definition Language) defined in The Common Object Request Broker: Architecture and Specification, version 2.3.1, October 1999. Available from http://www.omg.org/

DOM Level 2 Views
W3C (World Wide Web Consortium) Document Object Model Level 2 Views Specification, November 2000. Available at http://www.w3.org/TR/2000/REC-DOM-Level-2-Views-20001113

XML-StyleSheet
W3C (World Wide Web Consortium) Associating Style Sheets with XML documents Version 1.0, June 1999. Available at http://www.w3.org/1999/06/REC-xml-stylesheet-19990629.

E.2: Informative references

DOM Level 2 HTML
W3C (World Wide Web Consortium) Document Object Model Level 2 HTML Specification. Available at http://www.w3.org/TR/DOM-Level-2-HTML

Index

appendMedium
azimuth

background
backgroundAttachment
backgroundColor
backgroundImage
backgroundPosition
backgroundRepeat
blue
border
borderBottom
borderBottomColor
borderBottomStyle
borderBottomWidth
borderCollapse
borderColor
borderLeft
borderLeftColor
borderLeftStyle
borderLeftWidth
borderRight
borderRightColor
borderRightStyle
borderRightWidth
borderSpacing
borderStyle
borderTop
borderTopColor
borderTopStyle
borderTopWidth
borderWidth
bottom 36, 54

captionSide
CHARSET_RULE
clear
clip
color
content
Counter
counterIncrement
counterReset
createCSSStyleSheet
CSS2 15, 37, 127
CSS2Properties
CSS_ATTR
CSS_CM
CSS_COUNTER
CSS_CUSTOM
CSS_DEG
CSS_DIMENSION
CSS_EMS
CSS_EXS
CSS_GRAD
CSS_HZ
CSS_IDENT
CSS_IN
CSS_INHERIT
CSS_KHZ
CSS_MM
CSS_MS
CSS_NUMBER
CSS_PC
CSS_PERCENTAGE
CSS_PRIMITIVE_VALUE
CSS_PT
CSS_PX
CSS_RAD
CSS_RECT
CSS_RGBCOLOR
CSS_S
CSS_STRING

CSS_UNKNOWN
CSS_URI
CSS_VALUE_LIST
CSSCharsetRule
cssFloat
CSSFontFaceRule
CSSImportRule
CSSMediaRule
CSSPageRule
CSSPrimitiveValue
CSSRule
CSSRuleList
cssRules 16, 20
CSSStyleDeclaration
CSSStyleRule
CSSStyleSheet
cssText 19, 25, 28
CSSUnknownRule
CSSValue
CSSValueList
cssValueType
cue
cueAfter
cueBefore
cursor

deleteMedium
deleteRule 16, 21
direction
disabled
display
DocumentCSS
DocumentStyle
DOM Level 2 Core 9, 15, 40, 127
DOM Level 2 HTML 13, 127
DOM Level 2 Views 15, 127
DOMImplementationCSS

ECMAScript
ElementCSSInlineStyle
elevation
emptyCells
encoding

font
FONT_FACE_RULE
fontFamily
fontSize
fontSizeAdjust
fontStretch
fontStyle
fontVariant
fontWeight

getComputedStyle
getCounterValue
getFloatValue
getOverrideStyle
getPropertyCSSValue
getPropertyPriority
getPropertyValue
getRectValue
getRGBColorValue
getStringValue
green

height
href 10, 23
HTML4.0 13, 127

identifier
IMPORT_RULE
insertRule 17, 21
item 11, 12, 18, 26, 35

Java

left 36, 61
length 11, 11, 18, 25, 35
letterSpacing
lineHeight
LinkStyle
listStyle 37, 62
listStyleImage
listStylePosition
listStyleType

margin
marginBottom
marginLeft
marginRight
marginTop
markerOffset
marks
maxHeight
maxWidth
media 10, 21, 23
MEDIA_RULE
MediaList
mediaText
minHeight
minWidth

OMGIDL
orphans
outline
outlineColor
outlineStyle
outlineWidth
overflow
ownerNode
ownerRule

padding
paddingBottom
paddingLeft
paddingRight
paddingTop
page
PAGE_RULE
pageBreakAfter
pageBreakBefore
pageBreakInside
parentRule 19, 25
parentStyleSheet 10, 19
pause
pauseAfter
pauseBefore
pitch
pitchRange
playDuring
position
primitiveType

quotes

Rect
red
removeProperty
RGBColor
richness
right 36, 71

selectorText 20, 22
separator
setFloatValue
setProperty
setStringValue
sheet
size
speak
speakHeader
speakNumeral
speakPunctuation
speechRate
stress
style 20, 22, 23, 39
STYLE_RULE
StyleSheet 9, 23
StyleSheetList
styleSheets

tableLayout
textAlign
textDecoration
textIndent
textShadow
textTransform
title
top 36, 75
type 10, 19

unicodeBidi
UNKNOWN_RULE

verticalAlign
ViewCSS
visibility
voiceFamily
volume

whiteSpace
widows
width
wordSpacing

XML-StyleSheet 13, 13, 127

zIndex