



XHTML Role Attribute Module

A module to support role classification of elements

W3C Editor's Draft 28 January 2008

This version:

<http://www.w3.org/TR/2007/ED-xhtml-role-20080128>

Latest version:

<http://www.w3.org/TR/xhtml-role>

Previous version:

<http://www.w3.org/TR/2007/WD-xhtml-role-20071004/>

Diff from previous version:

[xhtml-role-diff.html](#)

Editors:

Mark Birbeck, x-port.net Ltd.

Shane McCarron, Applied Testing and Technology, Inc.

Steven Pemberton, CWI/W3C®

T. V. Raman, Google, Inc.

Richard Schwerdtfeger, IBM Corporation

This document is also available in these non-normative formats: PostScript version, PDF version, ZIP archive, and Gzip'd TAR archive.

The English version of this specification is the only normative version. Non-normative translations may also be available.

Copyright © 2006-2008 W3C® (MIT, ERCIM, Keio), All Rights Reserved. W3C liability, trademark and document use rules apply.

Abstract

The XHTML Role Attribute defined in this specification allows the author to annotate XML Languages with machine-extractable semantic information about the purpose of an element. Use cases include accessibility, device adaptation, server-side processing, and complex data description. This attribute can be integrated into any markup language based upon XHTML Modularization [XHTMLMOD [p.19]].

Status of This Document

This section describes the status of this document at the time of its publication. Other documents may supersede this document. A list of current W3C publications and the latest revision of this technical report can be found in the W3C technical reports index at <http://www.w3.org/TR/>.

This document is a Last Call Working Draft. It is based upon comments received against the previous draft, and also upon work done in the definition of [XHTML2 [p.19]]. The Last Call period extends through 26 October 2007.

This document has been produced by the W3C XHTML 2 Working Group as part of the HTML Activity. The goals of the XHTML 2 Working Group are discussed in the XHTML 2 Working Group charter.

This document was produced by a group operating under the 5 February 2004 W3C Patent Policy. W3C maintains a public list of any patent disclosures made in connection with the deliverables of the group; that page also includes instructions for disclosing a patent. An individual who has actual knowledge of a patent which the individual believes contains Essential Claim(s) must disclose the information in accordance with section 6 of the W3C Patent Policy.

Publication as a Working Draft does not imply endorsement by the W3C Membership. This is a draft document and may be updated, replaced or obsoleted by other documents at any time. It is inappropriate to cite this document as other than work in progress.

Please report errors in this specification to www-html-editor@w3.org (archive). It is inappropriate to send discussion email to this address. Public discussion may take place on www-html@w3.org (archive).

Table of Contents

1. Introduction	.5
2. Conformance Requirements	.7
2.1. Document Conformance	.7
2.2. Host Language Conformance	.7
3. The XHTML Role Attribute	.9
3.1. Extending the collection of roles	10
A. DTD Implementation	11
A.1. Qualified Names Module	11
B. Schema Implementation	15
B.1. Attributes Module	15
C. RDF/OWL Taxonomy	17
D. References	19
D.1. Normative References	19
D.2. Other References	19

E. Acknowledgments	21
--------------------	----

1. Introduction

This section is informative.

This document is a module designed to be used to help extend the scope of XHTML-family markup languages into new environments. It has been developed in conjunction with the accessibility community and other groups to make it easier to describe the semantic meaning of XHTML-family document content.

2. Conformance Requirements

This section is *normative*.

The keywords "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC2119 [p.19]].

Note that all examples in this document are informative, and are not meant to be interpreted as normative requirements.

2.1. Document Conformance

XHTML Role Attribute Module is not a stand-alone document type. It is intended to be integrated into other host languages such as XHTML. A conforming XHTML Role Attribute Module document is a document that requires only the facilities described as mandatory in this specification and the facilities described as mandatory in its host language. Such a document must meet all the following criteria:

1. The document **MUST** conform to the constraints expressed in its host language implementation.
2. If the host language is not in the XHTML namespace, and the host language does not incorporate this module into its own namespace, then the document **MUST** contain an XML namespace declaration for the XHTML Role Attribute Module namespace [XMLNAMES [p.19]]. The namespace for XHTML Role Attribute Module is defined to be `http://www.w3.org/1999/xhtml`. An example start tag of a root element might look like:

This example is informative

```
<html xmlns="http://www.w3.org/1999/xhtml" xml:lang="en" >
```

2.2. Host Language Conformance

When the XHTML Role Attribute Module is included in a host language, all of the facilities required in this specification **MUST** be included in the host language. In addition, the attribute defined in this specification **MUST** be included in the content model of the host language.

3. The XHTML Role Attribute

This section is normative.

The Role Attribute Module defines the `role` attribute and some values for that attribute in the default vocabulary space. The `role` attribute takes as its value one or more whitespace separated CURIEs [CURIE [p.19]]. Any non-qualified value MUST be interpreted as being from the XHTML vocabulary at <http://www.w3.org/1999/xhtml/vocab#>, and MUST be taken from the list defined in this section.

The attribute describes the role(s) the current element plays in the context of the document. This can be used, for example, by applications and assistive technologies to determine the purpose of an element. This could allow a user to make informed decisions on which actions may be taken on an element and activate the selected action in a device independent way. It could also be used as a mechanism for annotating portions of a document in a domain specific way (e.g., a legal term taxonomy).

This example is informative

```
<ul role="navigation wai:sitemap">
  <li href="downloads">Downloads</li>
  <li href="docs">Documentation</li>
  <li href="news">News</li>
</ul>
```

Authors may use the following standard roles, listed here with their conventional interpretations. They are intended to define regions of the document to help orient the user.

banner

A banner is usually defined as the advertisement at the top of a web page. The banner content typically contains the site or company logo and other key advertisements for the site.

contentinfo

This is information about the content on the page. For example, footnotes, copyrights, links to privacy statements, etc. would belong here.

definition

The contents of the associated element represent a definition (e.g., of a term or concept). If there is a `dfn` element within the contents (as defined in [XHTMLMOD [p.19]]), then that represents the term being defined.

main

This defines the main content of a document.

navigation

This is a collection of links suitable for use when navigating the document or related documents.

note

The content is parenthetical or ancillary to the main content of the resource.

search

This is the search section of a web document. This is typically a form used to submit search requests about the site or a more general Internet wide search service.

secondary

This is any unique section of the document. In the case of a portal, this may include but not be limited to: show times; current weather; or stocks to watch.

seealso

Indicates that the element contains content that is related to the main content of the page.

3.1. Extending the collection of roles

It is possible to define additional role values. Such values **MUST** be defined in their own vocabulary. Note that current best practice is that the URI associated with that vocabulary resolve to a resource that allows for the discovery of the definition of the roles in the vocabulary. Example definitions include the RDF/OWL Taxonomy for the XHTML role attribute values in Appendix C [p.17] , and the Web Accessibility Initiative's work on an RDF Taxonomy [ARIA-ROLE [p.19]].

A. DTD Implementation

This appendix is *normative*.

The DTD implementation of XHTML Role Attribute Module conforms to the requirements defined in [XHTMLMOD [p.19]]. Consequently, it provides a Qualified Names declaration module.

A.1. Qualified Names Module

Note that this module defines the parameter entity `%xhtml-role-attrs.qname;`. This entity is intended to be used in the attribute lists of elements in any host language that permits the use of the role attribute on elements in its own namespace. In this case the Host Language driver should set a parameter entity `%XHTML-ROLE.prefixed;` to `INCLUDE` and a parameter entity `%XHTML-ROLE.prefix;` to a value that is the prefix for the XHTML Role Attribute Module attributes.

```
<!-- ..... -->
<!-- XHTML Role QName Module ..... -->
<!-- file: xhtml-role-qname-1.mod

This is XHTML Role - the Role Attribute Module for XHTML.

Copyright 2006 W3C (MIT, ERCIM, Keio), All Rights Reserved.

This DTD module is identified by the PUBLIC and SYSTEM identifiers:

PUBLIC "-//W3C//ENTITIES XHTML Role Attribute Qnames 1.0//EN"
SYSTEM "http://www.w3.org/MarkUp/DTD/xhtml-role-qname-1.mod"

Revisions:
(none)
..... -->

<!-- XHTML Role Attribute QName (Qualified Name) Module

This module is contained in two parts, labeled Section 'A' and 'B':

Section A declares parameter entities to support namespace-
qualified names, namespace declarations, and name prefixing
for XHTML Role and extensions.

Section B declares parameter entities used to provide
namespace-qualified names for the XHTML role attribute:

    %role.qname;    the xmlns-qualified name for @role
    ...

XHTML Role extensions would create a module similar to this one.
-->

<!-- Section A: XHTML Role Attribute XML Namespace Framework ::::::::::::::: -->
<!-- 1. Declare a %XHTML-ROLE.prefixed; conditional section keyword, used
```

```

        to activate namespace prefixing. The default value should
        inherit '%NS.prefixed;' from the DTD driver, so that unless
        overridden, the default behavior follows the overall DTD
        prefixing scheme.
-->
<!ENTITY % NS.prefixed "IGNORE" >
<!ENTITY % XHTML-ROLE.prefixed "%NS.prefixed;" >

<!-- 2. Declare a parameter entity (eg., %XHTML-ROLE.xmlns;) containing
        the URI reference used to identify the XHTML Role Attribute namespace
-->
<!ENTITY % XHTML-ROLE.xmlns "http://www.w3.org/1999/xhtml" >

<!-- 3. Declare parameter entities (eg., %XML.prefix;) containing
        the default namespace prefix string(s) to use when prefixing
        is enabled. This may be overridden in the DTD driver or the
        internal subset of an document instance. If no default prefix
        is desired, this may be declared as an empty string.

        NOTE: As specified in [XMLNAMES], the namespace prefix serves
        as a proxy for the URI reference, and is not in itself significant.
-->
<!ENTITY % XHTML-ROLE.prefix "" >

<!-- 4. Declare parameter entities (eg., %XHTML-ROLE.pfx;) containing the
        colonized prefix(es) (eg., '%XHTML-ROLE.prefix;:') used when
        prefixing is active, an empty string when it is not.
-->
<![%XHTML-ROLE.prefixed;[
<!ENTITY % XHTML-ROLE.pfx "%XHTML-ROLE.prefix;:" >
]]>
<!ENTITY % XHTML-ROLE.pfx "" >

<!-- declare qualified name extensions here ..... -->
<!ENTITY % xhtml-role-qname-extra.mod "" >
%xhtml-role-qname-extra.mod;

<!-- 5. The parameter entity %XHTML-ROLE.xmlns.extra.attrib; may be
        redeclared to contain any non-XHTML Role Attribute namespace
        declaration attributes for namespaces embedded in XML. The default
        is an empty string. XLink should be included here if used
        in the DTD.
-->
<!ENTITY % XHTML-ROLE.xmlns.extra.attrib "" >

<!-- Section B: XML Qualified Names :::::::::::::::::::::::::::::: -->

<!-- 6. This section declares parameter entities used to provide
        namespace-qualified names for the XHTML role attribute.
-->

<!ENTITY % xhtml-role.role.qname "%XHTML-ROLE.pfx;role" >

<!-- The following defines a PE for use in the attribute sets of elements in
        other namespaces that want to incorporate the XHTML role attribute. Note

```

```
        that in this case the XHTML-ROLE.pfx should be defined. -->

<!ENTITY % xhtml-role.attrs.qname
    "%XHTML-ROLE.pfx;role          CDATA          #IMPLIED"
>

<!-- end of xhtml-role-qname-1.mod -->
```


B. Schema Implementation

This appendix is *normative*.

The schema implementation of XHTML Role Attribute Module conforms to the requirements defined in [XHTMLSCHEMAMOD [p.??]]. It is divided into an attributes module and an element module for the XHTML Role Attribute Module module defined in this Proposed Recommendation.

B.1. Attributes Module

```
<?xml version="1.0" encoding="UTF-8"?>
<xs:schema
  xmlns:xs="http://www.w3.org/2001/XMLSchema"
  elementFormDefault="qualified"
  xmlns:xhtml="http://www.w3.org/1999/xhtml/datatypes/"
>
  <xs:import namespace="http://www.w3.org/1999/xhtml/datatypes/"
    schemaLocation="xhtml-datatypes-1.xsd" />

  <xs:annotation>
    <xs:documentation>
      This is the XML Schema attribute module for XHTML Role
      $Id: xhtml-role-attr-1.xsd,v 1.1 2008/01/28 18:01:58 ahby Exp $
    </xs:documentation>
    <xs:documentation source="xhtml-copyright-1.xsd"/>
    <xs:documentation source="http://www.w3.org/TR/xhtml-role#A_role"/>
  </xs:annotation>
  <xs:attribute name="role" type="xhtml:CURIEs"/>
</xs:schema>
```


C. RDF/OWL Taxonomy

This section is informative

This example is informative

```
<?xml version="1.0"?>
<!DOCTYPE rdf:RDF [
  <!ENTITY xsd "http://www.w3.org/2001/XMLSchema#">
  <!ENTITY dc "http://dublincore.org/2003/03/24/dces#">
  <!ENTITY owl "http://www.w3.org/2002/07/owl#">
  <!ENTITY rdfs "http://www.w3.org/2000/01/rdf-schema#">
  <!ENTITY rdf "http://www.w3.org/1999/02/22-rdf-syntax-ns#">
  <!ENTITY states "http://www.w3.org/2005/07/aaa#">
  <!ENTITY wairole "http://www.w3.org/2005/01/wai-rdf/GUIRoleTaxonomy#">
]>
<rdf:RDF xml:base="http://www.w3.org/1999/xhtml"
  xmlns:dc="http://purl.org/dc/elements/1.1/#"
  xmlns:owl="http://www.w3.org/2002/07/owl#"
  xmlns:rdf="http://www.w3.org/1999/02/22-rdf-syntax-ns#"
  xmlns:rdfs="http://www.w3.org/2000/01/rdf-schema#"
  xmlns:states="http://www.w3.org/2005/07/aaa#"
  xmlns:wairole="http://www.w3.org/2005/01/wai-rdf/GUIRoleTaxonomy#" >
  <owl:Class rdf:ID="banner">
    <rdfs:subClassOf rdf:resource="wairole:region"/>
    <wairole:scope rdf:resource="wairole:document"/>
    <dc:description xml:lang="en">
      A banner is usually defined as the advertisement at the top of
      a web page. The banner content typically contains the site or
      company logo and other key advertisements for the site.
    </dc:description>
  </owl:Class>
  <owl:Class rdf:ID="contentinfo">
    <rdfs:subClassOf rdf:resource="wairole:region"/>
    <wairole:scope rdf:resource="wairole:document"/>
    <dc:description xml:lang="en">
      This is information about the content on the page.
      For example, footnotes, copyrights, links to privacy
      statements, etc. would belong here.
    </dc:description>
  </owl:Class>
  <owl:Class rdf:ID="definition">
    <rdfs:subClassOf rdf:resource="wairole:section"/>
    <wairole:scope rdf:resource="wairole:document"/>
    <dc:description xml:lang="en">
      The contents of the associated element represent a
      definition (e.g., of a term or concept). If there is a
      dfn element within the contents (as defined in [XHTMLMOD]),
      then that represents the term being defined.
    </dc:description>
  </owl:Class>
  <owl:Class rdf:ID="main">
    <rdfs:subClassOf rdf:resource="wairole:region"/>
    <wairole:scope rdf:resource="wairole:document"/>
    <dc:description xml:lang="en">
```

```

        This defines the main content of a document.
    </dc:description>
</owl:Class>
<owl:Class rdf:ID="navigation">
    <rdfs:subClassOf rdf:resource="wairole:region"/>
    <wairole:scope rdf:resource="wairole:document"/>
    <wairole:relatedConcept rdf:resource="wairole:menu"/>
    <dc:description xml:lang="en">
        This is the navigation bar on a web document. This is
        typically a list of links to other pages on the site or other
        areas of the same document.
    </dc:description>
</owl:Class>
<owl:Class rdf:ID="note">
    <rdfs:subClassOf rdf:resource="wairole:section"/>
    <wairole:scope rdf:resource="wairole:document"/>
    <dc:description xml:lang="en">
        The content is parenthetic or ancillary to the main content
        of the resource.
    </dc:description>
</owl:Class>
<owl:Class rdf:ID="search">
    <rdfs:subClassOf rdf:resource="wairole:region"/>
    <wairole:scope rdf:resource="wairole:document"/>
    <dc:description xml:lang="en">
        This is the search section of a web document. This is
        typically a form used to submit search requests about
        the site or a more general Internet wide search service.
    </dc:description>
</owl:Class>
<owl:Class rdf:ID="secondary">
    <rdfs:subClassOf rdf:resource="wairole:region"/>
    <dc:description xml:lang="en">
        This is any unique section of the document. In the case
        of a portal, this may include but not be limited to: show
        times; current weather; or stocks to watch.
    </dc:description>
</owl:Class>
<owl:Class rdf:ID="seealso">
    <rdfs:subClassOf rdf:resource="wairole:section"/>
    <dc:description xml:lang="en">
        Indicates that the element contains content that is related
        to the main content of the page.
    </dc:description>
    <wairole:relatedConcept rdf:resource="#main"/>
</owl:Class>
</rdf:RDF>

```

D. References

This appendix is *normative*.

D.1. Normative References

[CURIE]

"*CURIE Syntax 1.0*", W3C Working Draft, M. Birbeck, S. McCarron, *ed.*, 26 November 2007.
Available at: <http://www.w3.org/TR/2007/WD-curie-20071126/>
The latest version is available at: <http://www.w3.org/TR/curie>

[RFC2119]

"*Key words for use in RFCs to indicate requirement levels*", RFC 2119, S. Bradner, March 1997.
Available at: <http://www.rfc-editor.org/rfc/rfc2119.txt>

[XHTMLMOD]

"*Modularization of XHTML™ 1.1*", W3C Proposed Recommendation, D. Austin *et al.*, *eds.*, 13 February 2006.
Available at: <http://www.w3.org/TR/2006/PR-xhtml-modularization-20060213>
The latest version is available at: <http://www.w3.org/TR/xhtml-modularization>

[XMLNAMES]

"*Namespaces in XML*", W3C Recommendation, T. Bray *et al.*, *eds.*, 14 January 1999.
Available at: <http://www.w3.org/TR/1999/REC-xml-names-19990114>
The latest version is available at: <http://www.w3.org/TR/REC-xml-names>

D.2. Other References

[ARIA-ROLE]

"*Roles for Accessible Rich Internet Applications*". L. Seeman, R. Schwerdtfeger, 1 June 2007.
The latest version is available at: <http://www.w3.org/TR/aria-role>

[XHTML]

"*XHTML™ 1.0: The Extensible HyperText Markup Language (Second Edition)*". S. Pemberton *et al.*, 26 January 2000, revised 1 August 2002.
Available at: <http://www.w3.org/TR/2002/REC-xhtml1-20020801>
The latest version is available at: <http://www.w3.org/TR/xhtml1>

[XHTML2]

"*XHTML™ 2.0*". J. Axelsson *et al.*, 27 May 2005.
Available at: <http://www.w3.org/TR/2005/WD-xhtml2-20050527>
The latest version is available at: <http://www.w3.org/TR/xhtml2>

E. Acknowledgments

This section is informative.

At the time of publication, the participants in the W3C XHTML 2 Working Group were: