XHTML™ 1.1 - Module-based XHTML - Second Edition

XHTML™ 1.1 - Module-based XHTML - Second Edition

W3C Editor's Draft 13 February 2008

This version:
http://www.w3.org/TR/2007/ED-xhtml11-20080213
Latest stable version:
http://www.w3.org/TR/xhtml11
Previous Editor's Draft:
http://www.w3.org/MarkUp/2008/ED-xhtml11-20080123
Diff from previous Editor's Draft:
xhtml11-diff.html
Previous Recommendation:
http://www.w3.org/TR/2001/REC-xhtml11-20010531
Diff-marked version from previous Recommendation:
xhtml11-rec-diff.html
Version 1.1 Editors:
Shane McCarron, Applied Testing and Technology, Inc.
Masayasu Ishikawa, W3C
Editors:
Murray Altheim, Sun Microsystems
Shane McCarron, Applied Testing and Technology

This document is also available in these non-normative formats: PostScript version, PDF version, ZIP archive, and Gzip'd TAR archive.

Copyright ©2007 W3C® (MIT, ERCIM, Keio), All Rights Reserved. W3C liability, trademark and document use rules apply.

Abstract

This document defines an XHTML document type that is based upon the module framework and modules defined in XHTML Modularization [XHTMLMOD [p.13]]. The purpose of this document type is to serve as the basis for future extended XHTML 'family' document types, and to provide a consistent, forward-looking document type cleanly separated from the deprecated, legacy functionality of HTML 4 [HTML4 [p.13]] that was brought forward into the XHTML 1.0 [XHTML1 [p.13]] document types. This document type is most similar to XHTML 1.0 Strict, built using XHTML Modules. This means that many facilities available in other XHTML Family document types (e.g., XHTML Frames) are not available in this document type. These other facilities are available through modules defined in XHTML Modularization, and document authors are free to

define document types based upon XHTML 1.1 that use these facilities (see [XHTMLMOD [p.13]] for information on creating new document types).

Status of this document

This section describes the status of this document at the time of its publication. Other documents may supersede this document. A list of current W3C publications and the latest revision of this technical report can be found in the W3C technical reports index at http://www.w3.org/TR/.

This document is a Working Draft in anticipation of entering the W3C's Proposed Edited Recommendation process. It reflects clarifications and corrections as a result of many years of use by the community. It also includes an new implementation using XML Schemas. This implementation has gone through the W3C process, including Last Call, and is now integrated here in anticipation of its publication as a W3C Recommendation. It should not be normatively referenced until this document reaches the W3C Recommendation status.

Publication as a Working Draft does not imply endorsement by the W3C Membership. This is a draft document and may be updated, replaced or obsoleted by other documents at any time. It is inappropriate to cite this document as other than work in progress.

This document has been produced by the W3C XHTML 2 Working Group (*members only*) as part of the W3C HTML Activity. The goals of the XHTML 2 Working Group are discussed in the HTML Working Group charter.

This document was produced by a group operating under the 5 February 2004 W3C Patent Policy. W3C maintains a public list of any patent disclosures made in connection with the deliverables of the group; that page also includes instructions for disclosing a patent. An individual who has actual knowledge of a patent which the individual believes contains Essential Claim(s) must disclose the information in accordance with section 6 of the W3C Patent Policy.

Public discussion of HTML takes place on www-html@w3.org (archive). To subscribe send an email to www-html-request@w3.org with the word *subscribe* in the subject line.

Please report errors in this document to www-html-editor@w3.org (archive).

A list of current W3C Recommendations and other technical documents can be found at http://www.w3.org/TR.

Quick Table of Contents

1. Introduction 5
2. Conformance Definition 7
3. The XHTML 1.1 Document Type 9
A. Changes from XHTML 1.0 Strict 11
B. References 13

C. XHTML 1.1 Document Type Definition 15
D. XHTML 1.1 XML Schema Definition 27
E. Acknowledgements 49

Full Table of Contents

1. Introduction 5
2. Conformance Definition 7
2.1. Document Conformance 7
2.1.1. Strictly Conforming Documents 7
2.2. User Agent Conformance 8
3. The XHTML 1.1 Document Type 9
A. Changes from XHTML 1.0 Strict 11
B. References 13
B.1. Normative References 13
B.2. Informative References 13
C. XHTML 1.1 Document Type Definition 15
C.1. SGML Open Catalog Entry for XHTML 1.1 15
C.2. XHTML 1.1 Driver 15
C.3. XHTML 1.1 Customizations 21
D. XHTML 1.1 XML Schema Definition 27
D.1. XHTML 1.1 Schema Driver 27
D.2. XHTML 1.1 Schema Modules 29
D.3. XHTML 1.1 Customizations 35
E. Acknowledgements 49

1. Introduction

This section is *normative*.

With the introduction of the XHTML family of modules and document types, the W3C has helped move the Internet content-development community from the days of malformed, non-standard markup into the well formed, valid world of XML [XML [p.13]]. In XHTML 1.0, this move was moderated by a goal of providing for easy migration of existing, HTML 4 (or earlier) based content to XHTML and XML. With the advent of the XHTML modules defined in XHTML Modularization, the W3C has removed support for deprecated elements and attributes from the XHTML family. These elements and attributes were largely presentation oriented functionality that is better handled via style sheets or client-specific default behavior.

Going forward, XHTML family document types will be based upon this new, more structural functional collection. In this specification, the W3C's HTML Working Group has defined an initial document type based solely upon modules. This document type is designed to be portable to a broad collection of client devices, and applicable to the majority of Internet content. Content developers who base their content upon the functionality expressed in this specification can be confident that it will be consistently portable across XHTML family conforming user agents.

2. Conformance Definition

This section is *normative*.

The keywords "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC2119] [p.13] .

2.1. Document Conformance

This version of XHTML provides a definition of strictly conforming XHTML documents, which are restricted to elements and attributes from the XHTML namespace.

2.1.1. Strictly Conforming Documents

A strictly conforming XHTML 1.1 document is a document that requires only the facilities described as mandatory in this specification. Such a document MUST meet all the following criteria:

1. The document must conform to the constraints expressed in the schemas in Appendix D - XHTML 1.1 Schema [p.27] and Appendix C - XHTML 1.1 Document Type Definition [p.15] .

2. The local part of the root element of the document must be `html`.

3. The start tag of the root element of the document must explicitly contain an `xmlns` declaration for the XHTML namespace [XMLNS [p.??]]. The namespace URI for XHTML is defined to be `http://www.w3.org/1999/xhtml`.

   The start tag may also contain an `xsi:schemaLocation` attribute that associates this namespace with the XML Schema at the URI `http://www.w3.org/MarkUp/SCHEMA/xhtml11.xsd`.

   Sample root element

   ```
   <html xmlns="http://www.w3.org/1999/xhtml" xml:lang="en"
         xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
         xsi:schemaLocation="http://www.w3.org/1999/xhtml
                             http://www.w3.org/MarkUp/SCHEMA/xhtml11.xsd"
   >
   ```

4. There SHOULD be a DOCTYPE declaration in the document prior to the root element. If present, the public identifier included in the DOCTYPE declaration must reference the DTD found in Appendix F using its Public Identifier. The system identifier may be modified appropriately.

```
<!DOCTYPE html PUBLIC "-//W3C//DTD XHTML 1.1//EN"
    "http://www.w3.org/TR/xhtml11/DTD/xhtml11.dtd">
```

5. The start tag SHOULD contain a `version` attribute that declares the version of XHTML in use. The version of this version of XHTML is `-//W3C//DTD XHTML 1.1//EN`.

Example of an XHTML 1.1 document

```
<?xml version="1.0" encoding="UTF-8"?>
<!DOCTYPE html PUBLIC "-//W3C//DTD XHTML 1.1//EN"
    "http://www.w3.org/TR/xhtml11/DTD/xhtml11.dtd">
<html version="-//W3C//DTD XHTML 1.1//EN"
      xmlns="http://www.w3.org/1999/xhtml" xml:lang="en"
      xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
      xsi:schemaLocation="http://www.w3.org/1999/xhtml
                          http://www.w3.org/MarkUp/SCHEMA/xhtml11.xsd"
>
  <head>
    <title>Virtual Library</title>
  </head>
  <body>
    <p>Moved to <a href="http://example.org/">example.org</a>.</p>
  </body>
</html>
```

Note that in this example, the XML declaration is included. An XML declaration like the one above is not required in all XML documents. XHTML document authors should use XML declarations in all their documents. XHTML document authors must use an XML declaration when the character encoding of the document is other than the default UTF-8 or UTF-16 and no encoding is specified by a higher-level protocol.

XHTML 1.1 documents SHOULD be labeled with the Internet Media Type "application/xhtml+xml" as defined in [RFC3236 [p.13]]. For further information on using media types with XHTML, see the informative note [XHTMLMIME [p.14]].

2.2. User Agent Conformance

A conforming user agent MUST meet all user agent conformance requirements defined in [XHTMLMOD [p.13]].

3. The XHTML 1.1 Document Type

This section is *normative*.

The XHTML 1.1 document type is a fully functional document type with rich semantics. It is not, however, as varied in functionality as the XHTML 1.0 Transitional or Frameset document types. These document types defined many presentational components that are better handled through style sheets or other similar mechanisms. Moreover, since the XHTML 1.1 document type is based exclusively upon the facilities defined in the XHTML modules [XHTMLMOD [p.13]], it does not contain any of the deprecated functionality of XHTML 1.0 nor of HTML 4. Despite these exceptions, or perhaps because of them, the XHTML 1.1 document type is a solid basis for future document types that are targeted at varied user agent environments.

The XHTML 1.1 document type is made up of the following XHTML modules. The elements, attributes, and minimal content models associated with these modules are defined in "XHTML Modularization" [XHTMLMOD [p.13]]). The elements are listed here for information purposes, but the definitions in "XHTML Modularization" should be considered definitive. In the on-line version of this document, the module names in the list below link into the definitions of the modules within the current version of "XHTML Modularization".

Structure Module*

```
body, head, html, title
```

Text Module*

```
abbr, acronym, address, blockquote, br, cite, code, dfn, div, em,
h1, h2, h3, h4, h5, h6, kbd, p, pre, q, samp, span, strong, var
```

Hypertext Module*

```
a
```

List Module*

```
dl, dt, dd, ol, ul, li
```

Object Module

```
object, param
```

Presentation Module

```
b, big, hr, i, small, sub, sup, tt
```

Edit Module

```
del, ins
```

Bidirectional Text Module

```
bdo
```

Forms Module

```
button, fieldset, form, input, label, legend, select, optgroup,
option, textarea
```

Table Module

```
caption, col, colgroup, table, tbody, td, tfoot, th, thead, tr
```

Image Module

```
img
```

Client-side Image Map Module
    `area, map`
Server-side Image Map Module
    Attribute `ismap` on `img`
Intrinsic Events Module
    Events attributes
Metainformation Module
    `meta`
Scripting Module
    `noscript, script`
Stylesheet Module
    `style` element
Style Attribute Module *Deprecated*
    `style` attribute
Link Module
    `link`
Base Module
    `base`

XHTML also uses the Ruby Annotation module as defined in [RUBY [p.13]]:

Ruby Annotation Module
    `ruby, rbc, rtc, rb, rt, rp`

Finally, XHTML uses the inputmode attribute as defined in [XHTMLBASIC11 [p.13]]:

XHTML inputmode Attribute Module
    `inputmode` attribute

There are no additional definitions required by this document type. An implementation of this document type as an XML Schema is defined in Appendix D [p.27] , and as an XML DTD is defined in Appendix C [p.15] .

A. Changes from XHTML 1.0 Strict

This appendix is *informative*.

This Appendix describes the differences between XHTML 1.1 and XHTML 1.0 Strict. XHTML 1.1 represents a departure from both HTML 4 and XHTML 1.0. Most significant is the removal of features that were deprecated. In general, the strategy is to define a markup language that is rich in structural functionality, but that relies upon style sheets for presentation.

The differences can be summarized as follows:

1. On every element, the `lang` attribute has been removed in favor of the `xml:lang` attribute (as defined in [XHTMLMOD [p.13]]).
2. On the `a` and `map` elements, the `name` attribute has been removed in favor of the `id` attribute (as defined in [XHTMLMOD [p.13]]).
3. The "`ruby`" collection of elements has been added (as defined in [RUBY [p.13]]).

B. References

This appendix is *normative*.

B.1. Normative References

[HTML4]
HTML 4.01 Specification, W3C Recommendation, Dave Raggett, Arnaud Le Hors, Ian Jacobs, 24 December 1999.
See: http://www.w3.org/TR/1999/REC-html401-19991224

[RUBY]
Ruby Annotation, W3C Recommendation, Marcin Sawicki, et al., 31 May 2001.
See: http://www.w3.org/TR/2001/REC-ruby-20010531

[XHTML1]
XHTML 1.0: The Extensible HyperText Markup Language (Second Edition), W3C Recommendation, Steven Pemberton, et al., 26 January 2000, revised 1 August 2002.
See: http://www.w3.org/TR/2002/REC-xhtml1-20020801

[XHTMLBASIC11]
XHTML Basic 1.1, W3C Candidate Recommendation, Shane McCarron et al., 13 July 2007.
See: http://www.w3.org/TR/2007/CR-xhtml-basic-20070713

[XHTMLMOD]
XHTML Modularization 1.1, W3C Working Draft, Shane McCarron, et al., 5 July 2006
See: http://www.w3.org/TR/2006/WD-xhtml-modularization-20060705

[XML]
Extensible Markup Language (XML) 1.0 (Second Edition), W3C Recommendation, Tim Bray, Jean Paoli, C. M. Sperberg-McQueen, Eve Maler, F. Yergeau, 4 February 2004.
See: http://www.w3.org/TR/2004/REC-xml-20040204

B.2. Informative References

[CATALOG]
Entity Management: OASIS Technical Resolution 9401:1997 (Amendment 2 to TR 9401), Paul Grosso, Chair, Entity Management Subcommittee, SGML Open, 10 September 1997.
See: http://www.oasis-open.org/html/a401.htm

[RFC2119]
"*Key words for use in RFCs to indicate requirement levels*", RFC 2119, S. Bradner, March 1997.
Available at: http://www.ietf.org/rfc/rfc2119.txt

[RFC2854]
"The 'text/html' Media Type", D. Connely, L. Masinter, January 2000.
Available at: http://www.ietf.org/rfc/rfc2854.txt

[RFC3236]
"The 'application/xhtml+xml' Media Type", M. Baker, P. Stark, January 2002.
Available at: http://www.ietf.org/rfc/rfc3236.txt

[XHTMLMIME]
"*XHTML Media Types*", Masayasu Ishikawa, 1 August 2002.
Latest version available at: http://www.w3.org/TR/xhtml-media-types
[XMLNAMES]
"*Namespaces in XML*", W3C Recommendation, Tim Bray, Dave Hollander, Andrew Layman, 14 January 1999.
Available at: http://www.w3.org/TR/1999/REC-xml-names-19990114
[XMLSCHEMA]
"*XML Schema Part 1: Structures Second Edition*", W3C Recommendation, H. S. Thompson *et al.*, *eds.*, 28 October 2004.
Available at: http://www.w3.org/TR/2004/REC-xmlschema-1-20041028/
"*XML Schema Part 2: Datatypes Second Edition*", W3C Recommendation, P. V. Biron, A. Malhotra, *eds.*, 28 October 2004.
Available at: http://www.w3.org/TR/2004/REC-xmlschema-2-20041028/

C. XHTML 1.1 Document Type Definition

This appendix is *normative*.

C.1. SGML Open Catalog Entry for XHTML 1.1

This section contains the SGML Open Catalog-format definition [CATALOG [p.13]] of the public identifiers for XHTML 1.1.

```
-- ..................................................................... --
-- File catalog  ....................................................... --

--  XHTML 1.1 Catalog Data File

    Revision:  @(#)xhtml11.cat 1.9 2001/04/04 SMI

    See "Entity Management", SGML Open Technical Resolution 9401 for detailed
    information on supplying and using catalog data. This document is available
    from OASIS at URL:

        <http://www.oasis-open.org/html/tr9401.html>
--

-- ..................................................................... --
-- SGML declaration associated with XHTML  ............................. --

OVERRIDE YES

SGMLDECL "xml1.dcl"

-- ::::::::::::::::::::::::::::::::::::::::::::::::::::::::::::::::::::: --

-- XHTML 1.1 DTD modular driver file  .................................. --
-- note that this uses the local, flattened version of the DTD. If you want
   your catalog to use the master version of the XHTML Modules, change the
   entry to reference xhtml11.dtd instead of xhtml11-flat.dtd
--

PUBLIC "-//W3C//DTD XHTML 1.1//EN"                          "xhtml11-flat.dtd"

-- XHTML 1.1 framework modules ..................................... --

PUBLIC "-//W3C//ENTITIES XHTML 1.1 Document Model 1.0//EN"        "xhtml11-model-1.mod"

-- End of catalog data  ............................................ --
-- ..................................................................... --
```

C.2. XHTML 1.1 Driver

This section contains the driver for the XHTML 1.1 document type implementation as an XML DTD. It relies upon XHTML module implementations defined in [XHTMLMOD [p.13]] and in [RUBY [p.13]].

```
<!-- ....................................................................... -->
<!-- XHTML 1.1 DTD  ....................................................... -->
<!-- file: xhtml11.dtd
-->

<!-- XHTML 1.1 DTD

     This is XHTML, a reformulation of HTML as a modular XML application.

     The Extensible HyperText Markup Language (XHTML)
     Copyright 1998-2007 World Wide Web Consortium
        (Massachusetts Institute of Technology, European Research Consortium
         for Informatics and Mathematics, Keio University).
         All Rights Reserved.

     Permission to use, copy, modify and distribute the XHTML DTD and its
     accompanying documentation for any purpose and without fee is hereby
     granted in perpetuity, provided that the above copyright notice and
     this paragraph appear in all copies.  The copyright holders make no
     representation about the suitability of the DTD for any purpose.

     It is provided "as is" without expressed or implied warranty.

        Author:     Murray M. Altheim <altheim@eng.sun.com>
        Revision:   $Id: xhtml11.ps,v 1.1 2008/02/13 16:19:41 smccarro Exp $

-->
<!-- This is the driver file for version 1.1 of the XHTML DTD.

     Please use this public identifier to identify it:

         "-//W3C//DTD XHTML 1.1//EN"
-->
<!ENTITY % XHTML.version  "-//W3C//DTD XHTML 1.1//EN" >

<!-- Use this URI to identify the default namespace:

         "http://www.w3.org/1999/xhtml"

     See the Qualified Names module for information
     on the use of namespace prefixes in the DTD.

     Note that XHTML namespace elements are not prefixed by default,
     but the XHTML namespace prefix is defined as "xhtml" so that
     other markup languages can extend this one and use the XHTML
     prefixed global attributes if required.

-->
<!ENTITY % NS.prefixed "IGNORE" >
<!ENTITY % XHTML.prefix "xhtml" >

<!-- Be sure to include prefixed global attributes - we don't need
     them, but languages that extend XHTML 1.1 might.
-->
<!ENTITY % XHTML.global.attrs.prefixed "INCLUDE" >

<!-- Reserved for use with the XLink namespace:
```

```
-->
<!ENTITY % XLINK.xmlns "" >
<!ENTITY % XLINK.xmlns.attrib "" >

<!-- For example, if you are using XHTML 1.1 directly, use the public
     identifier in the DOCTYPE declaration, with the namespace declaration
     on the document element to identify the default namespace:

       <?xml version="1.0"?>
       <!DOCTYPE html PUBLIC "-//W3C//DTD XHTML 1.1//EN"
                             "http://www.w3.org/TR/xhtml11/DTD/xhtml11.dtd">
       <html xmlns="http://www.w3.org/1999/xhtml"
             xml:lang="en">
       ...
       </html>

     Revisions:
     (none)
-->

<!-- reserved for future use with document profiles -->
<!ENTITY % XHTML.profile  "" >

<!-- ensure XHTML Notations are disabled -->
<!ENTITY % xhtml-notations.module "IGNORE" >

<!-- Bidirectional Text features
     This feature-test entity is used to declare elements
     and attributes used for bidirectional text support.
-->
<!ENTITY % XHTML.bidi  "INCLUDE" >

<?doc type="doctype" role="title" { XHTML 1.1 } ?>

<!-- ....................................................................... -->

<!-- Pre-Framework Redeclaration placeholder  ..................... -->
<!-- this serves as a location to insert markup declarations
     into the DTD prior to the framework declarations.
-->
<!ENTITY % xhtml-prefw-redecl.module "IGNORE" >
<![%xhtml-prefw-redecl.module;[
%xhtml-prefw-redecl.mod;
<!-- end of xhtml-prefw-redecl.module -->]]>

<!ENTITY % xhtml-events.module "INCLUDE" >

<!-- Inline Style Module  ..................................... -->
<!ENTITY % xhtml-inlstyle.module "INCLUDE" >
<![%xhtml-inlstyle.module;[
<!ENTITY % xhtml-inlstyle.mod
     PUBLIC "-//W3C//ELEMENTS XHTML Inline Style 1.0//EN"
            "http://www.w3.org/MarkUp/DTD/xhtml-inlstyle-1.mod" >
%xhtml-inlstyle.mod;]]>

<!-- declare Document Model module instantiated in framework
-->
```

```
<!ENTITY % xhtml-model.mod
     PUBLIC "-//W3C//ENTITIES XHTML 1.1 Document Model 1.0//EN"
            "http://www.w3.org/MarkUp/DTD/xhtml11-model-1.mod" >

<!-- Modular Framework Module (required) ..... -->
<!ENTITY % xhtml-framework.module "INCLUDE" >
<![%xhtml-framework.module;[
<!ENTITY % xhtml-framework.mod
     PUBLIC "-//W3C//ENTITIES XHTML Modular Framework 1.0//EN"
            "http://www.w3.org/MarkUp/DTD/xhtml-framework-1.mod" >
%xhtml-framework.mod;]]>

<!-- Post-Framework Redeclaration placeholder  ..... -->
<!-- this serves as a location to insert markup declarations
     into the DTD following the framework declarations.
-->
<!ENTITY % xhtml-postfw-redecl.module "IGNORE" >
<![%xhtml-postfw-redecl.module;[
%xhtml-postfw-redecl.mod;
<!-- end of xhtml-postfw-redecl.module -->]]>

<!-- Text Module (Required)  ..... -->
<!ENTITY % xhtml-text.module "INCLUDE" >
<![%xhtml-text.module;[
<!ENTITY % xhtml-text.mod
     PUBLIC "-//W3C//ELEMENTS XHTML Text 1.0//EN"
            "http://www.w3.org/MarkUp/DTD/xhtml-text-1.mod" >
%xhtml-text.mod;]]>

<!-- Hypertext Module (required) ..... -->
<!ENTITY % xhtml-hypertext.module "INCLUDE" >
<![%xhtml-hypertext.module;[
<!ENTITY % xhtml-hypertext.mod
     PUBLIC "-//W3C//ELEMENTS XHTML Hypertext 1.0//EN"
            "http://www.w3.org/MarkUp/DTD/xhtml-hypertext-1.mod" >
%xhtml-hypertext.mod;]]>

<!-- Lists Module (required)  ..... -->
<!ENTITY % xhtml-list.module "INCLUDE" >
<![%xhtml-list.module;[
<!ENTITY % xhtml-list.mod
     PUBLIC "-//W3C//ELEMENTS XHTML Lists 1.0//EN"
            "http://www.w3.org/MarkUp/DTD/xhtml-list-1.mod" >
%xhtml-list.mod;]]>

<!-- ::::::::::::::::::::::::::::::::::::::::::::::::::::::::::::::::::::: -->

<!-- Edit Module  ..... -->
<!ENTITY % xhtml-edit.module "INCLUDE" >
<![%xhtml-edit.module;[
<!ENTITY % xhtml-edit.mod
     PUBLIC "-//W3C//ELEMENTS XHTML Editing Elements 1.0//EN"
            "http://www.w3.org/MarkUp/DTD/xhtml-edit-1.mod" >
%xhtml-edit.mod;]]>

<!-- BIDI Override Module  ..... -->
<!ENTITY % xhtml-bdo.module "%XHTML.bidi;" >
```

```
<![%xhtml-bdo.module;[
<!ENTITY % xhtml-bdo.mod
     PUBLIC "-//W3C//ELEMENTS XHTML BIDI Override Element 1.0//EN"
            "http://www.w3.org/MarkUp/DTD/xhtml-bdo-1.mod" >
%xhtml-bdo.mod;]]>

<!-- Ruby Module  ............................................ -->
<!ENTITY % Ruby.common.attlists "INCLUDE" >
<!ENTITY % Ruby.common.attrib "%Common.attrib;" >
<!ENTITY % xhtml-ruby.module "INCLUDE" >
<![%xhtml-ruby.module;[
<!ENTITY % xhtml-ruby.mod
     PUBLIC "-//W3C//ELEMENTS XHTML Ruby 1.0//EN"
            "http://www.w3.org/TR/ruby/xhtml-ruby-1.mod" >
%xhtml-ruby.mod;]]>

<!-- Presentation Module  .................................... -->
<!ENTITY % xhtml-pres.module "INCLUDE" >
<![%xhtml-pres.module;[
<!ENTITY % xhtml-pres.mod
     PUBLIC "-//W3C//ELEMENTS XHTML Presentation 1.0//EN"
            "http://www.w3.org/MarkUp/DTD/xhtml-pres-1.mod" >
%xhtml-pres.mod;]]>

<!-- Link Element Module  .................................... -->
<!ENTITY % xhtml-link.module "INCLUDE" >
<![%xhtml-link.module;[
<!ENTITY % xhtml-link.mod
     PUBLIC "-//W3C//ELEMENTS XHTML Link Element 1.0//EN"
            "http://www.w3.org/MarkUp/DTD/xhtml-link-1.mod" >
%xhtml-link.mod;]]>

<!-- Document Metainformation Module  ........................ -->
<!ENTITY % xhtml-meta.module "INCLUDE" >
<![%xhtml-meta.module;[
<!ENTITY % xhtml-meta.mod
     PUBLIC "-//W3C//ELEMENTS XHTML Metainformation 1.0//EN"
            "http://www.w3.org/MarkUp/DTD/xhtml-meta-1.mod" >
%xhtml-meta.mod;]]>

<!-- Base Element Module  .................................... -->
<!ENTITY % xhtml-base.module "INCLUDE" >
<![%xhtml-base.module;[
<!ENTITY % xhtml-base.mod
     PUBLIC "-//W3C//ELEMENTS XHTML Base Element 1.0//EN"
            "http://www.w3.org/MarkUp/DTD/xhtml-base-1.mod" >
%xhtml-base.mod;]]>

<!-- Scripting Module  ....................................... -->
<!ENTITY % xhtml-script.module "INCLUDE" >
<![%xhtml-script.module;[
<!ENTITY % xhtml-script.mod
     PUBLIC "-//W3C//ELEMENTS XHTML Scripting 1.0//EN"
            "http://www.w3.org/MarkUp/DTD/xhtml-script-1.mod" >
%xhtml-script.mod;]]>

<!-- Style Sheets Module  .................................... -->
```

```
<!ENTITY % xhtml-style.module "INCLUDE" >
<![%xhtml-style.module;[
<!ENTITY % xhtml-style.mod
     PUBLIC "-//W3C//ELEMENTS XHTML Style Sheets 1.0//EN"
            "http://www.w3.org/MarkUp/DTD/xhtml-style-1.mod" >
%xhtml-style.mod;]]>

<!-- Image Module  ............................................ -->
<!ENTITY % xhtml-image.module "INCLUDE" >
<![%xhtml-image.module;[
<!ENTITY % xhtml-image.mod
     PUBLIC "-//W3C//ELEMENTS XHTML Images 1.0//EN"
            "http://www.w3.org/MarkUp/DTD/xhtml-image-1.mod" >
%xhtml-image.mod;]]>

<!-- Client-side Image Map Module  ............................. -->
<!ENTITY % xhtml-csismap.module "INCLUDE" >
<![%xhtml-csismap.module;[
<!ENTITY % xhtml-csismap.mod
     PUBLIC "-//W3C//ELEMENTS XHTML Client-side Image Maps 1.0//EN"
            "http://www.w3.org/MarkUp/DTD/xhtml-csismap-1.mod" >
%xhtml-csismap.mod;]]>

<!-- Server-side Image Map Module  ............................. -->
<!ENTITY % xhtml-ssismap.module "INCLUDE" >
<![%xhtml-ssismap.module;[
<!ENTITY % xhtml-ssismap.mod
     PUBLIC "-//W3C//ELEMENTS XHTML Server-side Image Maps 1.0//EN"
            "http://www.w3.org/MarkUp/DTD/xhtml-ssismap-1.mod" >
%xhtml-ssismap.mod;]]>

<!-- Param Element Module  ..................................... -->
<!ENTITY % xhtml-param.module "INCLUDE" >
<![%xhtml-param.module;[
<!ENTITY % xhtml-param.mod
     PUBLIC "-//W3C//ELEMENTS XHTML Param Element 1.0//EN"
            "http://www.w3.org/MarkUp/DTD/xhtml-param-1.mod" >
%xhtml-param.mod;]]>

<!-- Embedded Object Module  ................................... -->
<!ENTITY % xhtml-object.module "INCLUDE" >
<![%xhtml-object.module;[
<!ENTITY % xhtml-object.mod
     PUBLIC "-//W3C//ELEMENTS XHTML Embedded Object 1.0//EN"
            "http://www.w3.org/MarkUp/DTD/xhtml-object-1.mod" >
%xhtml-object.mod;]]>

<!-- Inputmode Attribute Module  ............................... -->
<!ENTITY % xhtml-inputmode.module "INCLUDE" >
<![%xhtml-inputmode.module;[
<!ENTITY % xhtml-inputmode.mod
     PUBLIC "-//W3C//ELEMENTS XHTML Inputmode 1.0//EN"
            "http://www.w3.org/MarkUp/DTD/xhtml-inputmode-1.mod" >
%xhtml-inputmode.mod;]]>

<!-- Tables Module ............................................ -->
<!ENTITY % xhtml-table.module "INCLUDE" >
```

```
<![%xhtml-table.module;[
<!ENTITY % xhtml-table.mod
     PUBLIC "-//W3C//ELEMENTS XHTML Tables 1.0//EN"
            "http://www.w3.org/MarkUp/DTD/xhtml-table-1.mod" >
%xhtml-table.mod;]]>

<!-- Forms Module  ....................................... -->
<!ENTITY % xhtml-form.module "INCLUDE" >
<![%xhtml-form.module;[
<!ENTITY % xhtml-form.mod
     PUBLIC "-//W3C//ELEMENTS XHTML Forms 1.0//EN"
            "http://www.w3.org/MarkUp/DTD/xhtml-form-1.mod" >
%xhtml-form.mod;]]>

<!-- Target Attribute Module  ............................ -->
<!ENTITY % xhtml-target.module "INCLUDE" >
<![%xhtml-target.module;[
<!ENTITY % xhtml-target.mod
     PUBLIC "-//W3C//ELEMENTS XHTML Target 1.0//EN"
            "http://www.w3.org/MarkUp/DTD/xhtml-target-1.mod" >
%xhtml-target.mod;]]>

<!-- Legacy Markup ....................................... -->
<!ENTITY % xhtml-legacy.module "IGNORE" >
<![%xhtml-legacy.module;[
<!ENTITY % xhtml-legacy.mod
     PUBLIC "-//W3C//ELEMENTS XHTML Legacy Markup 1.0//EN"
            "http://www.w3.org/MarkUp/DTD/xhtml-legacy-1.mod" >
%xhtml-legacy.mod;]]>

<!-- Document Structure Module (required)  ............... -->
<!ENTITY % xhtml-struct.module "INCLUDE" >
<![%xhtml-struct.module;[
<!ENTITY % xhtml-struct.mod
     PUBLIC "-//W3C//ELEMENTS XHTML Document Structure 1.0//EN"
            "http://www.w3.org/MarkUp/DTD/xhtml-struct-1.mod" >
%xhtml-struct.mod;]]>

<!-- end of XHTML 1.1 DTD  ............................... -->
<!-- ..................................................... -->
```

C.3. XHTML 1.1 Customizations

An XHTML Family Document Type (such as XHTML 1.1) must define the content model that it uses. This is done through a separate content model module that is instantiated by the XHTML Modular Framework. The content model module and the XHTML 1.1 Driver (above) work together to customize the module implementations to the document type's specific requirements. The content model module for XHTML 1.1 is defined below:

```
<!-- ..................................................... -->
<!-- XHTML 1.1 Document Model Module  ..................... -->
<!-- file: xhtml11-model-1.mod

     This is XHTML 1.1, a reformulation of HTML as a modular XML application.
     Copyright 1998-2007 W3C (MIT, ERCIM, Keio), All Rights Reserved.
```

```
      Revision: $Id: xhtml11.ps,v 1.1 2008/02/13 16:19:41 smccarro Exp $ SMI

      This DTD module is identified by the PUBLIC and SYSTEM identifiers:

        PUBLIC "-//W3C//ENTITIES XHTML 1.1 Document Model 1.0//EN"
        SYSTEM "http://www.w3.org/MarkUp/DTD/xhtml11-model-1.mod"

      Revisions:
      (none)
      ..................................................................... -->

<!-- XHTML 1.1 Document Model

      This module describes the groupings of elements that make up
      common content models for XHTML elements.

      XHTML has three basic content models:

          %Inline.mix;  character-level elements
          %Block.mix;   block-like elements, eg., paragraphs and lists
          %Flow.mix;    any block or inline elements

      Any parameter entities declared in this module may be used
      to create element content models, but the above three are
      considered 'global' (insofar as that term applies here).

      The reserved word '#PCDATA' (indicating a text string) is now
      included explicitly with each element declaration that is
      declared as mixed content, as XML requires that this token
      occur first in a content model specification.
-->
<!-- Extending the Model

      While in some cases this module may need to be rewritten to
      accommodate changes to the document model, minor extensions
      may be accomplished by redeclaring any of the three *.extra;
      parameter entities to contain extension element types as follows:

          %Misc.extra;    whose parent may be any block or
                          inline element.

          %Inline.extra;  whose parent may be any inline element.

          %Block.extra;   whose parent may be any block element.

      If used, these parameter entities must be an OR-separated
      list beginning with an OR separator ("|"), eg., "| a | b | c"

      All block and inline *.class parameter entities not part
      of the *struct.class classes begin with "| " to allow for
      exclusion from mixes.
-->

<!-- ..............  Optional Elements in head  .................. -->

<!ENTITY % HeadOpts.mix
     "( %script.qname; | %style.qname; | %meta.qname;
```

```
      | %link.qname; | %object.qname; )*"
>

<!-- .................  Miscellaneous Elements  .................. -->

<!-- ins and del are used to denote editing changes
-->
<!ENTITY % Edit.class "| %ins.qname; | %del.qname;" >

<!-- script and noscript are used to contain scripts
     and alternative content
-->
<!ENTITY % Script.class "| %script.qname; | %noscript.qname;" >

<!ENTITY % Misc.extra "" >

<!-- These elements are neither block nor inline, and can
     essentially be used anywhere in the document body.
-->
<!ENTITY % Misc.class
     "%Edit.class;
      %Script.class;
      %Misc.extra;"
>

<!-- ....................  Inline Elements  ..................... -->

<!ENTITY % InlStruct.class "%br.qname; | %span.qname;" >

<!ENTITY % InlPhras.class
     "| %em.qname; | %strong.qname; | %dfn.qname; | %code.qname;
      | %samp.qname; | %kbd.qname; | %var.qname; | %cite.qname;
      | %abbr.qname; | %acronym.qname; | %q.qname;" >

<!ENTITY % InlPres.class
     "| %tt.qname; | %i.qname; | %b.qname; | %big.qname;
      | %small.qname; | %sub.qname; | %sup.qname;" >

<!ENTITY % I18n.class "| %bdo.qname;" >

<!ENTITY % Anchor.class "| %a.qname;" >

<!ENTITY % InlSpecial.class
     "| %img.qname; | %map.qname;
      | %object.qname;" >

<!ENTITY % InlForm.class
     "| %input.qname; | %select.qname; | %textarea.qname;
      | %label.qname; | %button.qname;" >

<!ENTITY % Inline.extra "" >

<!ENTITY % Ruby.class "| %ruby.qname;" >

<!-- %Inline.class; includes all inline elements,
     used as a component in mixes
-->
```

```
<!ENTITY % Inline.class
     "%InlStruct.class;
      %InlPhras.class;
      %InlPres.class;
      %I18n.class;
      %Anchor.class;
      %InlSpecial.class;
      %InlForm.class;
      %Ruby.class;
      %Inline.extra;"
>

<!-- %InlNoRuby.class; includes all inline elements
     except ruby, used as a component in mixes
-->
<!ENTITY % InlNoRuby.class
     "%InlStruct.class;
      %InlPhras.class;
      %InlPres.class;
      %I18n.class;
      %Anchor.class;
      %InlSpecial.class;
      %InlForm.class;
      %Inline.extra;"
>

<!-- %NoRuby.content; includes all inlines except ruby
-->
<!ENTITY % NoRuby.content
     "( #PCDATA
      | %InlNoRuby.class;
      %Misc.class; )*"
>

<!-- %InlNoAnchor.class; includes all non-anchor inlines,
     used as a component in mixes
-->
<!ENTITY % InlNoAnchor.class
     "%InlStruct.class;
      %InlPhras.class;
      %InlPres.class;
      %I18n.class;
      %InlSpecial.class;
      %InlForm.class;
      %Ruby.class;
      %Inline.extra;"
>

<!-- %InlNoAnchor.mix; includes all non-anchor inlines
-->
<!ENTITY % InlNoAnchor.mix
     "%InlNoAnchor.class;
      %Misc.class;"
>

<!-- %Inline.mix; includes all inline elements, including %Misc.class;
-->
```

```
<!ENTITY % Inline.mix
     "%Inline.class;
      %Misc.class;"
>

<!-- .....................  Block Elements  ..................... -->

<!-- In the HTML 4.0 DTD, heading and list elements were included
     in the %block; parameter entity. The %Heading.class; and
     %List.class; parameter entities must now be included explicitly
     on element declarations where desired.
-->

<!ENTITY % Heading.class
     "%h1.qname; | %h2.qname; | %h3.qname;
      | %h4.qname; | %h5.qname; | %h6.qname;" >

<!ENTITY % List.class "%ul.qname; | %ol.qname; | %dl.qname;" >

<!ENTITY % Table.class "| %table.qname;" >

<!ENTITY % Form.class  "| %form.qname;" >

<!ENTITY % Fieldset.class  "| %fieldset.qname;" >

<!ENTITY % BlkStruct.class "%p.qname; | %div.qname;" >

<!ENTITY % BlkPhras.class
     "| %pre.qname; | %blockquote.qname; | %address.qname;" >

<!ENTITY % BlkPres.class "| %hr.qname;" >

<!ENTITY % BlkSpecial.class
     "%Table.class;
      %Form.class;
      %Fieldset.class;"
>

<!ENTITY % Block.extra "" >

<!-- %Block.class; includes all block elements,
     used as an component in mixes
-->
<!ENTITY % Block.class
     "%BlkStruct.class;
      %BlkPhras.class;
      %BlkPres.class;
      %BlkSpecial.class;
      %Block.extra;"
>

<!-- %Block.mix; includes all block elements plus %Misc.class;
-->
<!ENTITY % Block.mix
     "%Heading.class;
      | %List.class;
      | %Block.class;
```

```
      %Misc.class;"
>

<!-- .................  All Content Elements  .................. -->

<!-- %Flow.mix; includes all text content, block and inline
-->
<!ENTITY % Flow.mix
     "%Heading.class;
      | %List.class;
      | %Block.class;
      | %Inline.class;
      %Misc.class;"
>

<!-- end of xhtml11-model-1.mod -->
```

D. XHTML 1.1 XML Schema Definition

This appendix is *normative*.

D.1. XHTML 1.1 Schema Driver

This section contains the driver for the XHTML 1.1 document type implementation as an XML Schema. It relies upon XHTML module implementations defined in [XHTMLMOD [p.13]] and in [RUBY [p.13]].

```
<?xml version="1.0" encoding="UTF-8"?>
<xs:schema
    xmlns:xs="http://www.w3.org/2001/XMLSchema"
    targetNamespace="http://www.w3.org/1999/xhtml"
    xmlns:xh11d="http://www.w3.org/1999/xhtml/datatypes/"
    xmlns="http://www.w3.org/1999/xhtml"
    elementFormDefault="qualified" >
    <xs:annotation>
        <xs:documentation>
      This is the XML Schema driver for XHTML 1.1.
      Please use this namespace for XHTML elements:

          "http://www.w3.org/1999/xhtml"

      $Id: xhtml11.ps,v 1.1 2008/02/13 16:19:41 smccarro Exp $
    </xs:documentation>
        <xs:documentation source="xhtml-copyright-1.xsd"/>
    </xs:annotation>
    <xs:annotation>
        <xs:documentation>
      This is XHTML, a reformulation of HTML as a modular XML application
      The Extensible HyperText Markup Language (XHTML)
      Copyright &#169;1998-2007 World Wide Web Consortium
      (Massachusetts Institute of Technology, European Research Consortium
       for Informatics and Mathematics, Keio University).
      All Rights Reserved.

      Permission to use, copy, modify and distribute the XHTML Schema
      modules and their accompanying xs:documentation for any purpose
      and without fee is hereby granted in perpetuity, provided that the above
      copyright notice and this paragraph appear in all copies.
      The copyright holders make no representation about the suitability of
      these XML Schema modules for any purpose.

      They are provided "as is" without expressed or implied warranty.
    </xs:documentation>
    </xs:annotation>
    <xs:annotation>
        <xs:documentation>
      This is the Schema Driver file for XHTML1.1
      Document Type

     This schema
        + imports external schemas (xml.xsd)
```

```
    + refedines (and include)s schema modules for XHTML1.1 Document Type.
    + includes Schema for Named content model for the
      XHTML1.1 Document Type

    XHTML1.1 Document Type includes the following Modules
       XHTML Core modules (Required for XHTML Family Conformance)
        +  text
        +  hypertext
        +  lists
        +  structure
       Other XHTML modules
        +  Edit
        +  Bdo
        +  Presentational
        +  Link
        +  Meta
        +  Base
        +  Scripting
        +  Style
        +  Image
        +  Applet
        +  Object
        +  Param (Applet/Object modules require Param Module)
        +  Tables
        +  Forms
        +  Client side image maps
        +  Server side image maps
        +  Ruby
</xs:documentation>
</xs:annotation>
<xs:import
    namespace="http://www.w3.org/XML/1998/namespace"
    schemaLocation="http://www.w3.org/2001/xml.xsd">
    <xs:annotation>
        <xs:documentation>
     This import brings in the XML namespace attributes
     The XML attributes are used by various modules.
   </xs:documentation>
    </xs:annotation>
</xs:import>
<xs:include
    schemaLocation="xhtml11-model-1.xsd">
    <xs:annotation>
        <xs:documentation>
    Document Model module for the XHTML1.1 Document Type.
    This schema file defines all named models used by XHTML
    Modularization Framework for XHTML1.1 Document Type
  </xs:documentation>
    </xs:annotation>
</xs:include>
<xs:import
    namespace="http://www.w3.org/1999/xhtml/datatypes/"
    schemaLocation="xhtml-datatypes-1.xsd"/>
<xs:include
    schemaLocation="xhtml11-modules-1.xsd">
    <xs:annotation>
        <xs:documentation>
```

```
            Schema that includes all modules (and redefinitions)
            for XHTML1.1 Document Type.
               </xs:documentation>
            </xs:annotation>
        </xs:include>
    </xs:schema>
```

D.2. XHTML 1.1 Schema Modules

XHTML Family implementations using XML Schema are required to provide their own schema module that imports the required modules from XHTML Modularization.

```
<?xml version="1.0" encoding="UTF-8"?>
<xs:schema xmlns:xs="http://www.w3.org/2001/XMLSchema"
           elementFormDefault="qualified"
           xmlns:xh11d="http://www.w3.org/1999/xhtml/datatypes/" >
    <xs:import namespace="http://www.w3.org/1999/xhtml/datatypes/"
               schemaLocation="xhtml-datatypes-1.xsd" />

    <xs:annotation>
        <xs:documentation>
      This schema includes all modules for XHTML1.1 Document Type.
      $Id: xhtml11.ps,v 1.1 2008/02/13 16:19:41 smccarro Exp $
    </xs:documentation>
        <xs:documentation source="xhtml-copyright-1.xsd"/>
    </xs:annotation>
    <xs:annotation>
        <xs:documentation>
     This schema includes all modules (and redefinitions)
     for XHTML1.1 Document Type.
     XHTML1.1 Document Type includes the following Modules

       XHTML Core modules (Required for XHTML Family Conformance)
            +  text
            +  hypertext
            +  lists
            +  structure

       Other XHTML modules
            +  Edit
            +  Bdo
            +  Presentational
            +  Link
            +  Meta
            +  Base
            +  Scripting
            +  Style
            +  Image
            +  Applet
            +  Object
            +  Param (Applet/Object modules require Param Module)
            +  Tables
            +  Target
            +  Forms
            +  Client side image maps
            +  Server side image maps

    </xs:documentation>
    </xs:annotation>
    <xs:include schemaLocation="xhtml-framework-1.xsd">
        <xs:annotation>
            <xs:documentation>
        Schema Framework Component Modules:
            +  notations
            +  datatypes
            +  common attributes
            +  character entities
      </xs:documentation>
            <xs:documentation source="http://www.w3.org/TR/xhtml-modularization/abstract_modules.html#s_commonatts"/>
        </xs:annotation>
    </xs:include>
    <xs:include schemaLocation="xhtml-text-1.xsd">
        <xs:annotation>
            <xs:documentation>
        Text module

        The Text module includes declarations for all core
        text container elements and their attributes.

            +  block phrasal
            +  block structural
            +  inline phrasal
            +  inline structural

        Elements defined here:
```

```
      * address, blockquote, pre, h1, h2, h3, h4, h5, h6
      * div, p
      * abbr, acronym, cite, code, dfn, em, kbd, q, samp, strong, var
      * br, span
  </xs:documentation>
        <xs:documentation source="http://www.w3.org/TR/2001/REC-xhtml-modularization-20010410/abstract_modules.html#s_textmodule"/>
    </xs:annotation>
</xs:include>
<xs:redefine schemaLocation="xhtml-hypertext-1.xsd">
    <xs:annotation>
        <xs:documentation>
     Hypertext module

     Elements defined here:
      * a
  </xs:documentation>
        <xs:documentation source="http://www.w3.org/TR/2001/REC-xhtml-modularization-20010410/abstract_modules.html#s_hypertextmodule"/>
    </xs:annotation>
    <xs:attributeGroup name="xhtml.a.attlist">
        <xs:attributeGroup ref="xhtml.a.attlist"/>
        <xs:attributeGroup ref="xhtml.a.csim.attlist">
            <xs:annotation>
                <xs:documentation>
          Redefinition by Client Side Image Map Module
        </xs:documentation>
            </xs:annotation>
        </xs:attributeGroup>
        <xs:attributeGroup ref="xhtml.a.events.attlist">
            <xs:annotation>
                <xs:documentation>
          Redefinition by XHTML Event Attribute Module
        </xs:documentation>
            </xs:annotation>
        </xs:attributeGroup>
        <xs:attributeGroup ref="xhtml.a.target.attlist">
            <xs:annotation>
                <xs:documentation>
          Target Module - A Attribute Additions
        </xs:documentation>
            </xs:annotation>
        </xs:attributeGroup>
    </xs:attributeGroup>
</xs:redefine>
<xs:include schemaLocation="xhtml-list-1.xsd">
    <xs:annotation>
        <xs:documentation>
    Lists module

    Elements defined here:
      * dt, dd, dl, ol, ul, li
  </xs:documentation>
        <xs:documentation source="http://www.w3.org/TR/2001/REC-xhtml-modularization-20010410/abstract_modules.html#s_listmodule"/>
    </xs:annotation>
</xs:include>
<xs:redefine schemaLocation="xhtml-struct-1.xsd">
    <xs:annotation>
        <xs:documentation>
    Structural module

    Elements defined here:
      * title, head, body, html
  </xs:documentation>
        <xs:documentation source="http://www.w3.org/TR/2001/REC-xhtml-modularization-20010410/abstract_modules.html#s_structuremodule"/>
    </xs:annotation>
    <xs:attributeGroup name="xhtml.version.attrib">
        <xs:annotation>
            <xs:documentation>
        Redefinition by the XHTML11 Markup (for value of version attr)
     </xs:documentation>
        </xs:annotation>
        <xs:attribute name="version" type="xh11d:FPI" fixed="-//W3C//DTD XHTML 1.1//EN"/>
    </xs:attributeGroup>
    <xs:attributeGroup name="xhtml.body.attlist">
        <xs:attributeGroup ref="xhtml.body.attlist">
            <xs:annotation>
                <xs:documentation>
          Original Body Attlist
        </xs:documentation>
            </xs:annotation>
        </xs:attributeGroup>
        <xs:attributeGroup ref="xhtml.body.events.attlist">
            <xs:annotation>
                <xs:documentation>
          Redefinition by XHTML Event Attribute Module
        </xs:documentation>
            </xs:annotation>
        </xs:attributeGroup>
    </xs:attributeGroup>
</xs:redefine>
<xs:include schemaLocation="xhtml-edit-1.xsd">
    <xs:annotation>
        <xs:documentation>
    Edit module

    Elements defined here:
      * ins, del
```

```
  </xs:documentation>
        <xs:documentation source="http://www.w3.org/TR/xhtml-modularization/abstract_modules.html#s_editmodule"/>
    </xs:annotation>
</xs:include>
<xs:include schemaLocation="xhtml-bdo-1.xsd">
    <xs:annotation>
        <xs:documentation>
    Bidirectional element module

    Elements defined here:
      * bdo
  </xs:documentation>
        <xs:documentation source="http://www.w3.org/TR/xhtml-modularization/abstract_modules.html#s_bdomodule"/>
    </xs:annotation>
</xs:include>
<xs:include schemaLocation="xhtml-pres-1.xsd">
    <xs:annotation>
        <xs:documentation>
    Presentational module

     Elements defined here:
       * hr, b, big, i, small,sub, sup, tt
  </xs:documentation>
        <xs:documentation source="http://www.w3.org/TR/xhtml-modularization/abstract_modules.html#s_presentationmodule"/>
    </xs:annotation>
</xs:include>
<xs:include schemaLocation="xhtml-link-1.xsd">
    <xs:annotation>
        <xs:documentation>
            Link module

            Elements defined here:
               * link
        </xs:documentation>
        <xs:documentation source="http://www.w3.org/TR/xhtml-modularization/abstract_modules.html#s_linkmodule"/>
    </xs:annotation>
    <xs:attributeGroup name="xhtml.link.attlist">
        <xs:annotation>
            <xs:documentation>
        Changes to XHTML Link Attlist
      </xs:documentation>
        </xs:annotation>
        <xs:attributeGroup ref="xhtml.link.attlist">
            <xs:annotation>
                <xs:documentation>
            Original Link Attributes (declared in Link Module)
         </xs:documentation>
            </xs:annotation>
        </xs:attributeGroup>
        <xs:attributeGroup ref="xhtml.link.target.attlist">
            <xs:annotation>
                <xs:documentation>
                  XHTML Target Module - Attribute additions
                 </xs:documentation>
            </xs:annotation>
        </xs:attributeGroup>
    </xs:attributeGroup>
</xs:include>
<xs:include schemaLocation="xhtml-meta-1.xsd">
    <xs:annotation>
        <xs:documentation>
    Meta module

    Elements defined here:
    * meta
  </xs:documentation>
        <xs:documentation source="http://www.w3.org/TR/xhtml-modularization/abstract_modules.html#s_metamodule"/>
    </xs:annotation>
</xs:include>
<xs:include schemaLocation="xhtml-base-1.xsd">
    <xs:annotation>
        <xs:documentation>
    Base module

    Elements defined here:
      * base
  </xs:documentation>
        <xs:documentation source="http://www.w3.org/TR/xhtml-modularization/abstract_modules.html#s_basemodule"/>
    </xs:annotation>
    <xs:attributeGroup name="xhtml.base.attlist">
        <xs:annotation>
            <xs:documentation>
        Changes to XHTML base Attlist
      </xs:documentation>
        </xs:annotation>
        <xs:attributeGroup ref="xhtml.base.attlist">
            <xs:annotation>
                <xs:documentation>
            Original Base Attributes (declared in Base Module)
         </xs:documentation>
            </xs:annotation>
        </xs:attributeGroup>
        <xs:attributeGroup ref="xhtml.base.target.attlist">
            <xs:annotation>
                <xs:documentation>
            XHTML Target Module - Attribute additions
```

```
         </xs:documentation>
            </xs:annotation>
        </xs:attributeGroup>
    </xs:attributeGroup>
</xs:include>
<xs:include schemaLocation="xhtml-script-1.xsd">
    <xs:annotation>
        <xs:documentation>
    Scripting module

    Elements defined here:
      * script, noscript
  </xs:documentation>
        <xs:documentation source="http://www.w3.org/TR/xhtml-modularization/abstract_modules.html#s_scriptmodule"/>
    </xs:annotation>
</xs:include>
<xs:include schemaLocation="xhtml-style-1.xsd">
    <xs:annotation>
        <xs:documentation>
    Style module

    Elements defined here:
      * style
  </xs:documentation>
        <xs:documentation source="http://www.w3.org/TR/xhtml-modularization/abstract_modules.html#s_stylemodule"/>
    </xs:annotation>
</xs:include>
<xs:include schemaLocation="xhtml-inlstyle-1.xsd">
    <xs:annotation>
        <xs:documentation>
    Style attribute module

    Attribute defined here:
      * style
  </xs:documentation>
        <xs:documentation source="http://www.w3.org/TR/xhtml-modularization/abstract_modules.html#s_styleattributemodule"/>
    </xs:annotation>
</xs:include>
<xs:redefine schemaLocation="xhtml-image-1.xsd">
    <xs:annotation>
        <xs:documentation>
    Image module

    Elements defined here:
      * img
  </xs:documentation>
        <xs:documentation source="http://www.w3.org/TR/xhtml-modularization/abstract_modules.html#s_imagemodule"/>
    </xs:annotation>
    <xs:attributeGroup name="xhtml.img.attlist">
        <xs:attributeGroup ref="xhtml.img.attlist">
            <xs:annotation>
                <xs:documentation>
            Original Image Attributes (in Image Module)
         </xs:documentation>
            </xs:annotation>
        </xs:attributeGroup>
        <xs:attributeGroup ref="xhtml.img.csim.attlist">
            <xs:annotation>
                <xs:documentation>
            Redefinition by Client Side Image Map Module
         </xs:documentation>
            </xs:annotation>
        </xs:attributeGroup>
        <xs:attributeGroup ref="xhtml.img.ssimap.attlist">
            <xs:annotation>
                <xs:documentation>
            Redefinition by Server Side Image Module
         </xs:documentation>
            </xs:annotation>
        </xs:attributeGroup>
    </xs:attributeGroup>
</xs:redefine>
<xs:redefine schemaLocation="xhtml-csismap-1.xsd">
    <xs:annotation>
        <xs:documentation>
    Client-side mage maps module

    Elements defined here:
      * area, map
  </xs:documentation>
        <xs:documentation source="http://www.w3.org/TR/xhtml-modularization/abstract_modules.html#s_imapmodule"/>
    </xs:annotation>
    <xs:attributeGroup name="xhtml.area.attlist">
        <xs:attributeGroup ref="xhtml.area.attlist">
            <xs:annotation>
                <xs:documentation>
            Original Area Attributes (in CSI Module)
         </xs:documentation>
            </xs:annotation>
        </xs:attributeGroup>
        <xs:attributeGroup ref="xhtml.area.events.attlist">
            <xs:annotation>
                <xs:documentation>
            Redefinition by Events Attribute Module
         </xs:documentation>
            </xs:annotation>
```

```
        </xs:attributeGroup>
        <xs:attributeGroup ref="xhtml.area.target.attlist">
            <xs:annotation>
                <xs:documentation>
            Target Module - Area Attribute Additions
         </xs:documentation>
            </xs:annotation>
        </xs:attributeGroup>
    </xs:attributeGroup>
</xs:redefine>
<xs:include schemaLocation="xhtml-ssismap-1.xsd">
    <xs:annotation>
        <xs:documentation>
   Server-side image maps module

    Attributes defined here:
      * ismap on img
  </xs:documentation>
        <xs:documentation source="http://www.w3.org/TR/xhtml-modularization/abstract_modules.html#s_servermapmodule"/>
    </xs:annotation>
</xs:include>
<xs:redefine schemaLocation="xhtml-object-1.xsd">
    <xs:annotation>
        <xs:documentation>
    Object module

    Elements defined here:
      * object
  </xs:documentation>
        <xs:documentation source="http://www.w3.org/TR/xhtml-modularization/abstract_modules.html#s_objectmodule"/>
    </xs:annotation>
    <xs:attributeGroup name="xhtml.object.attlist">
        <xs:attributeGroup ref="xhtml.object.attlist">
            <xs:annotation>
                <xs:documentation>
            Original Object Attlist
          </xs:documentation>
            </xs:annotation>
        </xs:attributeGroup>
        <xs:attributeGroup ref="xhtml.object.csim.attlist">
            <xs:annotation>
                <xs:documentation>
            Redefinition by Client Image Map Module
          </xs:documentation>
            </xs:annotation>
        </xs:attributeGroup>
    </xs:attributeGroup>
</xs:redefine>
<xs:include schemaLocation="xhtml-param-1.xsd">
    <xs:annotation>
        <xs:documentation>
    Param module

    Elements defined here:
      * param
  </xs:documentation>
    </xs:annotation>
</xs:include>
<xs:include schemaLocation="xhtml-table-1.xsd">
    <xs:annotation>
        <xs:documentation>
    Tables module

    Elements defined here:
      * table, caption, thead, tfoot, tbody, colgroup, col, tr, th, td
  </xs:documentation>
        <xs:documentation source="http://www.w3.org/TR/xhtml-modularization/abstract_modules.html#s_tablemodule"/>
    </xs:annotation>
</xs:include>
<xs:redefine schemaLocation="xhtml-form-1.xsd">
    <xs:annotation>
        <xs:documentation>
        Forms module

        Elements defined here:
          * form, label, input, select, optgroup, option,
          * textarea, fieldset, legend, button
      </xs:documentation>
        <xs:documentation source="http://www.w3.org/TR/xhtml-modularization/abstract_modules.html#s_extformsmodule"/>
    </xs:annotation>
    <xs:attributeGroup name="xhtml.form.attlist">
        <xs:annotation>
            <xs:documentation>
        Changes to XHTML Form Attlist
      </xs:documentation>
        </xs:annotation>
        <xs:attributeGroup ref="xhtml.form.attlist">
            <xs:annotation>
                <xs:documentation>
            Original Form Attributes (declared in Forms Module)
         </xs:documentation>
            </xs:annotation>
        </xs:attributeGroup>
        <xs:attributeGroup ref="xhtml.form.events.attlist">
            <xs:annotation>
                <xs:documentation>
```

```
        XHTML Events Module - Attribute additions
     </xs:documentation>
        </xs:annotation>
    </xs:attributeGroup>
    <xs:attributeGroup ref="xhtml.form.target.attlist">
        <xs:annotation>
            <xs:documentation>
              XHTML Target Module - Attribute additions
             </xs:documentation>
        </xs:annotation>
    </xs:attributeGroup>
</xs:attributeGroup>
<xs:attributeGroup name="xhtml.input.attlist">
    <xs:annotation>
        <xs:documentation>
    Changes to XHTML Form Input Element
  </xs:documentation>
    </xs:annotation>
    <xs:attributeGroup ref="xhtml.input.attlist">
        <xs:annotation>
            <xs:documentation>
        Original Input Attributes (in Forms Module)
     </xs:documentation>
        </xs:annotation>
    </xs:attributeGroup>
    <xs:attributeGroup ref="xhtml.input.csim.attlist">
        <xs:annotation>
            <xs:documentation>
        Redefinition by Client Side Image Map Module
     </xs:documentation>
        </xs:annotation>
    </xs:attributeGroup>
    <xs:attributeGroup ref="xhtml.input.ssimap.attlist">
        <xs:annotation>
            <xs:documentation>
        Redefinition by Server Side Image Map Module
     </xs:documentation>
        </xs:annotation>
    </xs:attributeGroup>
    <xs:attributeGroup ref="xhtml.input.events.attlist">
        <xs:annotation>
            <xs:documentation>
       Redefinition by Event Attribute Module
     </xs:documentation>
        </xs:annotation>
    </xs:attributeGroup>
</xs:attributeGroup>
<xs:attributeGroup name="xhtml.label.attlist">
    <xs:attributeGroup ref="xhtml.label.attlist">
        <xs:annotation>
            <xs:documentation>
        Original Label Attributes (in Forms Module)
     </xs:documentation>
        </xs:annotation>
    </xs:attributeGroup>
    <xs:attributeGroup ref="xhtml.label.events.attlist">
        <xs:annotation>
            <xs:documentation>
       Redefinition by Event Attribute Module
     </xs:documentation>
        </xs:annotation>
    </xs:attributeGroup>
</xs:attributeGroup>
<xs:attributeGroup name="xhtml.select.attlist">
    <xs:attributeGroup ref="xhtml.select.attlist">
        <xs:annotation>
            <xs:documentation>
        Original Select Attributes (in Forms Module)
     </xs:documentation>
        </xs:annotation>
    </xs:attributeGroup>
    <xs:attributeGroup ref="xhtml.select.events.attlist">
        <xs:annotation>
            <xs:documentation>
       Redefinition by Event Attribute Module
     </xs:documentation>
        </xs:annotation>
    </xs:attributeGroup>
</xs:attributeGroup>
<xs:attributeGroup name="xhtml.textarea.attlist">
    <xs:attributeGroup ref="xhtml.textarea.attlist">
        <xs:annotation>
            <xs:documentation>
        Original TextArea Attributes (in Forms Module)
     </xs:documentation>
        </xs:annotation>
    </xs:attributeGroup>
    <xs:attributeGroup ref="xhtml.textarea.events.attlist">
        <xs:annotation>
            <xs:documentation>
       Redefinition by Event Attribute Module
     </xs:documentation>
        </xs:annotation>
    </xs:attributeGroup>
</xs:attributeGroup>
<xs:attributeGroup name="xhtml.button.attlist">
```

```
            <xs:attributeGroup ref="xhtml.button.attlist">
                <xs:annotation>
                    <xs:documentation>
                   Original Button Attributes (in Forms Module)
                 </xs:documentation>
                    </xs:annotation>
                </xs:attributeGroup>
                <xs:attributeGroup ref="xhtml.button.events.attlist">
                    <xs:annotation>
                        <xs:documentation>
                  Redefinition by Event Attribute Module
                 </xs:documentation>
                    </xs:annotation>
                </xs:attributeGroup>
            </xs:attributeGroup>
        </xs:redefine>
        <xs:include schemaLocation="xhtml-ruby-basic-1.xsd">
            <xs:annotation>
                <xs:documentation>
            Ruby module

            Elements defined here:
              * ruby, rbc, rtc, rb, rt, rp

            Note that either Ruby or Basic Ruby should be used but not both
          </xs:documentation>
                <xs:documentation source="http://www.w3.org/TR/2001/REC-ruby-20010531/#simple-ruby1"/>
            </xs:annotation>
        </xs:include>
        <xs:include schemaLocation="xhtml-events-1.xsd">
            <xs:annotation>
                <xs:documentation>
            XHTML Events Modules

            Attributes defined here:
              XHTML Event Types
          </xs:documentation>
                <xs:documentation source="http://www.w3.org/TR/xhtml-modularization/abstract_modules.html#s_intrinsiceventsmodule"/>
            </xs:annotation>
        </xs:include>
    </xs:schema>
```

D.3. XHTML 1.1 Customizations

An XHTML Family Document Type (such as XHTML 1.1) must define the content model that it uses. This is done through a separate content model module that is instantiated by the XHTML Modular Framework. The content model module and the XHTML 1.1 Driver (above) work together to customize the module implementations to the document type's specific requirements. The content model module for XHTML 1.1 is defined below:

```
<?xml version="1.0" encoding="UTF-8"?>
<xs:schema
    xmlns:xs="http://www.w3.org/2001/XMLSchema"
    xmlns:xh11d="http://www.w3.org/1999/xhtml/datatypes/"
    elementFormDefault="qualified" >
    <xs:import
        namespace="http://www.w3.org/1999/xhtml/datatypes/"
        schemaLocation="xhtml-datatypes-1.xsd"/>
    <xs:annotation>
        <xs:documentation>
            This is the XML Schema module of common content models for XHTML11

            $Id: xhtml11.ps,v 1.1 2008/02/13 16:19:41 smccarro Exp $
        </xs:documentation>
        <xs:documentation source="xhtml-copyright-1.xsd"/>
    </xs:annotation>
    <xs:annotation>
        <xs:documentation>
            XHTML Document Model
            This module describes the groupings of elements/attributes
            that make up common content models for XHTML elements.
```

```
            XHTML has following basic content models:
               xhtml.Inline.mix; character-level elements
               xhtml.Block.mix; block-like elements, e.g., paragraphs and lists
               xhtml.Flow.mix; any block or inline elements
               xhtml.HeadOpts.mix; Head Elements
               xhtml.InlinePre.mix; Special class for pre content model
               xhtml.InlineNoAnchor.mix; Content model for Anchor

            Any groups declared in this module may be used to create
            element content models, but the above are considered 'global'
            (insofar as that term applies here). XHTML has the
            following Attribute Groups
               xhtml.Core.extra.attrib
               xhtml.I18n.extra.attrib
               xhtml.Common.extra

            The above attribute Groups are considered Global
        </xs:documentation>
    </xs:annotation>
    <xs:attributeGroup
        name="xhtml.I18n.extra.attrib">
        <xs:annotation>
            <xs:documentation> Extended I18n attribute </xs:documentation>
        </xs:annotation>
        <xs:attributeGroup
            ref="xhtml.dir.attrib">
            <xs:annotation>
                <xs:documentation>
                "dir" Attribute from Bi Directional Text (bdo) Module
                </xs:documentation>
            </xs:annotation>
        </xs:attributeGroup>
    </xs:attributeGroup>
    <xs:attributeGroup
        name="xhtml.Common.extra">
        <xs:annotation>
            <xs:documentation> Extended Common Attributes </xs:documentation>
        </xs:annotation>
        <xs:attributeGroup
            ref="xhtml.style.attrib">
            <xs:annotation>
                <xs:documentation>
                "style" attribute from Inline Style Module
                </xs:documentation>
            </xs:annotation>
        </xs:attributeGroup>
        <xs:attributeGroup ref="xhtml.Events.attrib">
            <xs:annotation>
                <xs:documentation>
                Attributes from Events Module
                </xs:documentation>
            </xs:annotation>
        </xs:attributeGroup>
    </xs:attributeGroup>
    <xs:attributeGroup
        name="xhtml.Core.extra.attrib">
        <xs:annotation>
```

```
        <xs:documentation> Extend Core Attributes </xs:documentation>
    </xs:annotation>
</xs:attributeGroup>
<xs:attributeGroup
    name="xhtml.Global.core.extra.attrib">
    <xs:annotation>
        <xs:documentation> Extended Global Core Attributes </xs:documentation>
    </xs:annotation>
</xs:attributeGroup>
<xs:attributeGroup
    name="xhtml.Global.I18n.extra.attrib">
    <xs:annotation>
        <xs:documentation> Extended Global I18n attributes </xs:documentation>
    </xs:annotation>
</xs:attributeGroup>
<xs:attributeGroup
    name="xhtml.Global.Common.extra">
    <xs:annotation>
        <xs:documentation> Extended Global Common Attributes </xs:documentation>
    </xs:annotation>
</xs:attributeGroup>
<xs:group
    name="xhtml.Head.extra">
    <xs:sequence/>
</xs:group>
<xs:group
    name="xhtml.HeadOpts.mix">
    <xs:choice>
        <xs:element
            name="script"
            type="xhtml.script.type"/>
        <xs:element
            name="style"
            type="xhtml.style.type"/>
        <xs:element
            name="meta"
            type="xhtml.meta.type"/>
        <xs:element
            name="link"
            type="xhtml.link.type"/>
        <xs:element
            name="object"
            type="xhtml.object.type"/>
        <xs:group
            ref="xhtml.Head.extra"/>
    </xs:choice>
</xs:group>
<xs:group
    name="xhtml.head.content">
    <xs:sequence>
        <xs:group
            ref="xhtml.HeadOpts.mix"
            minOccurs="0"
            maxOccurs="unbounded"/>
        <xs:choice>
            <xs:sequence>
                <xs:element
```

```
                        name="title"
                        minOccurs="1"
                        maxOccurs="1"
                        type="xhtml.title.type"/>
                    <xs:group
                        ref="xhtml.HeadOpts.mix"
                        minOccurs="0"
                        maxOccurs="unbounded"/>
                    <xs:sequence
                        minOccurs="0">
                        <xs:element
                            name="base"
                            type="xhtml.base.type"/>
                        <xs:group
                            ref="xhtml.HeadOpts.mix"
                            minOccurs="0"
                            maxOccurs="unbounded"/>
                    </xs:sequence>
                </xs:sequence>
                <xs:sequence>
                    <xs:element
                        name="base"
                        type="xhtml.base.type"
                        minOccurs="1"
                        maxOccurs="1"/>
                    <xs:group
                        ref="xhtml.HeadOpts.mix"
                        minOccurs="0"
                        maxOccurs="unbounded"/>
                    <xs:element
                        name="title"
                        minOccurs="1"
                        maxOccurs="1"
                        type="xhtml.title.type"/>
                    <xs:group
                        ref="xhtml.HeadOpts.mix"
                        minOccurs="0"
                        maxOccurs="unbounded"/>
                </xs:sequence>
            </xs:choice>
        </xs:sequence>
    </xs:group>
    <!--
    ins and del are used to denote editing changes
  -->
    <xs:group
        name="xhtml.Edit.class">
        <xs:choice>
            <xs:element
                name="ins"
                type="xhtml.edit.type"/>
            <xs:element
                name="del"
                type="xhtml.edit.type"/>
        </xs:choice>
    </xs:group>
    <!--
```

```
  script and noscript are used to contain scripts
  and alternative content
-->
  <xs:group
      name="xhtml.Script.class">
      <xs:choice>
          <xs:element
              name="script"
              type="xhtml.script.type"/>
          <xs:element
              name="noscript"
              type="xhtml.noscript.type"/>
      </xs:choice>
  </xs:group>
  <xs:group
      name="xhtml.Misc.extra">
      <xs:sequence/>
  </xs:group>
  <!--
  These elements are neither block nor inline, and can
  essentially be used anywhere in the document body.
-->
  <xs:group
      name="xhtml.Misc.class">
      <xs:choice>
          <xs:group
              ref="xhtml.Edit.class"/>
          <xs:group
              ref="xhtml.Script.class"/>
          <xs:group
              ref="xhtml.Misc.extra"/>
      </xs:choice>
  </xs:group>
  <!-- Inline Elements -->
  <xs:group
      name="xhtml.InlStruct.class">
      <xs:choice>
          <xs:element
              name="br"
              type="xhtml.br.type"/>
          <xs:element
              name="span"
              type="xhtml.span.type"/>
      </xs:choice>
  </xs:group>
  <xs:group
      name="xhtml.InlPhras.class">
      <xs:choice>
          <xs:element
              name="em"
              type="xhtml.em.type"/>
          <xs:element
              name="strong"
              type="xhtml.strong.type"/>
          <xs:element
              name="dfn"
              type="xhtml.dfn.type"/>
```

```
            <xs:element
                name="code"
                type="xhtml.code.type"/>
            <xs:element
                name="samp"
                type="xhtml.samp.type"/>
            <xs:element
                name="kbd"
                type="xhtml.kbd.type"/>
            <xs:element
                name="var"
                type="xhtml.var.type"/>
            <xs:element
                name="cite"
                type="xhtml.cite.type"/>
            <xs:element
                name="abbr"
                type="xhtml.abbr.type"/>
            <xs:element
                name="acronym"
                type="xhtml.acronym.type"/>
            <xs:element
                name="q"
                type="xhtml.q.type"/>
        </xs:choice>
    </xs:group>
    <xs:group
        name="xhtml.InlPres.class">
        <xs:choice>
            <xs:element
                name="tt"
                type="xhtml.InlPres.type"/>
            <xs:element
                name="i"
                type="xhtml.InlPres.type"/>
            <xs:element
                name="b"
                type="xhtml.InlPres.type"/>
            <xs:element
                name="big"
                type="xhtml.InlPres.type"/>
            <xs:element
                name="small"
                type="xhtml.InlPres.type"/>
            <xs:element
                name="sub"
                type="xhtml.InlPres.type"/>
            <xs:element
                name="sup"
                type="xhtml.InlPres.type"/>
        </xs:choice>
    </xs:group>
    <xs:group
        name="xhtml.I18n.class">
        <xs:sequence>
            <xs:element
                name="bdo"
```

```
            type="xhtml.bdo.type"/>
    </xs:sequence>
</xs:group>
<xs:group
    name="xhtml.Anchor.class">
    <xs:sequence>
        <xs:element
            name="a"
            type="xhtml.a.type"/>
    </xs:sequence>
</xs:group>
<xs:group
    name="xhtml.InlSpecial.class">
    <xs:choice>
        <xs:element
            name="img"
            type="xhtml.img.type"/>
        <xs:element
            name="map"
            type="xhtml.map.type"/>
        <xs:element
            name="object"
            type="xhtml.object.type"/>
    </xs:choice>
</xs:group>
<xs:group
    name="xhtml.InlForm.class">
    <xs:choice>
        <xs:element
            name="input"
            type="xhtml.input.type"/>
        <xs:element
            name="select"
            type="xhtml.select.type"/>
        <xs:element
            name="textarea"
            type="xhtml.textarea.type"/>
        <xs:element
            name="label"
            type="xhtml.label.type"/>
        <xs:element
            name="button"
            type="xhtml.button.type"/>
    </xs:choice>
</xs:group>
<xs:group
    name="xhtml.Inline.extra">
    <xs:sequence/>
</xs:group>
<xs:group
    name="xhtml.Ruby.class">
    <xs:sequence>
        <xs:element
            name="ruby"
            type="xhtml.ruby.type"/>
    </xs:sequence>
</xs:group>
```

```
  <!--
  Inline.class includes all inline elements,
  used as a component in mixes
-->
  <xs:group
      name="xhtml.Inline.class">
      <xs:choice>
          <xs:group
              ref="xhtml.InlStruct.class"/>
          <xs:group
              ref="xhtml.InlPhras.class"/>
          <xs:group
              ref="xhtml.InlPres.class"/>
          <xs:group
              ref="xhtml.I18n.class"/>
          <xs:group
              ref="xhtml.Anchor.class"/>
          <xs:group
              ref="xhtml.InlSpecial.class"/>
          <xs:group
              ref="xhtml.InlForm.class"/>
          <xs:group
              ref="xhtml.Ruby.class"/>
          <xs:group
              ref="xhtml.Inline.extra"/>
      </xs:choice>
  </xs:group>
  <!--
   InlNoRuby.class includes all inline elements
   except ruby
-->
  <xs:group
      name="xhtml.InlNoRuby.class">
      <xs:choice>
          <xs:group
              ref="xhtml.InlStruct.class"/>
          <xs:group
              ref="xhtml.InlPhras.class"/>
          <xs:group
              ref="xhtml.InlPres.class"/>
          <xs:group
              ref="xhtml.I18n.class"/>
          <xs:group
              ref="xhtml.Anchor.class"/>
          <xs:group
              ref="xhtml.InlSpecial.class"/>
          <xs:group
              ref="xhtml.InlForm.class"/>
          <xs:group
              ref="xhtml.Inline.extra"/>
      </xs:choice>
  </xs:group>
  <!--
  InlinePre.mix
  Used as a component in pre model
-->
  <xs:group
```

```
        name="xhtml.InlinePre.mix">
        <xs:choice>
            <xs:group
                ref="xhtml.InlStruct.class"/>
            <xs:group
                ref="xhtml.InlPhras.class"/>
            <xs:element
                name="tt"
                type="xhtml.InlPres.type"/>
            <xs:element
                name="i"
                type="xhtml.InlPres.type"/>
            <xs:element
                name="b"
                type="xhtml.InlPres.type"/>
            <xs:group
                ref="xhtml.I18n.class"/>
            <xs:group
                ref="xhtml.Anchor.class"/>
            <xs:group
                ref="xhtml.Misc.class"/>
            <xs:element
                name="map"
                type="xhtml.map.type"/>
            <xs:group
                ref="xhtml.Inline.extra"/>
        </xs:choice>
    </xs:group>
    <!--
    InlNoAnchor.class includes all non-anchor inlines,
    used as a component in mixes
  -->
    <xs:group
        name="xhtml.InlNoAnchor.class">
        <xs:choice>
            <xs:group
                ref="xhtml.InlStruct.class"/>
            <xs:group
                ref="xhtml.InlPhras.class"/>
            <xs:group
                ref="xhtml.InlPres.class"/>
            <xs:group
                ref="xhtml.I18n.class"/>
            <xs:group
                ref="xhtml.InlSpecial.class"/>
            <xs:group
                ref="xhtml.InlForm.class"/>
            <xs:group
                ref="xhtml.Ruby.class"/>
            <xs:group
                ref="xhtml.Inline.extra"/>
        </xs:choice>
    </xs:group>
    <!--
    InlNoAnchor.mix includes all non-anchor inlines
  -->
    <xs:group
```

```
      name="xhtml.InlNoAnchor.mix">
      <xs:choice>
          <xs:group
              ref="xhtml.InlNoAnchor.class"/>
          <xs:group
              ref="xhtml.Misc.class"/>
      </xs:choice>
  </xs:group>
  <!--
  Inline.mix includes all inline elements, including Misc.class
-->
  <xs:group
      name="xhtml.Inline.mix">
      <xs:choice>
          <xs:group
              ref="xhtml.Inline.class"/>
          <xs:group
              ref="xhtml.Misc.class"/>
      </xs:choice>
  </xs:group>
  <!--
 InlNoRuby.mix includes all of inline.mix elements
 except ruby
-->
  <xs:group
      name="xhtml.InlNoRuby.mix">
      <xs:choice>
          <xs:group
              ref="xhtml.InlNoRuby.class"/>
          <xs:group
              ref="xhtml.Misc.class"/>
      </xs:choice>
  </xs:group>
  <!--
  In the HTML 4 DTD, heading and list elements were included
  in the block group. The Heading.class and
  List.class groups must now be included explicitly
  on element declarations where desired.
-->
  <xs:group
      name="xhtml.Heading.class">
      <xs:choice>
          <xs:element
              name="h1"
              type="xhtml.h1.type"/>
          <xs:element
              name="h2"
              type="xhtml.h2.type"/>
          <xs:element
              name="h3"
              type="xhtml.h3.type"/>
          <xs:element
              name="h4"
              type="xhtml.h4.type"/>
          <xs:element
              name="h5"
              type="xhtml.h5.type"/>
```

```
        <xs:element
            name="h6"
            type="xhtml.h6.type"/>
    </xs:choice>
</xs:group>
<xs:group
    name="xhtml.List.class">
    <xs:choice>
        <xs:element
            name="ul"
            type="xhtml.ul.type"/>
        <xs:element
            name="ol"
            type="xhtml.ol.type"/>
        <xs:element
            name="dl"
            type="xhtml.dl.type"/>
    </xs:choice>
</xs:group>
<xs:group
    name="xhtml.Table.class">
    <xs:choice>
        <xs:element
            name="table"
            type="xhtml.table.type"/>
    </xs:choice>
</xs:group>
<xs:group
    name="xhtml.Form.class">
    <xs:choice>
        <xs:element
            name="form"
            type="xhtml.form.type"/>
    </xs:choice>
</xs:group>
<xs:group
    name="xhtml.Fieldset.class">
    <xs:choice>
        <xs:element
            name="fieldset"
            type="xhtml.fieldset.type"/>
    </xs:choice>
</xs:group>
<xs:group
    name="xhtml.BlkStruct.class">
    <xs:choice>
        <xs:element
            name="p"
            type="xhtml.p.type"/>
        <xs:element
            name="div"
            type="xhtml.div.type"/>
    </xs:choice>
</xs:group>
<xs:group
    name="xhtml.BlkPhras.class">
    <xs:choice>
```

```
            <xs:element
                name="pre"
                type="xhtml.pre.type"/>
            <xs:element
                name="blockquote"
                type="xhtml.blockquote.type"/>
            <xs:element
                name="address"
                type="xhtml.address.type"/>
        </xs:choice>
    </xs:group>
    <xs:group
        name="xhtml.BlkPres.class">
        <xs:sequence>
            <xs:element
                name="hr"
                type="xhtml.hr.type"/>
        </xs:sequence>
    </xs:group>
    <xs:group
        name="xhtml.BlkSpecial.class">
        <xs:choice>
            <xs:group
                ref="xhtml.Table.class"/>
            <xs:group
                ref="xhtml.Form.class"/>
            <xs:group
                ref="xhtml.Fieldset.class"/>
        </xs:choice>
    </xs:group>
    <xs:group
        name="xhtml.Block.extra">
        <xs:sequence/>
    </xs:group>
    <!--
    Block.class includes all block elements,
    used as an component in mixes
  -->
    <xs:group
        name="xhtml.Block.class">
        <xs:choice>
            <xs:group
                ref="xhtml.BlkStruct.class"/>
            <xs:group
                ref="xhtml.BlkPhras.class"/>
            <xs:group
                ref="xhtml.BlkPres.class"/>
            <xs:group
                ref="xhtml.BlkSpecial.class"/>
            <xs:group
                ref="xhtml.Block.extra"/>
        </xs:choice>
    </xs:group>
    <!--
   Block.mix includes all block elements plus %Misc.class;
  -->
    <xs:group
```

```
        name="xhtml.Block.mix">
        <xs:choice>
            <xs:group
                ref="xhtml.Heading.class"/>
            <xs:group
                ref="xhtml.List.class"/>
            <xs:group
                ref="xhtml.Block.class"/>
            <xs:group
                ref="xhtml.Misc.class"/>
        </xs:choice>
    </xs:group>
    <!--
    All Content Elements
    Flow.mix includes all text content, block and inline
    Note that the "any" element included here allows us
    to add data from any other namespace, a necessity
    for compound document creation.
    Note however that it is not possible to add
    to any head level element without further
    modification. To add RDF metadata to the head
    of a document, modify the structure module.
  -->
    <xs:group
        name="xhtml.Flow.mix">
        <xs:choice>
            <xs:group
                ref="xhtml.Heading.class"/>
            <xs:group
                ref="xhtml.List.class"/>
            <xs:group
                ref="xhtml.Block.class"/>
            <xs:group
                ref="xhtml.Inline.class"/>
            <xs:group
                ref="xhtml.Misc.class"/>
        </xs:choice>
    </xs:group>
    <!--
    BlkNoForm.mix includes all non-form block elements,
    plus Misc.class
  -->
    <xs:group
        name="xhtml.BlkNoForm.mix">
        <xs:choice>
            <xs:group
                ref="xhtml.Heading.class"/>
            <xs:group
                ref="xhtml.List.class"/>
            <xs:group
                ref="xhtml.BlkStruct.class"/>
            <xs:group
                ref="xhtml.BlkPhras.class"/>
            <xs:group
                ref="xhtml.BlkPres.class"/>
            <xs:group
                ref="xhtml.Table.class"/>
```

```
            <xs:group
                ref="xhtml.Block.extra"/>
            <xs:group
                ref="xhtml.Misc.class"/>
        </xs:choice>
    </xs:group>
    <xs:element
        name="html"
        type="xhtml.html.type"/>
</xs:schema>
```

E. Acknowledgements

This appendix is *informative*.

This specification was prepared by the W3C HTML Working Group. The members at the time of publication of the first edition were:

- Steven Pemberton, CWI (HTML Working Group Chair)
- Murray Altheim, Sun Microsystems
- Daniel Austin, Mozquito Technologies
- Jonny Axelsson, Opera Software
- Mark Baker, Sun Microsystems
- Tantek Çelik, Microsoft
- Doug Dominiak, Openwave Systems
- Herman Elenbaas, Philips Electronics
- Beth Epperson, Netscape/AOL
- Masayasu Ishikawa, W3C (HTML Activity Lead)
- Shin'ichi Matsui, Panasonic
- Shane McCarron, Applied Testing and Technology
- Ann Navarro, WebGeek, Inc.
- Peter Stark, Ericsson
- Michel Suignard, Microsoft
- Jeremy Wadsworth, Quark Inc.
- Malte Wedel, Mozquito Technologies
- Ted Wugofski, Openwave Systems

The members at the time of publication of the second edition were:

(insert the list here)